



SENATE MOTION

MADAM PRESIDENT:

I move that Senate Bill 303 be amended to read as follows:

- 1 Page 1, delete lines 1 through 17, begin a new paragraph and insert:
2 "SECTION 1. IC 16-44-2-8 IS AMENDED TO READ AS
3 FOLLOWS [EFFECTIVE JULY 1, 2021]: Sec. 8. (a) The inspections
4 and tests made by the state department under this chapter shall be
5 conducted in accordance with the methods outlined by the American
6 Society for Testing and Materials.
7 (b) The inspections and tests as to gasoline, gasohol, and kerosene
8 must reflect the following minimum specifications necessary for the
9 approval of the product:
10 (1) Gasoline or gasohol:
11 (A) Corrosion Test – Method ASTM D-130. A clean copper
12 strip may not show more than extremely slight discoloration
13 when submerged in the gasoline for three (3) hours at one
14 hundred twenty-two (122) degrees Fahrenheit.
15 (B) Distillation Range – Method ASTM D-86. When the
16 thermometer reads one hundred sixty-seven (167) degrees
17 Fahrenheit, not less than ten percent (10%) may be evaporated.
18 When the thermometer reads two hundred eighty-four (284)
19 degrees Fahrenheit, not less than fifty percent (50%) may be
20 evaporated. When the thermometer reads three hundred
21 ninety-two (392) degrees Fahrenheit, not less than ninety
22 percent (90%) may be evaporated. The residue may not exceed
23 two percent (2%). Percent evaporated is found by adding the
24 distillation loss to the amount collected in the receiver at each
25 specification temperature.
26 (C) Sulphur – Method ASTM D-1266 or D-2622. Sulphur may
27 not exceed twenty-five hundredths of one percent (0.25%).

1 (D) Vapor Pressure—Method ASTMD-4953, ASTMD-5191,
 2 or any other ASTM method to determine vapor pressure
 3 approved by the United States Environmental Protection
 4 Agency **apply to this clause and clauses (E) through (G).**
 5 For gasoline, the Reid vapor pressure at one hundred (100)
 6 degrees Fahrenheit may not exceed: ~~the following:~~

7 (i) fifteen (15) pounds per square inch at the normal
 8 barometric pressure at the point of delivery during
 9 ~~November~~, December, January, February, and March;

10 (ii) ~~Fourteen (14)~~ **thirteen and five-tenths (13.5)** pounds
 11 per square inch during April, ~~and~~ October, **and November;**
 12 **(iii) eleven and five-tenths (11.5) pounds per square inch**
 13 **during September 16 through September 30; and**

14 ~~(iii) (iv) Twelve (12)~~ **nine (9)** pounds per square inch during
 15 May, June, July, August, and September **1 through**
 16 **September 15;**

17 **as regulated by the United States Environmental**
 18 **Protection Agency.**

19 (E) **Except as provided in clauses (F) and (G), for gasohol (a**
 20 **blend of gasoline and alcohol); permitted under federal tax**
 21 **requirements); (also known as gasoline-ethanol blend)**
 22 **containing ethanol in a concentration of at least one**
 23 **percent (1%) by volume and not more than fifteen percent**
 24 **(15%) by volume, the vapor pressure may not exceed: the**
 25 **following:**

26 (i) sixteen (16) pounds per square inch during November,
 27 December, January, February, and March;

28 (ii) ~~Fifteen (15)~~ **fourteen and five-tenths (14.5)** pounds per
 29 square inch during April, ~~May~~, and October; **and**

30 **(iii) twelve and five-tenths (12.5) pounds per square inch**
 31 **during September 16 through September 30;**

32 **as regulated by the United States Environmental**
 33 **Protection Agency.**

34 (F) **For gasohol (also known as gasoline-ethanol blend)**
 35 **containing ethanol in a concentration of at least one**
 36 **percent (1%) by volume and less than nine percent (9%)**
 37 **by volume, the vapor pressure may not exceed (iii) Thirteen**
 38 **(13) nine (9) pounds per square inch:**

39 (i) ~~during May 1 June, July, August, and through~~ September
 40 **15 if measured at the terminal; and**

41 (ii) ~~during June 1 through~~ September 15 if measured at
 42 **retail;**

43 **as regulated by the United States Environmental**
 44 **Protection Agency.**

45 (G) **For gasohol (also known as gasoline-ethanol blend)**
 46 **containing ethanol in a concentration of at least nine**

1 **percent (9%) by volume and not more than fifteen percent**
 2 **(15%) by volume, the vapor pressure may not exceed ten**
 3 **(10) pounds per square inch:**

4 **(i) during May 1 through September 15 if measured at**
 5 **the terminal; and**

6 **(ii) during June 1 through September 15 if measured at**
 7 **retail;**

8 **as regulated by the United States Environmental**
 9 **Protection Agency.**

10 ~~(F)~~ **(H)** After July 23, 2004, gasoline may not contain more
 11 than one-half percent (0.5%) of MTBE by volume.

12 (2) Kerosene:

13 (A) Flash Test – Method ASTM D-56. Flash point may not be
 14 lower than one hundred (100) degrees Fahrenheit.

15 (B) For the purpose of this chapter, any petroleum product
 16 designated by name or reference as "kerosene" must meet the
 17 federal specifications for kerosene VV-K-211d in effect on
 18 March 1, 1977.

19 (c) Gasoline, gasohol, and kerosene products that do not comply
 20 with the minimum specifications described in subsection (b) may not
 21 be sold, offered for sale, or used in Indiana.

22 (d) Petroleum products other than gasoline, gasohol, or kerosene
 23 shall be inspected and tested by the methods as are necessary to
 24 determine the contents and characteristics of the product.

25 **(e) Compliant conventional gasoline to which 326 IAC 13-3**
 26 **applies is subject to vapor pressure requirements more stringent**
 27 **than those set forth in subsection (b)(1)(D).**

28 **(f) Compliant conventional gasoline to which 326 IAC 13-3**
 29 **applies and federal reformulated gasoline are subject to vapor**
 30 **pressure requirements more stringent than those set forth in**
 31 **subsection (b)(1)(E) through (b)(1)(G)."**

32 Delete page 2.

33 Page 3, delete lines 1 through 16.

34 Page 3, line 20, delete "alcohol." and insert "**ethanol that includes,**
 35 **by volume, more than ten percent (10%) and not more than fifteen**
 36 **percent (15%) ethanol."**

37 Page 3, line 22, delete "gasohol that" and insert "**gasohol,"**

38 Page 3, line 23, delete "contains more than ten percent (10%)
 39 alcohol by volume,"

40 Page 3, line 24, delete "place on the fuel dispenser where the fuel
 41 selection is made," and insert "**fuel grade selection button,"**

42 Page 3, line 26, delete "a" and insert "**this"**

43 Page 3, line 27, delete "setting forth the following text".

44 Page 3, line 28, delete ""Check" and insert ""**Attention: E15.**
 45 **Check"**

46 Page 3, line 29, after "requirements." insert "**or a similar**

1 **statement approved by the United States Environmental Protection**
2 **Agency."**
(Reference is to SB 303 as printed February 16, 2021.)

Senator MESSMER