

116TH CONGRESS
1ST SESSION

H. R. 1511

To reduce the number of preventable deaths and injuries caused by underride crashes, to improve motor carrier and passenger motor vehicle safety, and for other purposes.

IN THE HOUSE OF REPRESENTATIVES

MARCH 5, 2019

Mr. COHEN (for himself and Mr. DESAULNIER) introduced the following bill; which was referred to the Committee on Transportation and Infrastructure

A BILL

To reduce the number of preventable deaths and injuries caused by underride crashes, to improve motor carrier and passenger motor vehicle safety, and for other purposes.

1 *Be it enacted by the Senate and House of Representa-*
2 *tives of the United States of America in Congress assembled,*

3 **SECTION 1. SHORT TITLE.**

4 This Act may be cited as the “Stop Underrides Act”.

5 **SEC. 2. FINDINGS AND PURPOSES.**

6 (a) FINDINGS.—Congress finds that—

7 (1) underride crashes involving passenger motor
8 vehicles striking and traveling underneath a truck or

1 trailer are a significant public health and safety
2 threat;

3 (2) the National Highway Traffic Safety Ad-
4 ministration has reported that hundreds of prevent-
5 able fatalities and life-threatening injuries have oc-
6 curred as a result of underride crashes;

7 (3) the National Transportation Safety Board
8 has recommended the installation of rear, side, and
9 front underride guards on tractor-trailers and rear
10 and side underride guards on single unit trucks to
11 improve passenger motor vehicle safety; and

12 (4) this Act is introduced in the memory of the
13 thousands of victims of underride crashes, includ-
14 ing—

15 (A) Roya Christine Sadigh, AnnaLeah
16 Karth, Mary Lydia Karth, Roderick Cota,
17 Moonjohn Kim, Corey Moore, Gregg Williams,
18 Guy Champ Crawford, Carl Hall, Michael
19 Higginbotham, Sandra Maddamma, David
20 Mathis, Mary Katherine Mathis, James Moon-
21 ey, Christopher Weigl, Bill Zink, David
22 Magnan, Jasen Swift, Samuel Sierra, Brittany
23 McHargue, Christopher Samuel Padilla, Riley
24 Hein, Erin Alexander, Jordan Hensley, and Ed-
25 ward Hall;

1 (B) those whose catastrophic injuries dra-
2 matically changed their lives, including Julie
3 Magnan, Nancy Meuleners, Joshua Rojas, Maiv
4 Yang, Anita Plantage Bomgaars, and Michael
5 B. Hawkins; and

6 (C) those whose precious lives were cut far
7 too short as a result of preventable underride
8 crashes.

9 (b) PURPOSES.—The purposes of this Act are—

10 (1) to reduce the number of preventable deaths
11 and injuries caused by underride crashes; and

12 (2) to improve motor carrier and passenger
13 motor vehicle safety.

14 **SEC. 3. DEFINITIONS.**

15 Section 30102(a) of title 49, United States Code, is
16 amended—

17 (1) in the matter preceding paragraph (1), by
18 striking “chapter—” and inserting “chapter:”;

19 (2) by redesignating paragraphs (1), (2), (3),
20 (4), (5), (6), (7), (8), (9), (10), (11), (12), and (13)
21 as paragraphs (2), (3), (4), (5), (7), (8), (9), (10),
22 (11), (12), (15), (20), and (22), respectively;

23 (3) by inserting before paragraph (2) (as so re-
24 designated) the following:

1 “(1) ‘comprehensive underride protection sys-
2 tem’ means all of the front underride guards, rear
3 underride guards, or side underride guards, as appli-
4 cable, installed on a motor vehicle.”;

5 (4) by inserting after paragraph (5) (as so re-
6 designated) the following:

7 “(6) ‘front underride guard’ means a device in-
8 stalled on or near the front of a motor vehicle that
9 prevents or limits the distance that a vehicle struck
10 by the vehicle with the device will slide under the
11 front of the striking vehicle.”;

12 (5) by inserting after paragraph (12) (as so re-
13 designated) the following:

14 “(13) ‘passenger motor vehicle’ has the mean-
15 ing given that term in section 32101.

16 “(14) ‘rear underride guard’ means a device in-
17 stalled on or near the rear of a motor vehicle that
18 prevents or limits the distance that the front end of
19 a vehicle striking the rear of the vehicle with the de-
20 vice will slide under the rear of the impacted vehi-
21 cle.”;

22 (6) by inserting after paragraph (15) (as so re-
23 designated) the following:

24 “(16) ‘Secretary’ means the Secretary of Trans-
25 portation.

1 “(17) ‘semi-trailer’ means a trailer, other than
2 a pole trailer, which is designed to rest upon, or be
3 carried by, a motor vehicle.

4 “(18) ‘side underride guard’ means a device in-
5 stalled on or near the side of a motor vehicle that
6 prevents or limits the distance that the front end of
7 a vehicle striking the side of the vehicle with the de-
8 vice will slide under the side of the impacted vehicle.

9 “(19) ‘single unit truck’ means a truck (exclud-
10 ing any attached trailer).”;

11 (7) by inserting after paragraph (20) (as so re-
12 designated) the following:

13 “(21) ‘trailer’ means a vehicle, with or without
14 motive power, that is designed—

15 “(A) to carry persons or property; and

16 “(B) to be drawn by a motor vehicle.”; and

17 (8) by inserting “The term” after the para-
18 graph designation in each of paragraphs (1) through
19 (22) (as so redesignated).

20 **SEC. 4. UNDERRIDE GUARD RULEMAKING.**

21 (a) IN GENERAL.—Subchapter II of chapter 301 of
22 title 49, United States Code, is amended by adding at the
23 end the following:

24 **“§ 30129. Underride guards**

25 “(a) REAR UNDERRIDE GUARDS.—

1 “(1) IN GENERAL.—Not later than 1 year after
2 the date of enactment of this section, the Secretary
3 shall issue a final rule to require the installation of
4 rear underride guards that meet the performance
5 standards described in paragraph (3) on—

6 “(A) any trailer with a gross vehicle weight
7 rating of 10,000 pounds or more that is manu-
8 factured on or after the effective date of the
9 rule;

10 “(B) any semi-trailer with a gross vehicle
11 weight rating of 10,000 pounds or more that is
12 manufactured on or after the effective date of
13 the rule; and

14 “(C) any single unit truck—

15 “(i) the bottom of the carriage of
16 which is greater than 22 inches above the
17 ground;

18 “(ii) with a gross vehicle weight rating
19 of 10,000 pounds or more; and

20 “(iii) that is manufactured on or after
21 the effective date of the rule.

22 “(2) RETRO-FIT REQUIREMENTS.—Not later
23 than 2 years after the date of enactment of this sec-
24 tion, the Secretary shall issue a final rule requiring
25 the installation of rear underride guards that meet

1 the performance standards described in paragraph
2 (3) on—

3 “(A) any trailer with a gross vehicle weight
4 rating of 10,000 pounds or more that is manu-
5 factured before the effective date of the rule
6 under paragraph (1);

7 “(B) any semi-trailer with a gross vehicle
8 weight rating of 10,000 pounds or more that is
9 manufactured before the effective date of the
10 rule under paragraph (1); and

11 “(C) any single unit truck—

12 “(i) the bottom of the carriage of
13 which is greater than 22 inches above the
14 ground;

15 “(ii) with a gross vehicle weight rating
16 of 10,000 pounds or more; and

17 “(iii) that is manufactured before the
18 effective date of the rule under paragraph
19 (1).

20 “(3) PERFORMANCE STANDARDS.—A rear
21 underride guard shall be considered to meet the per-
22 formance standard referred to in paragraphs (1) and
23 (2) if the rear underride guard is able to prevent in-
24 trusion from the body or frame of a vehicle de-
25 scribed in paragraph (1) or (2), as applicable, into

1 the passenger compartment of a passenger motor ve-
2 hicle that contacts the guard while traveling at 35
3 miles per hour, as verified through crash testing
4 while attached to a trailer, after—

5 “(A) an impact in which the passenger ve-
6 hicle impacts the center of the rear of the trail-
7 er, semi-trailer, or single unit truck;

8 “(B) an impact in which 50 percent the
9 width of the passenger vehicle overlaps the rear
10 of the trailer, semi-trailer, or single unit truck;
11 and

12 “(C) an impact in which 30 percent of the
13 width of the passenger vehicle overlaps the rear
14 of the trailer, semi-trailer, or single unit truck.

15 “(4) COMPLIANCE DATES.—

16 “(A) IN GENERAL.—Except as provided in
17 subparagraph (B), compliance with each of the
18 rules issued by the Secretary under paragraphs
19 (1) and (2) shall be required beginning 1 year
20 after the date on which the final rule is pub-
21 lished in the Federal Register.

22 “(B) PHASE-IN.—The Secretary may per-
23 mit a phase-in period (not to exceed 2 years)
24 for the installation of rear underride guards on

1 trailers, semi-trailers, and single unit trucks de-
2 scribed in paragraph (2).

3 “(b) SIDE UNDERRIDE GUARDS.—

4 “(1) IN GENERAL.—Not later than 1 year after
5 the date of enactment of this section, the Secretary
6 shall issue a final rule requiring the installation of
7 side underride guards that meet the performance
8 standards described in paragraph (3) on—

9 “(A) any trailer with a gross vehicle weight
10 rating of 10,000 pounds or more that is manu-
11 factured on or after the effective date of the
12 rule;

13 “(B) any semi-trailer with a gross vehicle
14 weight rating of 10,000 pounds or more that is
15 manufactured on or after the effective date of
16 the rule; and

17 “(C) any single unit truck—

18 “(i) the bottom of the carriage of
19 which is greater than 22 inches above the
20 ground;

21 “(ii) with a gross vehicle weight rating
22 of 10,000 pounds or more; and

23 “(iii) that is manufactured on or after
24 the effective date of the rule.

1 “(2) RETRO-FIT REQUIREMENTS.—Not later
2 than 2 years after the date of enactment of this sec-
3 tion, the Secretary shall issue a final rule requiring
4 the installation of side underride guards that meet
5 the performance standards described in paragraph
6 (3) on—

7 “(A) any trailer with a gross vehicle weight
8 rating of 10,000 pounds or more that is manu-
9 factured before the effective date of the rule re-
10 quired by paragraph (1);

11 “(B) any semi-trailer with a gross vehicle
12 weight rating of 10,000 pounds or more that is
13 manufactured before the effective date of the
14 rule required by paragraph (1); and

15 “(C) any single unit truck—

16 “(i) the bottom of the carriage of
17 which is greater than 22 inches above the
18 ground;

19 “(ii) with a gross vehicle weight rating
20 of 10,000 pounds or more; and

21 “(iii) that is manufactured before the
22 effective date of the rule required by para-
23 graph (1).

24 “(3) PERFORMANCE STANDARDS.—A side
25 underride guard shall be considered to meet the per-

1 performance standards referred to in paragraphs (1)
2 and (2) if the side underride guard is able to prevent
3 intrusion from the body or frame of a vehicle de-
4 scribed in paragraph (1) or (2), as applicable, into
5 the passenger compartment of a passenger motor ve-
6 hicle that contacts the guard while traveling 35
7 miles per hour at any angle between 10 degrees and
8 90 degrees.

9 “(4) COMPLIANCE DATES.—

10 “(A) IN GENERAL.—Except as provided in
11 subparagraph (B), compliance with each of the
12 rules issued by the Secretary under paragraphs
13 (1) and (2) shall be required beginning on the
14 date that is 1 year after the respective issuance
15 date of each rule.

16 “(B) PHASE-IN.—The Secretary may per-
17 mit a phase-in period, not to exceed 3 years, for
18 the installation of side underride guards on
19 trailers, semi-trailers, and single unit trucks de-
20 scribed in paragraph (2).

21 “(c) FRONT UNDERRIDE GUARDS.—

22 “(1) IN GENERAL.—Not later than 2 years
23 after the date of enactment of this section, the Sec-
24 retary shall issue a final rule requiring the installa-
25 tion of front underride guards on—

1 “(A) any trailer with a gross vehicle weight
2 rating of 10,000 pounds or more that is manu-
3 factured on or after the effective date of the
4 rule;

5 “(B) any semi-trailer with a gross vehicle
6 weight rating of 10,000 pounds or more that is
7 manufactured on or after the effective date of
8 the rule; and

9 “(C) any single unit truck—

10 “(i) the bottom of the carriage of
11 which is greater than 22 inches above the
12 ground;

13 “(ii) with a gross vehicle weight rating
14 of 10,000 pounds or more; and

15 “(iii) that is manufactured on or after
16 the effective date of the rule.

17 “(2) RETROFIT REQUIREMENTS.—Not later
18 than 3 years after the date of enactment of this sec-
19 tion, the Secretary shall issue a rule requiring the
20 installation of front underride guards on—

21 “(A) any trailer with a gross vehicle weight
22 rating of 10,000 pounds or more that is manu-
23 factured before the effective date of the rule
24 under paragraph (1);

1 “(B) any semi-trailer with a gross vehicle
2 weight rating of 10,000 pounds or more that is
3 manufactured before the effective date of the
4 rule under paragraph (1); and

5 “(C) any single unit truck—

6 “(i) the bottom of the carriage of
7 which is greater than 22 inches above the
8 ground;

9 “(ii) with a gross vehicle weight rating
10 of 10,000 pounds or more; and

11 “(iii) that is manufactured before the
12 effective date of the rule under paragraph
13 (1).

14 “(3) COMPLIANCE DATES.—

15 “(A) IN GENERAL.—Except as provided in
16 subparagraph (B), compliance with each of the
17 rules issued by the Secretary under paragraphs
18 (1) and (2) shall be required beginning on the
19 date that is 1 year after the respective issuance
20 date of each rule.

21 “(B) PHASE-IN.—The Secretary may per-
22 mit a phase-in period (not to exceed 3 years)
23 for the installation of front underride guards on
24 vehicles described in paragraph (2).

1 “(4) REPORT.—Not later than 1 year after the
2 date of enactment of this section, the Secretary
3 shall—

4 “(A) complete research on equipping the
5 vehicles described in paragraphs (1) and (2)
6 with a front underride guard to prevent trucks
7 from overriding the passenger vehicle; and

8 “(B) submit to the Committee on Com-
9 merce, Science, and Transportation of the Sen-
10 ate and the Committees on Transportation and
11 Infrastructure and Energy and Commerce of
12 the House of Representatives a report on the
13 research described in subparagraph (A).

14 “(d) INSPECTION AND REPAIR REQUIREMENTS.—

15 “(1) POST-ACCIDENT INSPECTIONS.—To ensure
16 that all trailers, semi-trailers, and single unit trucks
17 are maintained in safe and proper operating condi-
18 tion at all times, the Secretary shall require that any
19 trailer, semi-trailer, or single unit truck involved in
20 an accident (as defined in section 390.5 of title 49,
21 Code of Federal Regulations (or a successor regula-
22 tion)) undergo and pass an inspection described in
23 appendix G to subchapter B of chapter III of title
24 49, Code of Federal Regulations (or successor regu-
25 lations), to certify that all components of the trailer,

1 semi-trailer, or single unit truck, as applicable, are
2 in safe and proper operating condition.

3 “(2) PRE-TRIP INSPECTIONS.—The Secretary
4 shall require drivers—

5 “(A) to conduct a pre-trip inspection of the
6 comprehensive underride protection system re-
7 quired under this section on their trailer, semi-
8 trailer, or single unit truck—

9 “(i) to identify—

10 “(I) any metal perforated by rust
11 or corrosion that compromises struc-
12 tural integrity;

13 “(II) cracked welds;

14 “(III) cracked or fractured
15 vertical members;

16 “(IV) cuts and tears in any
17 underride guard; and

18 “(V) missing fasteners and loose
19 fasteners; and

20 “(ii) to ensure the dimensional integ-
21 rity of those guards;

22 “(B) to include the results of the inspec-
23 tion described in subparagraph (A) in the driver
24 vehicle inspection report; and

1 “(C) to complete any necessary repairs to,
2 or replacement of, the underride protection sys-
3 tem before the vehicle is operated.”.

4 (b) CLERICAL AMENDMENT.—The chapter analysis
5 for chapter 301 of title 49, United States Code, is amend-
6 ed by striking the item relating to section 30128 and in-
7 serting the following:

“30128. Vehicle rollover prevention and crash mitigation.
“30129. Underride guards.”.

8 (c) RULEMAKINGS.—The Secretary of Transpor-
9 tation shall amend—

10 (1) sections 396.11 and 396.13 of title 49,
11 Code of Federal Regulations, in accordance with sec-
12 tion 30129(d)(2) of title 49, United States Code (as
13 added by subsection (a));

14 (2) section 396.17 of title 49, Code of Federal
15 Regulations, to include a requirement that motor
16 carriers and intermodal equipment providers include
17 an inspection of the comprehensive underride protec-
18 tion system (as defined in section 30102(a) of title
19 49, United States Code) of the commercial motor ve-
20 hicle in a periodic inspection required under section
21 396.17 of title 49, Code of Federal Regulations;

22 (3) section 392.7 of title 49, Code of Federal
23 Regulations, to include the comprehensive underride
24 protection system (as defined in section 30102(a) of

1 title 49, United States Code) in the list of parts and
2 accessories and components required to be in good
3 working order under each of subsections (a) and (b)
4 of section 392.7 of title 49, Code of Federal Regula-
5 tions; and

6 (4) appendix G to subchapter B of chapter III
7 of title 49, Code of Federal Regulations—

8 (A) by redesignating paragraphs 6 (relat-
9 ing to safe loading) through 14 (relating to mo-
10 torcoach seats) as paragraphs 7 through 15, re-
11 spectively; and

12 (B) by inserting after paragraph 5 (relat-
13 ing to lighting devices) the following:

14 “6. REAR IMPACT GUARDS AND REAR END PRO-
15 TECTION.—Any trailer or semitrailer required under
16 section 393.86 to be equipped with a rear impact
17 guard or rear end protection—

18 “(A) that does not meet the requirements
19 under section 393.86;

20 “(B) that—

21 “(i) is missing; or

22 “(ii) has—

23 “(I) any metal perforated by rust
24 or corrosion that compromises struc-
25 tural integrity;

- 1 “(II) a cracked weld;
- 2 “(III) a cracked or fractured
- 3 vertical member;
- 4 “(IV) a cut or tear in any
- 5 underride guard component; or
- 6 “(V) a missing fastener or a
- 7 loose fastener; or
- 8 “(C) for which the dimensional integrity of
- 9 the guard or protection is compromised.”.

10 **SEC. 5. RESEARCH AND PERIODIC REVIEW OF UNDERRIDE**

11 **GUARD STANDARDS.**

12 (a) **REQUEST FOR PROPOSALS.**—As soon as prac-

13 ticable, the Secretary of Transportation shall issue a Re-

14 quest for Proposals for the design of 2 high capacity rear

15 underride barrier prototypes of a generic guard (with en-

16 ergy absorption and without energy absorption) to prevent

17 underride crashes and protect motor vehicle passengers

18 against severe injury at crash speeds of up to 65 miles

19 per hour.

20 (b) **EVALUATION.**—The Secretary shall—

21 (1) evaluate the proposals received in response

22 to the Request for Proposals issued pursuant to sub-

23 section (a); and

24 (2) update the underride guard standards

25 under section 30129 of title 49, United States Code

1 (as added by section 4(a)), as appropriate, to pro-
2 vide the best underide protection that is techno-
3 logically feasible.

4 (c) PERIODIC REVIEWS.—

5 (1) IN GENERAL.—Not later than 5 years after
6 the underide guard standards are updated pursuant
7 to subsection (b)(2), and every 5 years thereafter,
8 the Secretary shall—

9 (A) conduct a review of underide guard
10 standards to evaluate the need for changes in
11 response to advancements in technology; and

12 (B) update the standards accordingly.

13 (2) REPORT.—After each review conducted
14 under this section, the Secretary shall submit to the
15 Committee on Commerce, Science, and Transpor-
16 tation of the Senate and the Committees on Trans-
17 portation and Infrastructure and Energy and Com-
18 merce of the House of Representatives a report on
19 the results of the review.

20 **SEC. 6. COMMITTEE ON UNDERRIDE PROTECTION.**

21 (a) ESTABLISHMENT.—The Secretary of Transpor-
22 tation shall establish the Committee on Underide Protec-
23 tion (referred to in this section as the “Committee”) to
24 oversee the ongoing underide rulemaking process.

1 (b) REPRESENTATION.—The Committee shall be
2 composed of—

3 (1) 1 representative of truck manufacturers;

4 (2) 1 representative of trailer manufacturers;

5 (3) 1 roadside inspector;

6 (4) 1 motor vehicle engineer, who shall be a
7 technician who works on motor vehicle safety im-
8 provements;

9 (5) 1 motor vehicle crash reconstructionist;

10 (6) 2 representatives of consumer-oriented traf-
11 fic safety organizations;

12 (7) 1 representative of the truck and auto in-
13 surance industry;

14 (8) 1 law enforcement crash investigator;

15 (9) 1 emergency medical service provider;

16 (10) 1 public health or injury prevention profes-
17 sional; and

18 (11) at least 4 people whose families have been
19 impacted by an underride crash.

20 (c) MEETINGS.—The Committee shall meet—

21 (1) until the final rules have been issued pursu-
22 ant to section 30129 of title 49, United States Code
23 (as added by section 4(a))—

24 (A) monthly, via conference call; and

1 (B) quarterly, in person, at the Depart-
2 ment of Transportation headquarters; and

3 (2) subsequent to the issuance of the final rules
4 described in paragraph (1), annually, at the Depart-
5 ment of Transportation headquarters, to assess the
6 status of override crash protection.

7 (d) ANNUAL REPORT.—The Committee shall submit
8 an annual report to the appropriate congressional commit-
9 tees that describes the progress made by the Secretary of
10 Transportation in meeting the rulemaking deadlines set
11 forth in section 30129 of title 49, United States Code (as
12 added by section 4(a)).

13 **SEC. 7. PUBLICATION OF VICTIMS OF TRUCK UNDERRIDE**
14 **CRASHES.**

15 The Secretary of Transportation shall—

16 (1) publish data on victims of truck override
17 crashes on a publicly accessible website; and

18 (2) update the data described in paragraph (1)
19 not less frequently than quarterly.

○