

BUILDING CODE REVIEW AND ADOPTION AMENDMENTS

2016 GENERAL SESSION

STATE OF UTAH

Chief Sponsor: Brad R. Wilson

Senate Sponsor: J. Stuart Adams

LONG TITLE

General Description:

This bill amends provisions related to the State Construction Code.

Highlighted Provisions:

This bill:

- ▶ modifies the process by which the Legislature adopts new versions of the State Construction Code and the State Fire Code;
- ▶ addresses the ability of state and local entities to adopt a rule or ordinance that is different from the State Construction Code or the State Fire Code;
- ▶ adopts, with amendments:
 - the 2015 International Building Code;
 - the 2015 International Residential Code;
 - the 2015 International Plumbing Code;
 - the 2015 International Mechanical Code;
 - the 2015 International Fuel Gas Code;
 - the 2014 National Electric Code;
 - the 2015 International Energy Conservation Code; and
 - the 2015 International Existing Building Code;
- ▶ updates provisions to coordinate with the newly adopted international codes;
- ▶ amends provisions related to the amount of fireworks a person may store in a building equipped with an approved sprinkler system;
- ▶ amends provisions related to carbon monoxide alarm installation;
- ▶ amends provisions related to supplying toilet facilities during building construction;

- 30 ▶ provides an alternative means of complying with the International Energy
- 31 Conservation Code;
- 32 ▶ amends provisions related to air duct leakage testing;
- 33 ▶ modifies the amount of allowed air duct leakage;
- 34 ▶ modifies energy rating index compliance requirements;
- 35 ▶ modifies installation requirements for potable water supply protection;
- 36 ▶ modifies electrical wiring requirements for a basement, garage, or accessory
- 37 building;
- 38 ▶ deletes a requirement in the International Plumbing Code that trenching parallel to a
- 39 footing or wall not extend into the bearing plane of the footing or wall;
- 40 ▶ deletes an International Plumbing Code requirement for installation of a temperature
- 41 limiting device in a footbath, pedicure bath, or head shampoo sink;
- 42 ▶ deletes an International Plumbing Code requirement for multiple-compartment
- 43 sinks that discharge independently to a waste receptor;
- 44 ▶ provides an alternative method for storm drain installation;
- 45 ▶ provides for the use of a gray water recycling system in a single family residential
- 46 area;
- 47 ▶ provides an alternative compliance method related to embedded joints;
- 48 ▶ provides an alternative method for installing an overcurrent device;
- 49 ▶ enacts a provision related to building permits for projects using polyurethane
- 50 insulated concrete form block;
- 51 ▶ provides emission requirements for certain natural gas-fired water heaters; and
- 52 ▶ amends provisions to coordinate with newly adopted codes and related Utah Code
- 53 sections.

54 Money Appropriated in this Bill:

55 None

56 Other Special Clauses:

57 This bill provides a special effective date.

58 **Utah Code Sections Affected:**

59 AMENDS:

60 **15A-1-204**, as last amended by Laws of Utah 2014, Chapters 178 and 189

61 **15A-1-403**, as enacted by Laws of Utah 2011, Chapter 14

62 **15A-2-102**, as last amended by Laws of Utah 2014, Chapter 189

63 **15A-2-103**, as last amended by Laws of Utah 2015, Chapter 258

64 **15A-2-104**, as last amended by Laws of Utah 2014, Chapter 189

65 **15A-3-102**, as last amended by Laws of Utah 2013, Chapter 297

66 **15A-3-103**, as last amended by Laws of Utah 2013, Chapter 297

67 **15A-3-104**, as last amended by Laws of Utah 2014, Chapter 243

68 **15A-3-105**, as last amended by Laws of Utah 2013, Chapter 297

69 **15A-3-106**, as last amended by Laws of Utah 2014, Chapter 153

70 **15A-3-107**, as last amended by Laws of Utah 2013, Chapter 297

71 **15A-3-108**, as last amended by Laws of Utah 2013, Chapter 297

72 **15A-3-110**, as last amended by Laws of Utah 2013, Chapter 297

73 **15A-3-112**, as last amended by Laws of Utah 2013, Chapter 297

74 **15A-3-113**, as last amended by Laws of Utah 2013, Chapter 297

75 **15A-3-202**, as last amended by Laws of Utah 2015, Chapter 205

76 **15A-3-203**, as last amended by Laws of Utah 2013, Chapter 279

77 **15A-3-204**, as last amended by Laws of Utah 2013, Chapter 297

78 **15A-3-205**, as last amended by Laws of Utah 2013, Chapter 297

79 **15A-3-206**, as last amended by Laws of Utah 2013, Chapter 297

80 **15A-3-302**, as last amended by Laws of Utah 2013, Chapter 297

81 **15A-3-303**, as last amended by Laws of Utah 2013, Chapter 297

82 **15A-3-304**, as last amended by Laws of Utah 2013, Chapter 297

83 **15A-3-305**, as last amended by Laws of Utah 2013, Chapter 297

84 **15A-3-306**, as last amended by Laws of Utah 2014, Chapter 189

85 **15A-3-308**, as enacted by Laws of Utah 2011, Chapter 14

- 86 15A-3-310, as last amended by Laws of Utah 2013, Chapter 297
- 87 15A-3-311, as last amended by Laws of Utah 2013, Chapter 297
- 88 15A-3-313, as last amended by Laws of Utah 2013, Chapter 297
- 89 15A-3-314, as last amended by Laws of Utah 2013, Chapter 297
- 90 15A-3-401, as last amended by Laws of Utah 2014, Chapter 100
- 91 15A-3-501, as last amended by Laws of Utah 2013, Chapter 297
- 92 15A-3-601, as last amended by Laws of Utah 2013, Chapter 297
- 93 15A-3-701, as last amended by Laws of Utah 2013, Chapter 279
- 94 15A-3-801, as last amended by Laws of Utah 2013, Chapter 297
- 95 15A-4-103, as enacted by Laws of Utah 2011, Chapter 14
- 96 15A-4-107, as enacted by Laws of Utah 2011, Chapter 14
- 97 15A-4-203, as enacted by Laws of Utah 2011, Chapter 14
- 98 58-11a-502, as last amended by Laws of Utah 2014, Chapter 100

99 ENACTS:

- 100 15A-3-315, Utah Code Annotated 1953
- 101 15A-3-901, Utah Code Annotated 1953
- 102 15A-6-101, Utah Code Annotated 1953
- 103 15A-6-102, Utah Code Annotated 1953
- 104 15A-6-201, Utah Code Annotated 1953
- 105 15A-6-202, Utah Code Annotated 1953

106 REPEALS:

- 107 15A-3-106.5, as enacted by Laws of Utah 2014, Chapter 153



109 *Be it enacted by the Legislature of the state of Utah:*

110 Section 1. Section 15A-1-204 is amended to read:

111 **15A-1-204. Adoption of State Construction Code -- Amendments by commission**

112 **-- Approved codes -- Exemptions.**

113 (1) (a) The State Construction Code is the construction codes adopted with any

114 modifications in accordance with this section that the state and each political subdivision of the
115 state shall follow.

116 (b) A person shall comply with the applicable provisions of the State Construction
117 Code when:

118 (i) new construction is involved; and

119 (ii) the owner of an existing building, or the owner's agent, is voluntarily engaged in:

120 (A) the repair, renovation, remodeling, alteration, enlargement, rehabilitation,
121 conservation, or reconstruction of the building; or

122 (B) changing the character or use of the building in a manner that increases the
123 occupancy loads, other demands, or safety risks of the building.

124 (c) On and after July 1, 2010, the State Construction Code is the State Construction
125 Code in effect on July 1, 2010, until in accordance with this section:

126 (i) a new State Construction Code is adopted; or

127 (ii) one or more provisions of the State Construction Code are amended or repealed in
128 accordance with this section.

129 (d) A provision of the State Construction Code may be applicable:

130 (i) to the entire state; or

131 (ii) within a county, city, or town.

132 (2) (a) The Legislature shall adopt a State Construction Code by enacting legislation
133 that adopts a nationally recognized construction code with any modifications.

134 (b) Legislation [~~enacted under this Subsection (2)~~] described in Subsection (2)(a) shall
135 state that [it] the legislation takes effect on the July 1 after the day on which the legislation is
136 enacted, unless otherwise stated in the legislation.

137 (c) Subject to Subsection [~~(5)~~] (6), a State Construction Code adopted by the
138 Legislature is the State Construction Code until, in accordance with this section, the Legislature
139 adopts a new State Construction Code by:

140 (i) adopting a new State Construction Code in its entirety; or

141 (ii) amending or repealing one or more provisions of the State Construction Code.

142 (3) (a) Except as provided in Subsection (3)(b), for each update of a nationally
143 recognized construction code, the commission shall prepare a report described in Subsection
144 (4).

145 (b) For the provisions of a nationally recognized construction code that apply only to
146 detached one- and two-family dwellings and townhouses not more than three stories above
147 grade plane in height with separate means of egress and their accessory structures, the
148 commission shall:

149 (i) prepare a report described in Subsection (4) in 2021 and, thereafter, for every
150 second update of the nationally recognized construction code; and

151 (ii) not prepare a report described in Subsection (4) in 2018.

152 (4) (a) In accordance with Subsection (3), on or before September 1 of the same year as
153 the year designated in the title of a nationally recognized construction code, the commission
154 shall prepare and submit a report to the Business and Labor Interim Committee that:

155 (i) states whether the commission recommends the Legislature adopt the update with
156 any modifications; and

157 (ii) describes the costs and benefits of each recommended change in the update or in
158 any modification.

159 (b) After the Business and Labor Interim Committee receives the report described in
160 Subsection (4)(a), the Business and Labor Interim Committee shall:

161 (i) study the recommendations during the remainder of the interim; and

162 (ii) if the Business and Labor Interim Committee decides to recommend legislative
163 action to the Legislature, prepare legislation for consideration by the Legislature in the next
164 general session.

165 ~~[(3)]~~ (5) (a) (i) The commission shall, by no later than November 30 of each year in
166 which the commission is not required to submit a report described in Subsection (4),
167 recommend in a report to the Business and Labor Interim Committee whether the Legislature
168 should ~~[-(i)]~~ amend or repeal one or more provisions of [a] the State Construction Code ~~[-or]~~.

169 ~~[(ii) in a year of a regularly scheduled update of a nationally recognized code, adopt a~~

170 ~~construction code with any modifications.]~~

171 (ii) As part of a recommendation described in Subsection (5)(a)(i), the commission
172 shall describe the costs and benefits of each proposed amendment or repeal.

173 (b) The commission may recommend legislative action related to the State

174 Construction Code:

175 (i) on its own initiative;

176 (ii) upon the recommendation of the division; or

177 (iii) upon the receipt of a request by one of the following that the commission
178 recommend legislative action related to the State Construction Code:

179 (A) a local regulator;

180 (B) a state regulator;

181 (C) a state agency involved with the construction and design of a building;

182 (D) the Construction Services Commission;

183 (E) the Electrician Licensing Board;

184 (F) the Plumbers Licensing Board; or

185 (G) a recognized construction-related association.

186 ~~[(4)]~~ (c) If the Business and Labor Interim Committee decides to recommend
187 legislative action to the Legislature, the Business and Labor Interim Committee shall prepare
188 legislation for consideration by the Legislature in the next general session ~~[that, if passed by the~~
189 ~~Legislature, would:].~~

190 ~~[(a) adopt a new State Construction Code in its entirety; or]~~

191 ~~[(b) amend or repeal one or more provisions of the State Construction Code.]~~

192 ~~[(5)]~~ (6) (a) Notwithstanding ~~[Subsection (3)]~~ the provisions of this section, the
193 commission may, in accordance with Title 63G, Chapter 3, Utah Administrative Rulemaking
194 Act, amend the State Construction Code if the commission determines that waiting for
195 legislative action in the next general legislative session would:

196 (i) cause an imminent peril to the public health, safety, or welfare; or

197 (ii) place a person in violation of federal or other state law.

198 (b) If the commission amends the State Construction Code in accordance with this
199 Subsection [~~(5)~~] (6), the commission shall file with the division:

200 (i) the text of the amendment to the State Construction Code; and

201 (ii) an analysis that includes the specific reasons and justifications for the commission's
202 findings.

203 (c) If the State Construction Code is amended under this Subsection [~~(5)~~] (6), the
204 division shall:

205 (i) publish the amendment to the State Construction Code in accordance with Section
206 15A-1-205; and

207 (ii) notify the Business and Labor Interim Committee of the amendment to the State
208 Construction Code, including a copy of the commission's analysis described in Subsection [~~(5)~~]
209 (6)(b)(ii).

210 (d) If not formally adopted by the Legislature at [~~its~~] the next annual general session,
211 an amendment to the State Construction Code under this Subsection [~~(5)~~] (6) is repealed on the
212 July 1 immediately following the next annual general session that follows the adoption of the
213 amendment.

214 [~~(6)~~] (7) (a) The division, in consultation with the commission, may approve, without
215 adopting, one or more approved codes, including a specific edition of a construction code, for
216 use by a compliance agency.

217 (b) If the code adopted by a compliance agency is an approved code described in
218 Subsection [~~(6)~~] (7)(a), the compliance agency may:

219 (i) adopt an ordinance requiring removal, demolition, or repair of a building;

220 (ii) adopt, by ordinance or rule, a dangerous building code; or

221 (iii) adopt, by ordinance or rule, a building rehabilitation code.

222 (8) Except as provided in Subsections (6), (7), (9), and (10), or as expressly provided in
223 state law, a state executive branch entity or political subdivision of the state may not, after
224 December 1, 2016, adopt or enforce a rule, ordinance, or requirement that applies to a subject
225 specifically addressed by, and that is more restrictive than, the State Construction Code.

226 (9) A state executive branch entity or political subdivision of the state may:
227 (a) enforce a federal law or regulation;
228 (b) adopt or enforce a rule, ordinance, or requirement if the rule, ordinance, or
229 requirement applies only to a facility or construction owned or used by a state entity or a
230 political subdivision of the state; or
231 (c) enforce a rule, ordinance, or requirement:
232 (i) that the state executive branch entity or political subdivision adopted or made
233 effective before July 1, 2015; and
234 (ii) for which the state executive branch entity or political subdivision can demonstrate,
235 with substantial evidence, that the rule, ordinance, or requirement is necessary to protect an
236 individual from a condition likely to cause imminent injury or death.
237 (10) The Department of Health or the Department of Environmental Quality may
238 enforce a rule or requirement adopted before January 1, 2015.
239 ~~[(7)]~~ (11) (a) Except as provided in Subsection ~~[(7)]~~ (11)(b), a structure used solely in
240 conjunction with agriculture use, and not for human occupancy, is exempt from the permit
241 requirements of the State Construction Code.
242 (b) (i) Unless exempted by a provision other than Subsection ~~[(7)]~~ (11)(a), a plumbing,
243 electrical, and mechanical permit may be required when that work is included in a structure
244 described in Subsection ~~[(7)]~~ (11)(a).
245 (ii) Unless located in whole or in part in an agricultural protection area created under
246 Title 17, Chapter 41, Agriculture and Industrial Protection Areas, a structure described in
247 Subsection ~~[(7)]~~ (11)(a) is not exempt from a permit requirement if the structure is located on
248 land that is:
249 (A) within the boundaries of a city or town, and less than five contiguous acres; or
250 (B) within a subdivision for which the county has approved a subdivision plat under
251 Title 17, Chapter 27a, Part 6, Subdivisions, and less than two contiguous acres.
252 ~~[(8)]~~ (12) A structure that is no more than 1,000 square feet and is used solely for the
253 type of sales described in Subsection 59-12-104(20) is exempt from the permit requirements

254 described in:

255 (a) Chapter 2, Adoption of State Construction Code;

256 (b) Chapter 3, Statewide Amendments Incorporated as Part of State Construction

257 Code; and

258 (c) Chapter 4, Local Amendments Incorporated as Part of State Construction Code.

259 Section 2. Section **15A-1-403** is amended to read:

260 **15A-1-403. Adoption of State Fire Code.**

261 (1) (a) The State Fire Code is:

262 (i) a code promulgated by a nationally recognized code authority that is adopted by the
263 Legislature under this section with any modifications; and

264 (ii) a code to which cities, counties, fire protection districts, and the state shall adhere
265 in safeguarding life and property from the hazards of fire and explosion.

266 (b) On and after July 1, 2010, the State Fire Code is the State Fire Code in effect on
267 July 1, 2010, until in accordance with this section:

268 (i) a new State Fire Code is adopted; or

269 (ii) one or more provisions of the State Fire Code are amended or repealed in
270 accordance with this section.

271 (c) A provision of the State Fire Code may be applicable:

272 (i) to the entire state; or

273 (ii) within a city, county, or fire protection district.

274 (2) (a) The Legislature shall adopt a State Fire Code by enacting legislation that adopts
275 a nationally recognized fire code with any modifications.

276 (b) Legislation [~~enacted under this~~] described in Subsection (2)(a) shall state that [it]
277 the legislation takes effect on the July 1 after the day on which the legislation is enacted, unless
278 otherwise stated in the legislation.

279 (c) Subject to Subsection [~~(5)~~] (6), a State Fire Code adopted by the Legislature is the
280 State Fire Code until in accordance with this section the Legislature adopts a new State Fire
281 Code by:

282 (i) adopting a new State Fire Code in its entirety; or

283 (ii) amending or repealing one or more provisions of the State Fire Code.

284 (3) (a) Except as provided in Subsection (3)(b), for each update of a nationally
285 recognized fire code, the board shall prepare a report described in Subsection (4).

286 (b) For the provisions of a nationally recognized fire code that apply only to detached
287 one- and two-family dwellings and townhouses not more than three stories above grade plane
288 in height with separate means of egress and their accessory structures, the board shall:

289 (i) prepare a report described in Subsection (4) in 2021 and, thereafter, for every
290 second update of the nationally recognized fire code; and

291 (ii) not prepare a report described in Subsection (4) in 2018.

292 (4) (a) In accordance with Subsection (3), on or before September 1 of the same year as
293 the year designated in the title of an update of a nationally recognized fire code, the board shall
294 prepare and submit a report to the Business and Labor Interim Committee that:

295 (i) states whether the board recommends the Legislature adopt the update with any
296 modifications; and

297 (ii) describes the costs and benefits of each recommended change in the update or in
298 any modification.

299 (b) After the Business and Labor Interim Committee receives the report described in
300 Subsection (4)(a), the Business and Labor Interim Committee shall:

301 (i) study the recommendations during the remainder of the interim; and

302 (ii) if the Business and Labor Interim Committee decides to recommend legislative
303 action to the Legislature, prepare legislation for consideration by the Legislature in the next
304 general session.

305 ~~[(3)]~~ (5) (a) (i) The board shall, by no later than November 30 of each year in which the
306 board is not required to submit a report described in Subsection (4), recommend in a report to
307 the Business and Labor Interim Committee whether the Legislature should~~[-(i)]~~ amend or
308 repeal one or more provisions of the State Fire Code~~[-or]~~.

309 ~~[(ii) in a year of a regularly scheduled update of a nationally recognized fire code;~~

310 ~~adopt with any modifications the nationally recognized fire code.]~~

311 (ii) As part of a recommendation described in Subsection (5)(a)(i), the board shall
312 describe the costs and benefits of each proposed amendment or repeal.

313 (b) The board may recommend legislative action related to the State Fire Code:

314 (i) on its own initiative; or

315 (ii) upon the receipt of a request by a city, county, or fire protection district that the
316 board recommend legislative action related to the State Fire Code.

317 (c) Within 45 days after ~~[receipt of]~~ the day on which the board receives a request
318 under Subsection ~~[(3)]~~ (5)(b), the board shall direct the division to convene an informal hearing
319 concerning the request.

320 (d) The board shall conduct a hearing under this section in accordance with the rules of
321 the board.

322 (e) The board shall decide whether to include the request in the report ~~[required under]~~
323 described in Subsection ~~[(3)]~~ (5)(a) ~~[whether to recommend the legislative action raised by a~~
324 request].

325 (f) (i) Within 15 days ~~[following the completion of a hearing of the board under this~~
326 Subsection (3), the board] after the day on which the board conducts a hearing, the board shall
327 direct the division to notify the entity that made the request of the board's decision regarding
328 the request.

329 (ii) The division shall provide the notice:

330 ~~[(i)]~~ (A) in writing; and

331 ~~[(ii)]~~ (B) in a form prescribed by the board.

332 ~~[(4)]~~ (g) If the Business and Labor Interim Committee decides to recommend
333 legislative action to the Legislature, the Business and Labor Interim Committee shall prepare
334 legislation for consideration by the Legislature in the next general session that, if passed by the
335 Legislature, would~~[(a) adopt a new State Fire Code in its entirety; or (b)]~~ amend or repeal one
336 or more provisions of the State Fire Code.

337 ~~[(5)]~~ (6) (a) Notwithstanding ~~[Subsection (3)]~~ the provisions of this section, the board

338 may, in accordance with Title 63G, Chapter 3, Utah Administrative Rulemaking Act, amend a
339 State Fire Code if the board determines that waiting for legislative action in the next general
340 legislative session would:

- 341 (i) cause an imminent peril to the public health, safety, or welfare; or
- 342 (ii) place a person in violation of federal or other state law.

343 (b) If the board amends a State Fire Code in accordance with this Subsection [~~(5)~~] (6),
344 the board shall:

- 345 (i) publish the State Fire Code with the amendment; and
- 346 (ii) notify the Business and Labor Interim Committee of the adoption, including a copy
347 of an analysis by the board identifying specific reasons and justifications for its findings.

348 (c) If not formally adopted by the Legislature at [its] the next annual general session, an
349 amendment to a State Fire Code adopted under this Subsection [~~(5)~~] (6) is repealed on the July
350 1 immediately following the next annual general session that follows the adoption of the
351 amendment.

352 [~~(6)~~] (7) (a) [~~A~~] Except as provided in Subsection (7)(b), a legislative body of a
353 political subdivision may enact an ordinance in the political subdivision's fire code that is more
354 restrictive [in its fire code requirements] than the State Fire Code:

- 355 (i) in order to meet a public safety need of the political subdivision; and
- 356 (ii) subject to the requirements of [~~this~~] Subsection [~~(6)~~] (7)(c).

357 (b) Except as provided in Subsections (7)(c), (10), and (11), or as expressly provided in
358 state law, a political subdivision may not, after December 1, 2016, enact or enforce a rule or
359 ordinance that applies to a structure built in accordance with the International Residential
360 Code, as adopted in the State Construction Code, that is more restrictive than the State Fire
361 Code.

362 (c) A political subdivision may adopt:

- 363 (i) the appendices of the International Fire Code, 2015 edition; and
- 364 (ii) a fire sprinkler ordinance in accordance with Section [15A-5-203](#).

365 [~~(b)~~] (d) A legislative body of a political subdivision that enacts an ordinance under

366 [~~this section on or after July 1, 2010~~] Subsection (7)(a) shall:

367 (i) notify the board in writing at least 30 days before the day on which the legislative
368 body enacts the ordinance and include in the notice a statement as to the proposed subject
369 matter of the ordinance; and

370 (ii) after the legislative body enacts the ordinance, report to the board before the board
371 makes the report required under Subsection [~~(6)(e)~~] (7)(e), including providing the board:

372 (A) a copy of the ordinance enacted under this Subsection [~~(6)~~] (7); and

373 (B) a description of the public safety need that is the basis of enacting the ordinance.

374 [~~(e)~~] (e) The board shall submit to the Business and Labor Interim Committee each
375 year with the recommendations submitted in accordance with Subsection [~~(3)~~] (4):

376 (i) a list of the ordinances enacted under this Subsection [~~(6)~~] (7) during the fiscal year
377 immediately [~~proceeding~~] preceding the report; and

378 (ii) recommendations, if any, for legislative action related to an ordinance enacted
379 under this Subsection [~~(6)~~] (7).

380 [~~(f)~~] (f) (i) The state fire marshal shall keep an indexed copy of an ordinance enacted
381 under this Subsection [~~(6)~~] (7).

382 (ii) The state fire marshal shall make a copy of an ordinance enacted under this
383 Subsection [~~(6)~~] (7) available on request.

384 [~~(g)~~] (g) The board may make rules in accordance with Title 63G, Chapter 3, Utah
385 Administrative Rulemaking Act, to establish procedures for a legislative body of a political
386 subdivision to follow to provide the notice and report required under this Subsection [~~(6)~~] (7).

387 (8) Except as provided in Subsections (9), (10), and (11), or as expressly provided in
388 state law, a state executive branch entity may not, after December 1, 2016, adopt or enforce a
389 rule or requirement that:

390 (a) is more restrictive than the State Fire Code; and

391 (b) applies to detached one- and two-family dwellings and townhouses not more than
392 three stories above grade plane in height with a separate means of egress and their accessory
393 structures.

394 (9) A state government entity may adopt a rule or requirement regarding a residential
395 occupancy that is regulated by:

396 (a) the State Fire Prevention Board;

397 (b) the Department of Health; or

398 (c) the Department of Human Services.

399 (10) A state executive branch entity or political subdivision of the state may:

400 (a) enforce a federal law or regulation;

401 (b) adopt or enforce a rule, ordinance, or requirement if the rule, ordinance, or
402 requirement applies only to a facility or construction owned or used by a state entity or a
403 political subdivision of the state; or

404 (c) enforce a rule, ordinance, or requirement:

405 (i) that the state executive branch entity or political subdivision adopted or made
406 effective before July 1, 2015; and

407 (ii) for which the state executive branch entity or political subdivision can demonstrate,
408 with substantial evidence, that the rule, ordinance, or requirement is necessary to protect an
409 individual from a condition likely to cause imminent injury or death.

410 (11) The Department of Health or the Department of Environmental Quality may
411 enforce a rule or requirement adopted before January 1, 2015.

412 Section 3. Section **15A-2-102** is amended to read:

413 **15A-2-102. Definitions.**

414 As used in this chapter and Chapter 3, Statewide Amendments Incorporated as Part of
415 State Construction Code, and Chapter 4, Local Amendments Incorporated as Part of State
416 Construction Code:

417 (1) "HUD Code" means the Federal Manufactured Housing Construction and Safety
418 Standards Act, as issued by the Department of Housing and Urban Development and published
419 in 24 C.F.R. Parts 3280 and 3282 (as revised April 1, 1990).

420 (2) "IBC" means the edition of the International Building Code adopted under Section
421 **15A-2-103.**

422 (3) "IEBC" means the edition of the International Existing Building Code adopted
423 under Section 15A-2-103.

424 ~~[(3)]~~ (4) "IECC" means the edition of the International Energy Conservation Code
425 adopted under Section 15A-2-103.

426 ~~[(4)]~~ (5) "IFGC" means the edition of the International Fuel Gas Code adopted under
427 Section 15A-2-103.

428 ~~[(5)]~~ (6) "IMC" means the edition of the International Mechanical Code adopted under
429 Section 15A-2-103.

430 ~~[(6)]~~ (7) "IPC" means the edition of the International Plumbing Code adopted under
431 Section 15A-2-103.

432 ~~[(7)]~~ (8) "IRC" means the edition of the International Residential Code adopted under
433 Section 15A-2-103.

434 ~~[(8)]~~ (9) "NEC" means the edition of the National Electrical Code adopted under
435 Section 15A-2-103.

436 ~~[(9)]~~ (10) "UWUI" means the edition of the Utah Wildland Urban Interface Code
437 adopted under Section 15A-2-103.

438 Section 4. Section 15A-2-103 is amended to read:

439 **15A-2-103. Specific editions adopted of construction code of a nationally**
440 **recognized code authority.**

441 (1) Subject to the other provisions of this part, the following construction codes are
442 incorporated by reference, and together with the amendments specified in Chapter 3, Part 3,
443 Statewide Amendments to International Plumbing Code, and Chapter 4, Local Amendments
444 Incorporated as Part of State Construction Code, are the construction standards to be applied to
445 building construction, alteration, remodeling, and repair, and in the regulation of building
446 construction, alteration, remodeling, and repair in the state:

447 (a) the ~~[2012]~~ 2015 edition of the International Building Code, including Appendix J,
448 issued by the International Code Council;

449 (b) the ~~[2012]~~ 2015 edition of the International Residential Code, issued by the

450 International Code Council;

451 (c) the [2012] 2015 edition of the International Plumbing Code, issued by the
452 International Code Council;

453 (d) the [2012] 2015 edition of the International Mechanical Code, issued by the
454 International Code Council;

455 (e) the [2012] 2015 edition of the International Fuel Gas Code, issued by the
456 International Code Council;

457 (f) the [2011] 2014 edition of the National Electrical Code, issued by the National Fire
458 Protection Association;

459 (g) the [2012] 2015 edition of the International Energy Conservation Code, issued by
460 the International Code Council;

461 (h) the 2015 edition of the International Existing Building Code, issued by the
462 International Code Council;

463 [~~(h)~~] (i) subject to Subsection 15A-2-104(2), the HUD Code;

464 [~~(i)~~] (j) subject to Subsection 15A-2-104(1), Appendix E of the [2012] 2015 edition of
465 the International Residential Code, issued by the International Code Council; and

466 [~~(j)~~] (k) subject to Subsection 15A-2-104(1), the 2005 edition of the NFPA 225 Model
467 Manufactured Home Installation Standard, issued by the National Fire Protection Association.

468 (2) Consistent with Title 65A, Chapter 8, Management of Forest Lands and Fire
469 Control, the Legislature adopts the 2006 edition of the Utah Wildland Urban Interface Code,
470 issued by the International Code Council, with the alternatives or amendments approved by the
471 Utah Division of Forestry, as a construction code that may be adopted by a local compliance
472 agency by local ordinance or other similar action as a local amendment to the codes listed in
473 this section.

474 Section 5. Section **15A-2-104** is amended to read:

475 **15A-2-104. Installation standards for manufactured housing.**

476 (1) The following are the installation standards for manufactured housing for new
477 installations or for existing manufactured or mobile homes that are subject to relocation,

478 building alteration, remodeling, or rehabilitation in the state:

479 (a) The manufacturer's installation instruction for the model being installed is the
480 primary standard.

481 (b) If the manufacturer's installation instruction for the model being installed is not
482 available or is incomplete, the following standards apply:

483 (i) Appendix E of the [2012] 2015 edition of the IRC, as issued by the International
484 Code Council for installations defined in Section AE101 of Appendix E; or

485 (ii) if an installation is beyond the scope of the [2012] 2015 edition of the IRC as
486 defined in Section AE101 of Appendix E, the 2005 edition of the NFPA 225 Model
487 Manufactured Home Installation Standard, issued by the National Fire Protection Association.

488 (c) A manufacturer, dealer, or homeowner is permitted to design for unusual
489 installation of a manufactured home not provided for in the manufacturer's standard installation
490 instruction, Appendix E of the [2012] 2015 edition of the IRC, or the 2005 edition of the
491 NFPA 225, if the design is approved in writing by a professional engineer or architect licensed
492 in Utah.

493 (d) For a mobile home built before June 15, 1976, the mobile home shall also comply
494 with the additional installation and safety requirements specified in Chapter 3, Part 8,
495 Installation and Safety Requirements for Mobile Homes Built Before June 15, 1976.

496 (2) Pursuant to the HUD Code Section 604(d), a manufactured home may be installed
497 in the state that does not meet the local snow load requirements as specified in Chapter 3, Part
498 2, Statewide Amendments to International Residential Code, except that the manufactured
499 home shall have a protective structure built over the home that meets the IRC and the snow
500 load requirements under Chapter 3, Part 2, Statewide Amendments to International Residential
501 Code.

502 Section 6. Section **15A-3-102** is amended to read:

503 **15A-3-102. Amendments to Chapters 1 through 3 of IBC.**

504 (1) IBC, Section 106, is deleted.

505 (2) [(a)] In IBC, Section 110, a new section is added as follows: "[H0.3.5] 110.3.5.1,

506 Weather-resistant exterior wall envelope. An inspection shall be made of the weather-resistant
507 exterior wall envelope as required by Section 1403.2, and flashing as required by Section
508 1405.4 to prevent water from entering the weather-resistive barrier."

509 ~~[(b) The remaining sections of IBC, Section 110, are renumbered as follows: 110.3.6,~~
510 ~~Lath or gypsum board inspection; 110.3.7, Fire and smoke-resistant penetrations; 110.3.8,~~
511 ~~Energy efficiency inspections; 110.3.9, Other inspections; 110.3.10, Special inspections; and~~
512 ~~110.3.11, Final inspection.]~~

513 (3) IBC, Section 115.1, is deleted and replaced with the following: "115.1 Authority.
514 Whenever the building official finds any work regulated by this code being performed in a
515 manner either contrary to the provisions of this code or other pertinent laws or ordinances or is
516 dangerous or unsafe, the building official is authorized to stop work."

517 (4) In IBC, Section 202, the following definition is added for Ambulatory Surgical
518 Center: "AMBULATORY SURGICAL CENTER. A building or portion of a building licensed
519 by the Utah Department of Health where procedures are performed that may render patients
520 incapable of self preservation where care is less than 24 hours. See Utah Administrative Code
521 R432-13."

522 (5) In IBC, Section 202, the definition for Foster Care Facilities is modified by
523 changing the word "Foster" to "Child."

524 (6) In IBC, Section 202, the definition for "[F]Record Drawings" is modified by
525 deleting the words "a fire alarm system" and replacing them with "any fire protection system".

526 (7) In IBC, Section 202, the following definition is added for Residential
527 Treatment/Support Assisted Living Facility: "RESIDENTIAL TREATMENT/SUPPORT
528 ASSISTED LIVING FACILITY. See Section 308.1.2."

529 (8) In IBC, Section 202, the following definition is added for Type I Assisted Living
530 Facility: "TYPE I ASSISTED LIVING FACILITY. See Section 308.1.2."

531 (9) In IBC, Section 202, the following definition is added for Type II Assisted Living
532 Facility: "TYPE II ASSISTED LIVING FACILITY. See Section 308.1.2."

533 ~~[(10) In the list in IBC, Section 304.1, the following words are added after the words~~

534 "~~Ambulatory care facilities~~": "~~where four or more care recipients are rendered incapable of self~~
535 ~~preservation.~~"

536 [~~(H)~~] (10) In IBC, Section 305.2, the words "child care centers," are inserted after the
537 word "supervision," and the following sentence is added at the end of the paragraph: "See
538 Section 425 for special requirements for Day Care."

539 [~~(I)~~] (11) In IBC, Section 305.2.2 and 305.2.3, the word "five" is deleted and replaced
540 with the word "four" in both places.

541 [~~(J)~~] (12) A new IBC Section 305.2.4 is added as follows: "305.2.4 Child Day Care --
542 Residential Certificate or a Family License. Areas used for child day care purposes with a
543 Residential Certificate R430-50 or a Family License, as defined in Utah Administrative Code,
544 R430-90, Licensed Family Child Care, may be located in a Group R-2 or R-3 occupancy as
545 provided in Section 310.5 or shall comply with the International Residential Code in
546 accordance with Section R101.2."

547 [~~(K)~~] (13) A new IBC Section 305.2.5 is added as follows: "305.2.5 Child Care
548 Centers. Areas used for Hourly Child Care Centers, as defined in Utah Administrative Code,
549 R430-60, Child Care Center as defined in Utah Administrative Code, R430-100, or Out of
550 School Time Programs, as defined in Utah Administrative Code, R430-70, may be classified as
551 accessory occupancies."

552 (14) In IBC, Table 307.1(1), footnote "d" is added to the row for Consumer fireworks
553 in the column titled STORAGE - Solid Pounds (cubic feet).

554 (15) In IBC, Section 308.2, the word "FOSTER" is deleted and replaced with
555 "CHILD."

556 [~~(L)~~] (16) A new IBC Section 308.2.1 is added as follows: "308.2.1 Assisted living
557 facilities and related occupancies. The following words and terms shall, for the purposes of
558 this section and as used elsewhere in this code, have the meanings shown herein.

559 TYPE I ASSISTED LIVING FACILITY. A residential facility licensed by the Utah
560 Department of Health that provides a protected living arrangement for ambulatory,
561 non-restrained persons who are capable of achieving mobility sufficient to exit the facility

562 without the assistance of another person.

563 Occupancies. Limited capacity, type I assisted living facilities with two to five residents shall
564 be classified as R-3 occupancies. Small, type I assisted living facilities with six to sixteen
565 residents shall be classified as R-4 occupancies. Large, type I assisted living facilities with
566 over sixteen residents shall be classified as I-1 occupancies.

567 TYPE II ASSISTED LIVING FACILITY. A residential facility licensed by the Utah
568 Department of Health that provides an array of coordinated supportive personal and health care
569 services to residents who meet the definition of semi-independent.

570 Semi-Independent. A person who is:

571 A. Physically disabled but able to direct his or her own care; or

572 B. Cognitively impaired or physically disabled but able to evacuate from the facility with the
573 physical assistance of one person.

574 Occupancies. Limited capacity, type II assisted living facilities with two to five residents shall
575 be classified as R-4 occupancies. Small, type II assisted living facilities with six to sixteen
576 residents shall be classified as I-1 occupancies. Large, type II assisted living facilities with
577 over sixteen residents shall be classified as I-2 occupancies.

578 RESIDENTIAL TREATMENT/SUPPORT ASSISTED LIVING FACILITY. A residential
579 treatment/support assisted living facility which creates a group living environment for four or
580 more residents licensed by the Utah Department of Human Services, and provides a protected
581 living arrangement for ambulatory, non-restrained persons who are capable of achieving
582 mobility sufficient to exit the facility without the physical assistance of another person."

583 [~~(16)~~] (17) In IBC, Section 308.3, the words "(see Section 308.2.1)" are added after the
584 words "assisted living facilities[.]"

585 [~~(17)~~] (18) In IBC, Section [~~308.3.1~~] 308.3.4, all of the words after the first
586 International Residential Code are deleted.

587 [~~(18)~~] (19) In IBC, Section 308.4, the following changes are made:

588 (a) The words "five persons" are deleted and replaced with the words "three persons."

589 (b) The words "foster care facilities" are deleted and replaced with "child care

590 facilities."

591 (c) The words "(both intermediate care facilities and skilled nursing facilities)" are
592 added after "nursing homes."

593 [~~(d)~~ The words "Ambulatory Surgical Centers with five or more operating rooms" are
594 added to the list.]

595 [~~(19)~~ (20) In IBC, Section [~~308.4.1~~] 308.4.2, the word "five" is deleted and replaced
596 with the word "three" in both places.

597 [~~(20)~~ (21) In IBC, Section 308.6, the word "five" is deleted and replaced with the
598 word "four^[#]."

599 [~~(21)~~ (22) In IBC, Section 308.6.1, the following changes are made:

600 (a) The word "five" is deleted and replaced with the word "four^[#]."

601 (b) The words "2-1/2 years or less of age" are deleted and replaced with "under the age
602 of two^[#]."

603 (c) The following sentence is added at the end: "See Section [~~425~~] 427 for special
604 requirements for Day Care."

605 [~~(22)~~ (23) In IBC, Sections 308.6.3 and 308.6.4, the word "five" is deleted and
606 replaced with the word "four" in both places and the following sentence is added at the end:
607 "See Section [~~425~~] 427 for special requirements for Day Care."

608 [~~(23)~~ (24) In IBC, Section 310.5, the words "and single family dwellings complying
609 with the IRC" are added after "Residential occupancies^[#]."

610 [~~(24)~~ (25) In IBC, Section 310.5.1, the words "other than Child Care" are inserted
611 after the word "dwelling" in the first sentence and the following sentence is added at the end:
612 "See Section [~~425~~] 427 for special requirements for Child Day Care."

613 [~~(25)~~ (26) A new IBC Section [~~310.5.2~~] 310.5.3 is added as follows: "[~~310.5.2~~]
614 310.5.3 Child Care. Areas used for child care purposes may be located in a residential
615 dwelling unit under all of the following conditions and Section [~~425~~] 427:

616 1. Compliance with Utah Administrative Code, R710-8, Day Care Rules, as enacted under the
617 authority of the Utah Fire Prevention Board.

618 2. Use is approved by the Utah Department of Health, as enacted under the authority of the
619 Utah Code, Title 26, Chapter 39, Utah Child Care Licensing Act, and in any of the following
620 categories:

- 621 a. Utah Administrative Code, R430-50, Residential Certificate Child Care.
- 622 b. Utah Administrative Code, R430-90, Licensed Family Child Care.

623 3. Compliance with all zoning regulations of the local regulator."

624 ~~[(26)]~~ (27) In IBC, Section 310.6, the words "(see Section 308.2.1)" are added after
625 "assisted living facilities[^u]."

626 Section 7. Section **15A-3-103** is amended to read:

627 **15A-3-103. Amendments to Chapters 4 through 6 of IBC.**

628 (1) IBC Section 403.5.5 is deleted.

629 ~~[(2) IBC Section (F)406.5.8 is deleted and replaced with the following: "(F)406.5.8~~

630 Standpipe system. An open parking garage shall be equipped with an approved Class I manual
631 standpipe system when fire department access is not provided for firefighting operations to
632 within 150 feet of all portions of the open parking garage as measured from the approved fire
633 department vehicle access.]

634 [Exception: Open parking garages equipped throughout with an automatic sprinkler system in
635 accordance with Section 903.3.1.1 and a standpipe system is not required by Section 905.3.1.]"

636 ~~[(3) A new IBC Section (F)406.5.8.1 is added as follows: "(F)406.5.8.1 Installation~~
637 requirements. Class I manual standpipe shall be designed and installed in accordance with
638 Section 905 and NFPA 14. Class I manual standpipe shall be accessible throughout the
639 parking garage such that all portions of the parking structure are protected within 150 feet of a
640 hose connection."]

641 ~~[(4)]~~ (2) In IBC, Section 422.2, a new paragraph is added as follows: "422.2

642 Separations: Ambulatory care facilities licensed by the Utah Department of Health shall be
643 separated from adjacent tenants with a fire ~~[barrier]~~ partition having a minimum one hour
644 fire-resistance rating. Any level below the level of exit discharge shall be separated from the
645 level of exit discharge by a horizontal assembly having a minimum one hour fire-resistance

646 rating.

647 Exception: A fire barrier is not required to separate the level of exit discharge when:

648 1. Such levels are under the control of the Ambulatory Care Facility.

649 2. Any hazardous spaces are separated by horizontal assembly having a minimum one hour
650 fire-resistance rating."

651 [~~5~~] (3) A new IBC Section [~~425~~] 427, Day Care, is added as follows:

652 "[~~425.1~~] 427.1 Detailed Requirements. In addition to the occupancy and construction
653 requirements in this code, the additional provisions of this section shall apply to all Day Care in
654 accordance with Utah Administrative Code R710-8 Day Care Rules.

655 [~~425.2~~] 427.2 Definitions.

656 [~~425.2.1~~] 427.2.1 Authority Having Jurisdiction (AHJ): State Fire Marshal, his duly authorized
657 deputies, or the local fire enforcement authority code official.

658 [~~425.2.2~~] 427.2.2 Day Care Facility: Any building or structure occupied by clients of any age
659 who receive custodial care for less than 24 hours by individuals other than parents, guardians,
660 relatives by blood, marriage or adoption.

661 [~~425.2.3~~] 427.2.3 Day Care Center: Providing care for five or more clients in a place other than
662 the home of the person cared for. This would also include Child Care Centers, Out of School
663 Time or Hourly Child Care Centers licensed by the Department of Health.

664 [~~425.2.4~~] 427.2.4 Family Day Care: Providing care for clients listed in the following two
665 groups:

666 [~~425.2.4.1~~] 427.2.4.1 Type 1: Services provided for five to eight clients in a home. This would
667 also include a home that is certified by the Department of Health as Residential Certificate
668 Child Care or licensed as Family Child Care.

669 [~~425.2.4.2~~] 427.2.4.2 Type 2: Services provided for nine to sixteen clients in a home with
670 sufficient staffing. This would also include a home that is licensed by the Department of
671 Health as Family Child Care.

672 [~~425.2.5~~] 427.2.5 R710-8: Utah Administrative Code, R710-8, Day Care Rules, as enacted
673 under the authority of the Utah Fire Prevention Board.

674 [425.3.] 427.3 Family Day Care.

675 [425.3.1] 427.3.1 Family Day Care units shall have on each floor occupied by clients, two
676 separate means of egress, arranged so that if one is blocked the other will be available.

677 [425.3.2] 427.3.2 Family Day Care units that are located in the basement or on the second story
678 shall be provided with two means of egress, one of which shall discharge directly to the
679 outside.

680 [425.3.2.1] 427.3.2.1 Residential Certificate Child Care and Licensed Family Child Care with
681 five to eight clients in a home, located on the ground level or in a basement, may use an
682 emergency escape or rescue window as allowed in IFC, Chapter 10, Section [~~1029~~] 1030.

683 [425.3.3] 427.3.3 Family Day Care units shall not be located above the second story.

684 [425.3.4] 427.3.4 In Family Day Care units, clients under the age of two shall not be located
685 above or below the first story.

686 [425.3.4.1] 427.3.4.1 Clients under the age of two may be housed above or below the first story
687 where there is at least one exit that leads directly to the outside and complies with IFC, Section
688 [~~1009~~] 1011 or Section [~~1010~~] 1012 or Section [~~1026~~] 1027.

689 [425.3.5] 427.3.5 Family Day Care units located in split entry/split level type homes in which
690 stairs to the lower level and upper level are equal or nearly equal, may have clients housed on
691 both levels when approved by the AHJ.

692 [425.3.6] 427.3.6 Family Day Care units shall have a portable fire extinguisher on each level
693 occupied by clients, which shall have a classification of not less than 2A:10BC, and shall be
694 serviced in accordance with NFPA, Standard 10, Standard for Portable Fire Extinguishers.

695 [425.3.7] 427.3.7 Family Day Care units shall have single station smoke detectors in good
696 operating condition on each level occupied by clients. Battery operated smoke detectors shall
697 be permitted if the facility demonstrates testing, maintenance, and battery replacement to insure
698 continued operation of the smoke detectors.

699 [425.3.8] 427.3.8 Rooms in Family Day Care units that are provided for clients to sleep or nap,
700 shall have at least one window or door approved for emergency escape.

701 [425.3.9] 427.3.9 Fire drills shall be conducted in Family Day Care units quarterly and shall

702 include the complete evacuation from the building of all clients and staff. At least annually, in
703 Type I Family Day Care units, the fire drill shall include the actual evacuation using the escape
704 or rescue window, if one is used as a substitute for one of the required means of egress.

705 [~~425.4~~] 427.4 Day Care Centers.

706 [~~425.4.1~~] 427.4.1 Day Care Centers shall comply with either I-4 requirements or E
707 requirements of the IBC, whichever is applicable for the type of Day Care Center.

708 [~~425.4.2~~] 427.4.2 Emergency Evacuation Drills shall be completed as required in IFC, Chapter
709 4, Section 405.

710 [~~425.4.3~~] 427.4.3 Location at grade. Group E child day care centers shall be located at the
711 level of exit discharge.

712 [~~425.4.3.1~~] 427.4.3.1 Child day care spaces for children over the age of 24 months may be
713 located on the second floor of buildings equipped with automatic fire protection throughout
714 and an automatic fire alarm system.

715 [~~425.4.4~~] 427.4.4 Egress. All Group E child day care spaces with an occupant load of more
716 than 10 shall have a second means of egress. If the second means of egress is not an exit door
717 leading directly to the exterior, the room shall have an emergency escape and rescue window
718 complying with Section [~~1029~~] 1030.

719 [~~425.4.5~~] 427.4.5 All Group E Child Day Care Centers shall comply with Utah Administrative
720 Code, R430-100 Child Care Centers, R430-60 Hourly Child Care Centers, and R430-70 Out of
721 School Time.

722 [~~425.5~~] 427.5 Requirements for all Day Care.

723 [~~425.5.1~~] 427.5.1 Heating equipment in spaces occupied by children shall be provided with
724 partitions, screens, or other means to protect children from hot surfaces and open flames.

725 [~~425.5.2~~] 427.5.2 A fire escape plan shall be completed and posted in a conspicuous place. All
726 staff shall be trained on the fire escape plan and procedure."

727 [~~(6)~~] (4) In IBC, Section [~~504.2~~] 504.4, a new section is added as follows: [~~"504.2.1~~]

728 "504.4.1 Notwithstanding the exceptions to Section 504.2, Group I-2 Assisted Living Facilities
729 shall be allowed [~~to be two stories of~~] on each level of a two-story building of Type V-A

730 construction when all of the following apply:

- 731 1. All secured units are located at the level of exit discharge in compliance with Section
732 [~~1008.1.9.3~~] 1010.1.9.3 as amended;
- 733 2. The total combined area of both stories shall not exceed the total allowable area for a
734 one-story building; and
- 735 3. All other provisions that apply in Section 407 have been provided."

736 Section 8. Section **15A-3-104** is amended to read:

737 **15A-3-104. Amendments to Chapters 7 through 9 of IBC.**

738 (1) IBC, Section (F)901.8, is deleted and replaced with the following: "(F)901.8 Pump
739 and riser room size. Fire pump and automatic sprinkler system riser rooms shall be designed
740 with adequate space for all installed equipment necessary for the installation and to provide
741 sufficient working space around the stationary equipment. Clearances around equipment shall
742 be in accordance with manufacturer requirements and not less than the following minimum
743 elements:

744 901.8.1 A minimum clear and unobstructed distance of 12-inches shall be provided from the
745 installed equipment to the elements of permanent construction.

746 901.8.2 A minimum clear and unobstructed distance of 12-inches shall be provided between
747 all other installed equipment and appliances.

748 901.8.3 A clear and unobstructed width of 36-inches shall be provided in front of all installed
749 equipment and appliances, to allow for inspection, service, repair or replacement without
750 removing such elements of permanent construction or disabling the function of a required
751 fire-resistance-rated assembly.

752 901.8.4 Automatic sprinkler system riser rooms shall be provided with a clear and
753 unobstructed passageway to the riser room of not less than 36-inches, and openings into the
754 room shall be clear and unobstructed, with doors swinging in the outward direction from the
755 room and the opening providing a clear width of not less than 34-inches and a clear height of
756 the door opening shall not be less than 80-inches.

757 901.8.5 Fire pump rooms shall be provided with a clear and unobstructed passageway to the

758 fire pump room of not less than 72-inches, and openings into the room shall be clear,
759 unobstructed and large enough to allow for the removal of the largest piece of equipment, with
760 doors swinging in the outward direction from the room and the opening providing a clear width
761 of not less than 68-inches and a clear height of the door opening shall not be less than
762 80-inches."

763 (2) In IBC, Section (F)903.2.2, the words "the entire floor" are deleted and replaced
764 with "a building" and the last paragraph is deleted.

765 (3) IBC, Section (F)903.2.4, condition 2, is deleted and replaced with the following: "2.
766 A Group F-1 fire area is located more than three stories above the lowest level of fire
767 department vehicle access."

768 (4) IBC, Section (F)903.2.7, condition 2, is deleted and replaced with the following: "2.
769 A Group M fire area is located more than three stories above the lowest level of fire department
770 vehicle access."

771 (5) IBC, Sections (F)903.2.8, (F)903.2.8.1, [~~and~~] (F)903.2.8.2, and (F)903.2.8.4, are
772 deleted and replaced with the following: "(F)903.2.8 Group R. An automatic sprinkler system
773 installed in accordance with Section 903.3 shall be provided throughout all buildings with a
774 Group R fire area.

775 Exceptions:

776 1. Detached one- and two-family dwellings and multiple single-family dwellings (townhouses)
777 constructed in accordance with the International Residential Code For One- and Two-Family
778 Dwellings.

779 2. Single story Group R-1 occupancies with fire areas not more than 2,000 square feet that
780 contain no installed plumbing or heating, where no cooking occurs, and constructed of Type
781 I-A, I-B, II-A, or II-B construction."

782 (6) IBC, Sections (F)903.2.8.3 and (F)903.2.8.3.1, are renumbered to (F)903.2.8.1 and
783 (F)903.2.8.1.1.

784 (7) IBC, Section (F)903.2.8.3.2, is renumbered to (F)903.2.8.1.2 and the following
785 exception is added:

786 [3:] "Exception: Group R-4 fire areas not more than 4,500 gross square feet and not containing
787 more than 16 residents, provided the building is equipped throughout with an approved fire
788 alarm system that is interconnected and receives its primary power from the building wiring
789 and a commercial power system."

790 (8) IBC, Section (F)903.2.8.4, is deleted.

791 [(6)] (9) IBC, Section (F)903.2.9, condition 2, is deleted and replaced with the
792 following: "2. A Group S-1 fire area is located more than three stories above the lowest level
793 of fire department vehicle access."

794 [(7)] (10) IBC, Section [(F)904.11] (F)904.12, is deleted and replaced with the
795 following: "[~~(F)904.11~~] (F)904.12 Commercial cooking systems. The automatic
796 fire-extinguishing system for commercial cooking systems shall be of a type recognized for
797 protection of commercial cooking equipment and exhaust systems. Pre-engineered automatic
798 extinguishing systems shall be tested in accordance with UL 300 and listed and labeled for the
799 intended application. The system shall be installed in accordance with this code, its listing and
800 the manufacturer's installation instructions.

801 Exception: Factory-built commercial cooking recirculating systems that are tested in
802 accordance with UL 710B and listed, labeled, and installed in accordance with Section 304.1 of
803 the International Mechanical Code."

804 [(8)] (11) IBC, Sections [(F)904.11.3, (F)904.11.3.1, (F)904.11.4, and (F)904.11.4.1,]
805 (F)904.12.3, (F)904.12.3.1, (F)904.12.4, and (F)904.12.4.1, are deleted.

806 (12) In IBC, Section 905, a new subsection, Section (F)905.3.9, is added as follows:

807 "Open Parking Garages. Open parking garages shall be equipped with an approved
808 Class 1 manual standpipe system when fire department access is not provided for firefighting
809 operations to within 150 feet of all portions of the open parking garage as measured from the
810 approved fire department vehicle access. Class 1 manual standpipe shall be accessible
811 throughout the parking garage such that all portions of the parking structure are protected
812 within 150 feet of a hose connection."

813 (13) In IBC, Section (F)905.8, the exception is deleted and replaced with the following:

814 "Exception: Where subject to freezing and approved by the fire code official."
815 ~~[(9)]~~ (14) In IBC, Section (F)907.2.3 Group E~~[-(a) The],~~ the first sentence is deleted
816 and rewritten as follows: "A manual fire alarm system that [initiates] activates the occupant
817 notification system in accordance with Section (F)907.5 [and] shall be installed, in accordance
818 with Section (F)907.6 [shall be installed] and administrative rules made by the State Fire
819 Prevention Board in Group E occupancies."

820 ~~[(b) In Exception number 3, starting on line five, the words "emergency voice/alarm~~
821 ~~communication system" are deleted and replaced with "occupant notification system".]~~

822 ~~[(10) In IBC, Section (F)908.7, the first sentence is deleted and replaced as follows:~~
823 ~~"Groups R-1, R-2, R-3, R-4, I-1, and I-4 occupancies"; the exceptions are deleted and the~~
824 ~~following sentence is added after the first sentence: "A minimum of one carbon monoxide~~
825 ~~alarm shall be installed on each habitable level."]~~

826 ~~[(11) In IBC, Section (F)908.7, the following new subsections are added:]~~

827 ~~["(F)908.7.1 Interconnection. Where more than one carbon monoxide alarm is required to be~~
828 ~~installed within Group R or I-1 occupancies, the carbon monoxide alarms shall be~~
829 ~~interconnected in such a manner that the activation of one alarm will activate all of the alarms.~~
830 ~~Physical interconnection of carbon monoxide alarms shall not be required where listed wireless~~
831 ~~alarms are installed and all alarms sound upon activation of one alarm. The alarm shall be~~
832 ~~clearly audible in all bedrooms over background noise levels with all intervening doors closed.]~~

833 ~~[(F)908.7.2 Power source. In new construction, required carbon monoxide alarms shall receive~~
834 ~~their primary power from the building wiring where such wiring is served from a commercial~~
835 ~~source and shall be equipped with a battery backup. Carbon monoxide alarms with integral~~
836 ~~strobes that are not equipped with battery backup shall be connected to an emergency electrical~~
837 ~~system. Carbon monoxide alarms shall emit a signal when the batteries are low. Wiring shall~~
838 ~~be permanent and without a disconnecting switch other than as required for overcurrent~~
839 ~~protection.]~~

840 ~~[Exception: Carbon monoxide alarms are not required to be equipped with battery backup~~
841 ~~where they are connected to an emergency electrical system."]~~

842 ~~[(12) IBC, Section (F)908.7.1, is renumbered to 908.7.3.]~~

843 (15) IBC, Sections (F)915 through (F)915.6, are deleted and replaced with the
844 following:

845 "(F)915 Where required.

846 Group I-1, I-2, I-4, and R occupancies located in a building containing a fuel-burning appliance
847 or in a building that has an attached garage shall be equipped with single-station carbon
848 monoxide alarms. The carbon monoxide alarms shall be listed as complying with UL 2034 or
849 UL 2075 and be installed and maintained in accordance with NFPA 720 and the manufacturer's
850 instructions. An open parking garage, as defined in Chapter 2, or an enclosed parking garage,
851 ventilated in accordance with Section 404 of the International Mechanical Code, shall not be
852 considered an attached garage. A minimum of one carbon monoxide alarm shall be installed
853 on each habitable level.

854 (F)915.1 Interconnection.

855 Where more than one carbon monoxide alarm is required to be installed within Group I-1, I-2,
856 I-4, or R occupancies, the carbon monoxide alarm shall be interconnected in such a manner that
857 the activation of one alarm will activate all of the alarms. Physical interconnection of carbon
858 monoxide alarms shall not be required where listed wireless alarms are installed and all alarms
859 sound upon activation of one alarm. The alarm shall be clearly audible in all bedrooms over
860 background noise levels with all intervening doors closed.

861 (F)915.2 Power source.

862 In new construction, required carbon monoxide alarms shall receive their primary power from
863 the building wiring where such wiring is served from a commercial source and shall be
864 equipped with a battery backup. Carbon monoxide alarms with integral strobes that are not
865 equipped with a battery backup shall be connected to an emergency electrical system. Carbon
866 monoxide alarms shall emit a signal when the batteries are low. Wiring shall be permanent and
867 without a disconnecting switch other than as required for overcurrent protection.

868 Exceptions.

869 1. Carbon monoxide alarms are not required to be equipped with a battery backup where they

870 are connected to an emergency electrical system.

871 2. Hard wiring of carbon monoxide alarms in existing areas shall not be required where the
872 alterations or repairs do not result in the removal of interior wall or ceiling finishes exposing
873 the structure, unless there is an attic, crawl space, or basement available that could provide
874 access for hard wiring without the removal of interior finishes.

875 (F)915.3 Group E.

876 A carbon monoxide detection system shall be installed in new buildings that contain Group E
877 occupancies in accordance with IFC, Chapter 9, Section 915. A carbon monoxide detection
878 system shall be installed in existing buildings that contain Group E occupancies in accordance
879 with IFC, Chapter 11, Section 1103.9.

880 (F)915.3.1 Where required.

881 In Group E occupancies, a carbon monoxide detection system shall be provided where a
882 fuel-burning appliance, a fuel-burning fireplace, or a fuel-burning forced air furnace is present.

883 (F)915.3.2 Detection equipment.

884 Each carbon monoxide detection system shall be installed in accordance with NFPA 720 and
885 the manufacturer's instructions and be listed as complying with, for single station detectors, UL
886 2034 and, for system detectors, UL 2075.

887 (F)915.3.3 Locations.

888 Each carbon monoxide detection system shall be installed in the locations specified in NFPA
889 720.

890 (F)915.3.4 Combination detectors.

891 A combination carbon monoxide/smoke detector is an acceptable alternative to a carbon
892 monoxide detection system if the combination carbon monoxide/smoke detector is listed in
893 accordance with UL 2075 and UL 268.

894 (F)915.3.5 Power source.

895 Each carbon monoxide detection system shall receive primary power from the building wiring
896 if the wiring is served from a commercial source. If primary power is interrupted, each carbon
897 monoxide detection system shall receive power from a battery. Wiring shall be permanent and

898 without a disconnecting switch other than that required for overcurrent protection.

899 (F)915.3.6 Maintenance.

900 Each carbon monoxide detection system shall be maintained in accordance with NFPA 720. A
901 carbon monoxide detection system that becomes inoperable or begins to produce end of life
902 signals shall be replaced."

903 Section 9. Section **15A-3-105** is amended to read:

904 **15A-3-105. Amendments to Chapters 10 through 12 of IBC.**

905 (1) In IBC, Section [~~1008.1.9.6, the words "Group I-1 and"~~ are added in the title and in
906 ~~the first sentence before the words "Group I-2" and]~~ 1010.1.9.6, a new number [8] 9 is added as
907 follows: "[8] 9. The secure area or unit with special egress locks shall be located at the level of
908 exit discharge in Type V construction."

909 [~~(2) In IBC, Section 1008.1.9.7, a new number 7 is added as follows: "7. The secure~~
910 ~~area or unit with delayed egress locks shall be located at the level of exit discharge in Type V~~
911 ~~construction."~~]

912 [~~(3)~~ (2) In IBC, Section [~~1009.7.2]~~ 1011.5.2, exception [5] 3 is deleted and replaced
913 with the following: "[5] 3. In Group R-3 occupancies, within dwelling units in Group R-2
914 occupancies, and in Group U occupancies that are accessory to a Group R-3 occupancy, or
915 accessory to individual dwelling units in Group R-2 occupancies, the maximum riser height
916 shall be 8 inches (203 mm) and the minimum tread depth shall be 9 inches (229 mm). The
917 minimum winder tread depth at the walk line shall be 10 inches (254 mm), and the minimum
918 winder tread depth shall be 6 inches (152 mm). A nosing not less than 0.75 inch (19.1 mm) but
919 not more than 1.25 inches (32 mm) shall be provided on stairways with solid risers where the
920 tread depth is less than 10 inches (254 mm)."

921 [~~(4)~~ (3) In IBC, Section [~~1009.15]~~ 1011.11, a new exception [6] 5 is added as follows:
922 "[6] 5. In occupancies in Group R-3, as applicable in Section 101.2 and in occupancies in
923 Group U, which are accessory to an occupancy in Group R-3, as applicable in Section 101.2,
924 handrails shall be provided on at least one side of stairways consisting of four or more risers."

925 [~~(5)~~ (4) In IBC, Section [~~1011.5]~~ 1013.5, the words ", including when the building

926 may not be fully occupied[-]" are added at the end of the sentence.

927 [~~(6)~~] (5) IBC, Section [~~1024~~] 1025, is deleted.

928 [~~(7)~~] (6) In IBC, Section [~~1028.12~~] 1029.14, exception 2 is deleted.

929 [~~(8)~~] (7) In IBC, Section 1109.8, the following words "shall be capable of operation
930 without a key and" are inserted in the second sentence between the words "lift" and "shall".

931 [~~(9)~~] (8) In IBC, Section 1208.4, subparagraph 1 is deleted and replaced with the
932 following: "1. The unit shall have a living room of not less than 165 square feet (15.3 m²) of
933 floor area. An additional 100 square feet (9.3 m²) of floor area shall be provided for each
934 occupant of such unit in excess of two."

935 Section 10. Section **15A-3-106** is amended to read:

936 **15A-3-106. Amendments to Chapters 13 through 15 of IBC.**

937 IBC, Chapters 13 [~~and~~], 14, and 15 are not amended.

938 Section 11. Section **15A-3-107** is amended to read:

939 **15A-3-107. Amendments to Chapter 16 of IBC.**

940 (1) In IBC, Table 1604.5, Risk Category III, in the sentence that begins "Group I-2," a
941 new footnote c is added as follows: "c. Type II Assisted Living Facilities that are I-2
942 occupancy classifications in accordance with Section 308 shall be Risk Category II in this
943 table."

944 (2) In IBC, Section 1605.2, in the portion of the definition for the value of f_2 , the words
945 "and 0.2 for other roof configurations" are deleted and replaced with the following: " $f_2 = 0.20 +$
946 $.025(A-5)$ for other configurations where roof snow load exceeds 30 psf;

947 $f_2 = 0$ for roof snow loads of 30 psf (1.44kN/m²) or less.

948 Where A = Elevation above sea level at the location of the structure (ft./1,000)."

949 (3) In IBC, Sections 1605.3.1 and 1605.3.2, exception 2 in each section is deleted and
950 replaced with the following: "2. Flat roof snow loads of 30 pounds per square foot (1.44
951 kNm²) or less need not be combined with seismic loads. Where flat roof snow loads exceed 30
952 pounds per square foot (1.44 kNm²), the snow loads may be reduced in accordance with the
953 following in load combinations including both snow and seismic loads. W_s as calculated

954 below, shall be combined with seismic loads.

955 $W_s = (0.20 + 0.025(A-5))P_f$ is greater than or equal to $0.20 P_f$.

956 Where:

957 W_s = Weight of snow to be included in seismic calculations

958 A = Elevation above sea level at the location of the structure (ft./1,000)

959 P_f = Design roof snow load, psf.

960 For the purpose of this section, snow load shall be assumed uniform on the roof footprint
961 without including the effects of drift or sliding. The Importance Factor, I , used in calculating P_f
962 may be considered 1.0 for use in the formula for W_s ".

963 (4) IBC, Section 1608.1, is deleted and replaced with the following: "1608.1 General.
964 Except as modified in Sections 1608.1.1, 1608.1.2, and 1608.1.3, design snow loads shall be
965 determined in accordance with Chapter 7 of ASCE 7, but the design roof load shall not be less
966 than that determined by Section 1607."

967 (5) A new IBC, Section 1608.1.1, is added as follows: "1608.1.1 Section 7.4.5 of
968 Chapter 7 of ASCE 7 referenced in Section 1608.1 of the IBC is deleted and replaced with the
969 following: Section 7.4.5 Ice Dams and Icicles Along Eaves. Where ground snow loads exceed
970 75 psf, eaves shall be capable of sustaining a uniformly distributed load of $2p_f$ on all
971 overhanging portions. No other loads except dead loads shall be present on the roof when this
972 uniformly distributed load is applied. All building exits under down-slope eaves shall be
973 protected from sliding snow and ice."

974 (6) In IBC, Section 1608.1.2, a new section is added as follows: "1608.1.2 Utah Snow
975 Loads. The snow loads specified in Table 1608.1.2(b) shall be used for the jurisdictions
976 identified in that table. Otherwise, the ground snow load, P_g , to be used in the determination of
977 design snow loads for buildings and other structures shall be determined by using the following
978 formula: $P_g = (P_o^2 + S^2(A-A_o)^2)^{0.5}$ for A greater than A_o , and $P_g = P_o$ for A less than or equal to
979 A_o .

980 WHERE:

981 P_g = Ground snow load at a given elevation (psf);

982 P_o = Base ground snow load (psf) from Table No. 1608.1.2(a);

983 S = Change in ground snow load with elevation (psf/100 ft.) From Table No. 1608.1.2(a);

984 A = Elevation above sea level at the site (ft./1,000);

985 A_o = Base ground snow elevation from Table 1608.1.2(a) (ft./1,000).

986 The building official may round the roof snow load to the nearest 5 psf. The ground snow
 987 load, P_g , may be adjusted by the building official when a licensed engineer or architect submits
 988 data substantiating the adjustments.

989 Where the minimum roof live load in accordance with Section [~~1607.11~~] 1607.12 is greater
 990 than the design roof snow load, such roof live load shall be used for design, however, it shall
 991 not be reduced to a load lower than the design roof snow load. Drifting need not be considered
 992 for roof snow loads less than 20 psf."

993 (7) IBC, Table 1608.1.2(a) and Table 1608.1.2(b), are added as follows:

| "TABLE NO. 1608.1.2(a) | | | | |
|--|-----------|-------|-----|-------|
| STATE OF UTAH - REGIONAL SNOW LOAD FACTORS | | | | |
| | COUNTY | P_o | S | A_o |
| 994 | Beaver | 43 | 63 | 6.2 |
| 995 | Box Elder | 43 | 63 | 5.2 |
| 996 | Cache | 50 | 63 | 4.5 |
| 997 | Carbon | 43 | 63 | 5.2 |
| 998 | Daggett | 43 | 63 | 6.5 |
| 999 | Davis | 43 | 63 | 4.5 |
| 1000 | Duchesne | 43 | 63 | 6.5 |
| 1001 | Emery | 43 | 63 | 6.0 |
| 1002 | Garfield | 43 | 63 | 6.0 |
| 1003 | Grand | 36 | 63 | 6.5 |
| 1004 | Iron | 43 | 63 | 5.8 |
| 1005 | Juab | 43 | 63 | 5.2 |

| | | | | |
|------|------------|----|----|-----|
| 1009 | Kane | 36 | 63 | 5.7 |
| 1010 | Millard | 43 | 63 | 5.3 |
| 1011 | Morgan | 57 | 63 | 4.5 |
| 1012 | Piute | 43 | 63 | 6.2 |
| 1013 | Rich | 57 | 63 | 4.1 |
| 1014 | Salt Lake | 43 | 63 | 4.5 |
| 1015 | San Juan | 43 | 63 | 6.5 |
| 1016 | Sanpete | 43 | 63 | 5.2 |
| 1017 | Sevier | 43 | 63 | 6.0 |
| 1018 | Summit | 86 | 63 | 5.0 |
| 1019 | Tooele | 43 | 63 | 4.5 |
| 1020 | Uintah | 43 | 63 | 7.0 |
| 1021 | Utah | 43 | 63 | 4.5 |
| 1022 | Wasatch | 86 | 63 | 5.0 |
| 1023 | Washington | 29 | 63 | 6.0 |
| 1024 | Wayne | 36 | 63 | 6.5 |
| 1025 | Weber | 43 | 63 | 4.5 |

1026 TABLE NO. 1608.1.2(B)

1027 REQUIRED SNOW LOADS FOR SELECTED UTAH CITIES AND TOWNS^{1,2}

1028 The following jurisdictions require design snow load values that differ from the Equation in the Utah Snow Load Study.

| 1029 | County | City | Elevation | Ground Snow Load (psf) | Roof Snow Load (psf) ⁶ |
|------|--------|---|-----------|------------------------|-----------------------------------|
| 1030 | Carbon | Price ³ | 5550 | 43 | 30 |
| | | All other county locations ⁵ | -- | -- | -- |

| | | | | | |
|------|--|---|-------------|-----|----|
| 1031 | Davis | Fruit Heights ³ | 4500 - 4850 | 57 | 40 |
| 1032 | Emery | Green River ³ | 4070 | 36 | 25 |
| 1033 | Garfield | Panguitch ³ | 6600 | 43 | 30 |
| 1034 | Rich | Woodruff ³ | 6315 | 57 | 40 |
| | | Laketown ⁴ | 6000 | 57 | 40 |
| | | Garden City ⁵ | -- | -- | -- |
| | | Randolph ⁴ | 6300 | 57 | 40 |
| 1035 | San Juan | Monticello ³ | 6820 | 50 | 35 |
| 1036 | Summit | Coalville ³ | 5600 | 86 | 60 |
| | | Kamas ⁴ | 6500 | 114 | 80 |
| 1037 | Tooele | Tooele ³ | 5100 | 43 | 30 |
| 1038 | Utah | Orem ³ | 4650 | 43 | 30 |
| | | Pleasant Grove ⁴ | 5000 | 43 | 30 |
| | | Provo ⁵ | -- | -- | -- |
| 1039 | Wasatch | Heber ⁵ | -- | -- | -- |
| 1040 | Washington | Leeds ³ | 3460 | 29 | 20 |
| | | Santa Clara ³ | 2850 | 21 | 15 |
| | | St. George ³ | 2750 | 21 | 15 |
| | | All other county locations ⁵ | -- | -- | -- |
| 1041 | Wayne | Loa ³ | 7080 | 43 | 30 |
| 1042 | ¹ The IBC requires a minimum live load - See [1607.11.2] Section 1607.12. | | | | |
| 1043 | ² This table is informational only in that actual site elevations may vary. Table is only valid if site elevation is within 100 feet of the listed elevation. Otherwise, contact the local Building Official. | | | | |
| 1044 | ³ Values adopted from Table VII of the Utah Snow Load Study. | | | | |
| 1045 | ⁴ Values based on site-specific study. Contact local Building Official for additional information. | | | | |

1046 ⁵Contact local Building Official.

1047 ⁶Based on $C_e = 1.0$, $C_t = 1.0$ and $I_s = 1.0$ "

1048 (8) A new IBC, Section 1608.1.3, is added as follows: "1608.1.3 Thermal Factor. The
1049 value for the thermal factor, C_t , used in calculation of P_f shall be determined from Table 7.3 in
1050 ASCE 7.

1051 Exception: Except for unheated structures, the value of C_t need not exceed 1.0 when ground
1052 snow load, P_g is calculated using Section 1608.1.2 as amended."

1053 (9) IBC, Section 1608.2, is deleted and replaced with the following: "1608.2 Ground
1054 Snow Loads. The ground snow loads to be used in determining the design snow loads for roofs
1055 in states other than Utah are given in Figure 1608.2 for the contiguous United States and Table
1056 1608.2 for Alaska. Site-specific case studies shall be made in areas designated CS in figure
1057 1608.2. Ground snow loads for sites at elevations above the limits indicated in Figure 1608.2
1058 and for all sites within the CS areas shall be approved. Ground snow load determination for
1059 such sites shall be based on an extreme value statistical analysis of data available in the vicinity
1060 of the site using a value with a 2-percent annual probability of being exceeded (50-year mean
1061 recurrence interval). Snow loads are zero for Hawaii, except in mountainous regions as
1062 approved by the building official."

1063 (10) A new IBC, Section 1613.1.1, is added as follows: "1613.1.1 ASCE 12.7.2 and
1064 12.14.8.1 of Chapter 12 of ASCE 7 referenced in Section 1613.1, Definition of W , Item 4 is
1065 deleted and replaced with the following:

1066 4. Where the flat roof snow load, P_f , exceeds 30 psf, the snow load included in seismic design
1067 shall be calculated, in accordance with the following formula: $W_s = (0.20 + 0.025(A-5))P_f$ is
1068 greater than or equal to $0.20 P_f$.

1069 WHERE:

1070 W_s = Weight of snow to be included in seismic calculations

1071 A = Elevation above sea level at the location of the structure (ft./1,000)

1072 P_f = Design roof snow load, psf.

1073 For the purposes of this section, snow load shall be assumed uniform on the roof footprint

1074 without including the effects of drift or sliding. The Importance Factor, I , used in calculating P_f
 1075 may be considered 1.0 for use in the formula for W_s ."

1076 (11) A new IBC, Section ~~[1613.5]~~ 1613.7, is added as follows: "~~[1613.5]~~ 1613.7
 1077 ASCE 7, Section 13.5.6.2.2 paragraph (e) is modified to read as follows: (e) Penetrations shall
 1078 have a sleeve or adapter through the ceiling tile to allow for free movement of at least 1 inch
 1079 (25 mm) in all horizontal directions.

1080 Exceptions:

- 1081 1. Where rigid braces are used to limit lateral deflections.
- 1082 2. At fire sprinkler heads in frangible surfaces per NFPA 13."

1083 Section 12. Section **15A-3-108** is amended to read:

1084 **15A-3-108. Amendments to Chapters 17 through 19 of IBC.**

1085 (1) A new IBC, Section 1807.1.6.4, is added as follows: "1807.1.6.4 Empirical
 1086 concrete foundation design. Group R, Division 3 Occupancies three stories or less in height,
 1087 and Group U Occupancies, which are constructed in accordance with Section 2308, or with
 1088 other methods employing repetitive wood-frame construction or repetitive cold-formed steel
 1089 structural member construction, shall be permitted to have concrete foundations constructed in
 1090 accordance with Table 1807.1.6.4."

1091 (2) A new IBC, Table 1807.1.6.4 is added as follows:

1092 "TABLE 1807.1.6.4

1093 EMPIRICAL FOUNDATION WALLS (1,7,8)

| 1094 Max. Height | Top Edge Support | Min. Thickness | Vertical Steel (2) | Horizontal Steel (3) | Steel at Openings (4) | Max. Lintel Length | Min. Lintel Length |
|------------------|------------------|----------------|--------------------|----------------------|--|--------------------|---|
| 1095 2'(610 mm) | None | 6" | (5) | 2- #4 Bars | 2- #4 Bars above 1- #4 Bar each side 1- #4 Bar below | 2'(610 mm) | 2" for each foot of opening width; min. 6" |
| 1096 3'(914 mm) | None | 6" | #4@32" | 3- #4 Bars | 2- #4 Bars above 1- #4 Bar each side 1- #4 Bar below | 2'(610 mm) | 2" for each foot of opening width; min. 6" |

| | | | | | | | | |
|------|--|-----------------------------|----|--------|------------|--|--------------|--|
| 1097 | 4'(1,219 mm) | None | 6" | #4@32" | 4- #4 Bars | 2- #4 Bars above 1- #4 Bar each side 1- #4 Bar below | 3'(914 mm) | 2" for each foot of opening width; min. 6" |
| 1098 | 6'(1,829 mm) | Floor or roof Diaphragm (6) | 8" | #4@24" | 5- #4 Bars | 2- #4 Bars above 1- #4 Bar each side 1- #4 Bar below | 6'(1,829 mm) | 2" for each foot of opening width; min. 6" |
| 1099 | 8'(2,438 mm) | Floor or roof Diaphragm (6) | 8" | #4@24" | 6- #4 Bars | 2- #4 Bars above 1- #4 Bar each side 1- #4 Bar below | 6'(1,829 mm) | 2" for each foot of opening width; min. 6" |
| 1100 | 9'(2,743 mm) | Floor or roof Diaphragm (6) | 8" | #4@16" | 7- #4 Bars | 2- #4 Bars above 1- #4 Bar each side 1- #4 Bar below | 6'(1,829 mm) | 2" for each foot of opening width; min. 6" |
| 1101 | Over 9'(2,743 mm), Engineering required for each column | | | | | | | |
| 1102 | Footnotes: | | | | | | | |
| 1103 | (1) Based on 3,000 psi (20.6 Mpa) concrete and 60,000 psi (414 Mpa) reinforcing steel. | | | | | | | |
| 1104 | (2) To be placed in the center of the wall, and extended from the footing to within three inches (76 mm) of the top of the wall; dowels of #4 bars to match vertical steel placement shall be provided in the footing, extending 24 inches (610 mm) into the foundation wall. | | | | | | | |
| 1105 | (3) One bar shall be located in the top four inches (102 mm), one bar in the bottom four inches (102 mm) and the other bars equally spaced between. Such bar placement satisfies the requirements of Section 1805.9. Corner reinforcing shall be provided so as to lap 24 inches (610 mm). | | | | | | | |
| 1106 | (4) Bars shall be placed within two inches (51 mm) of the openings and extend 24 inches (610 mm) beyond the edge of the opening; vertical bars may terminate three inches (76 mm) from the top of the concrete. | | | | | | | |
| 1107 | (5) Dowels of #4 bar at 32 inches on center shall be provided in the footing, extending 18 inches (457 mm) into the foundation wall. | | | | | | | |
| 1108 | (6) Diaphragm shall conform to the requirements of Section 2308. | | | | | | | |

- | | |
|------|---|
| 1109 | (7) Footing shall be a minimum of nine inches thick by 20 inches wide. |
| 1110 | (8) Soil backfill shall be soil classification types GW, GP, SW, or SP, per Table 1610.1. Soil shall not be submerged or saturated in groundwater." |

1111 ~~[(3) In IBC, Section 1904.2, a new exception 1 is added as follows and the current~~
 1112 ~~exception is modified to be number 2.]~~

1113 ~~[Exceptions:]~~

1114 ~~["1. In ACI Table 4.3.1, for Exposure Class F1, change Maximum w/cm from 0.45 to~~
 1115 ~~0.5 and Minimum f_c from 4,500 psi to 3,000 psi."]~~

1116 ~~[(4)]~~ (3) A new IBC, Section ~~[1905.1.11]~~ 1905.1.9, is added as follows: ~~["1905.1.11]~~
 1117 ~~"1905.1.9~~ ACI 318, Table 4.2.1." Modify ACI 318, Table ~~[4.2.1]~~ 19.3.1.1 to read as follows:
 1118 In the portion of the table designated as "Conditions", the following Exposure ~~[categories]~~
 1119 category and ~~[classes are]~~ class is deleted and replaced with the following:

1120 "F0: Concrete elements not exposed to freezing and thawing cycles to include footing and
 1121 foundation elements that are completely buried in soil."

1122 ~~[F1: Concrete elements exposed to freezing and thawing cycles and are not likely to be~~
 1123 ~~saturated or exposed to deicing chemicals.]~~

1124 ~~[F2: Concrete elements exposed to freezing and thawing cycles and are likely to be saturated,~~
 1125 ~~but not exposed to deicing chemicals.]~~

1126 ~~[F3: Concrete elements exposed to freezing and thawing cycles and are likely to be saturated~~
 1127 ~~and exposed to deicing chemicals."]~~

1128 Section 13. Section **15A-3-110** is amended to read:

1129 **15A-3-110. Amendments to Chapters 23 through 25 of IBC.**

1130 (1) A new IBC, Section 2306.1.5, is added as follows: "2306.1.5 Load duration factors.
 1131 The allowable stress increase of 1.15 for snow load, shown in Table 2.3.2, Frequently Used
 1132 Load Duration Factors, Cd, of the National Design Specifications, shall not be utilized at
 1133 elevations above 5,000 feet (1,524 M)."

1134 (2) In IBC, Section ~~[2308.6]~~ 2308.3.1, a new exception, 3, is added as follows:
 1135 ~~"[Exception:]~~ 3. Where foundation plates or sills are bolted or anchored to the foundation with

1136 not less than 1/2 inch (12.7 mm) diameter steel bolts or approved anchors, embedded at least 7
1137 inches (178 mm) into concrete or masonry and spaced not more than 32 inches (816 mm) apart,
1138 there shall be a minimum of two bolts or anchor straps per piece located not less than 4 inches
1139 (102 mm) from each end of each piece. A properly sized nut and washer shall be tightened on
1140 each bolt to the plate."

1141 (3) IBC, Section 2506.2.1, is deleted and replaced with the following: "2506.2.1 Other
1142 materials. Metal suspension systems for acoustical and lay-in panel ceilings shall conform with
1143 ASTM C635 listed in Chapter 35 and Section 13.5.6 of ASCE 7, as amended in Section
1144 [~~1613.8~~] 1613.5, for installation in high seismic areas."

1145 Section 14. Section **15A-3-112** is amended to read:

1146 **15A-3-112. Amendments to Chapters 29 through 31 of IBC.**

1147 (1) In IBC [P] Table 2902.1 the following changes are made:

1148 (a) The title for [P] Table 2902.1 is deleted and replaced with the following: "[P] Table
1149 2902.1, Minimum Number of Required Plumbing Facilities ^{a, h}".

1150 (b) In the row for "E" occupancy in the field for "OTHER" a new footnote i is added.

1151 (c) In the row for "I-4" occupancy in the field for "OTHER" a new footnote i is added.

1152 (d) A new footnote h is added as follows: "FOOTNOTE: h. When provided, in public
1153 toilet facilities there shall be an equal number of diaper changing facilities in male toilet rooms
1154 and female toilet rooms."

1155 (e) A new footnote i is added to the table as follows: "FOOTNOTE i: Non-residential
1156 child care facilities shall comply with additional sink requirements of Utah Administrative
1157 Code R430-100-4."

1158 (2) A new IBC, Section [P]2902.7, is added as follows:

1159 "[P]2902.7 Toilet Facilities for Workers.

1160 Toilet facilities shall be provided for construction workers and such facilities shall be
1161 maintained in a sanitary condition. Construction worker toilet facilities of the nonsewer type
1162 shall conform to ANSI Z4.3."

1163 [~~(2)~~] (3) In IBC, Section 3006.5, a new exception is added as follows: "Exception:

1164 Hydraulic elevators and roped hydraulic elevators with a rise of 50 feet or less."

1165 Section 15. Section **15A-3-113** is amended to read:

1166 **15A-3-113. Amendments to Chapters 32 through 35 of IBC.**

1167 [~~1) A new section IBC, Section 3401.7, is added as follows: "3401.7 Parapet bracing,~~
1168 ~~wall anchors, and other appendages. Until June 30, 2014, a building constructed before 1975~~
1169 ~~shall have parapet bracing, wall anchors, and appendages such as cornices, spires, towers,~~
1170 ~~tanks, signs, statuary, etc. evaluated by a licensed engineer when the building is undergoing~~
1171 ~~structural alterations, which may include structural sheathing replacement of 10% or greater, or~~
1172 ~~other structural repairs. Reroofing or water membrane replacement may not be considered a~~
1173 ~~structural alteration or repair for purposes of this section. Beginning July 1, 2014, a building~~
1174 ~~constructed before 1975 shall have parapet bracing, wall anchors, and appendages such as~~
1175 ~~cornices, spires, towers, tanks, signs, statuary, etc. evaluated by a licensed engineer when the~~
1176 ~~building is undergoing a total reroofing. Parapet bracing, wall anchors, and appendages~~
1177 ~~required by this section shall be evaluated in accordance with 75% of the seismic forces as~~
1178 ~~specified in Section 1613. When allowed by the local building official, alternate methods of~~
1179 ~~equivalent strength as referenced in an approved code under Utah Code, Subsection~~
1180 ~~15A-1-204(6)(a), will be considered when accompanied by engineer-sealed drawings, details,~~
1181 ~~and calculations. When found to be deficient because of design or deteriorated condition, the~~
1182 ~~engineer's recommendations to anchor, brace, reinforce, or remove the deficient feature shall be~~
1183 ~~implemented.]~~

1184 [Exceptions:]

1185 [1. ~~Group R-3 and U occupancies.]~~

1186 [2. ~~Unreinforced masonry parapets need not be braced according to the above stated provisions~~
1187 ~~provided that the maximum height of an unreinforced masonry parapet above the level of the~~
1188 ~~diaphragm tension anchors or above the parapet braces shall not exceed one and one-half times~~
1189 ~~the thickness of the parapet wall. The parapet height may be a maximum of two and one-half~~
1190 ~~times its thickness in other than Seismic Design Categories D, E, or F."]~~

1191 [(2) IBC, Section 3408.4, is deleted and replaced with the following: "3408.4 Seismic-

1192 When a change in occupancy results in a structure being reclassified to a higher Risk Category
 1193 (as defined in Table 1604.5), or when such change of occupancy results in a design occupant
 1194 load increase of 100% or more, the structure shall conform to the seismic requirements for a
 1195 new structure.]

1196 [Exceptions:]

1197 [1. Specific seismic detailing requirements of this code or ASCE 7 for a new structure shall
 1198 not be required to be met where it can be shown that the level of performance and seismic
 1199 safety is equivalent to that of a new structure. A demonstration of equivalence analysis shall
 1200 consider the regularity, overstrength, redundancy, and ductility of the structure. Alternatively,
 1201 the building official may allow the structure to be upgraded in accordance with referenced
 1202 sections as found in an approved code under Utah Code, Subsection 15A-1-204(6)(a).]

1203 [2. When a change of use results in a structure being reclassified from Risk Category I or II to
 1204 Risk Category III and the structure is located in a seismic map area where SDS is less than
 1205 0.33, compliance with the seismic requirements of this code and ASCE 7 are not required.]

1206 [3. Where design occupant load increase is less than 25 occupants and the Risk Category does
 1207 not change."]

1208 [(3)] (1) In IBC, Chapter 35, the referenced standard ICCA117.1-09, Section 606.2,
 1209 Exception 1 is modified to include the following sentence at the end of the exception:

1210 "The minimum clear floor space shall be centered on the sink assembly."

1211 [(4)] (2) The following referenced standard is added under UL in IBC, Chapter 35:

| "Number | Title | Referenced in code section number |
|-----------|---|-----------------------------------|
| 2034-2008 | Standard of Single- and Multiple-station Carbon Monoxide Alarms | 907.9" |

1214 Section 16. Section 15A-3-202 is amended to read:

1215 **15A-3-202. Amendments to Chapters 1 through 5 of IRC.**

1216 (1) In IRC, Section R102, a new Section R102.7.2 is added as follows: "R102.7.2

1217 Physical change for bedroom window egress. A structure whose egress window in an existing
1218 bedroom is smaller than required by this code, and that complied with the construction code in
1219 effect at the time that the bedroom was finished, is not required to undergo a physical change to
1220 conform to this code if the change would compromise the structural integrity of the structure or
1221 could not be completed in accordance with other applicable requirements of this code,
1222 including setback and window well requirements."

1223 (2) In IRC, Section 109:

1224 (a) A new IRC, Section 109.1.5, is added as follows: "R109.1.5 Weather-resistant
1225 exterior wall envelope inspections. An inspection shall be made of the weather-resistant
1226 exterior wall envelope as required by Section R703.1 and flashings as required by Section
1227 R703.8 to prevent water from entering the weather-resistive barrier."

1228 (b) The remaining sections are renumbered as follows: R109.1.6 Other inspections;
1229 R109.1.6.1 Fire- and smoke-resistance-rated construction inspection; R109.1.6.2 Reinforced
1230 masonry, insulating concrete form (ICF) and conventionally formed concrete wall inspection;
1231 and R109.1.7 Final inspection.

1232 (3) IRC, Section R114.1, is deleted and replaced with the following: "R114.1 Notice to
1233 owner. Upon notice from the building official that work on any building or structure is being
1234 prosecuted contrary to the provisions of this code or other pertinent laws or ordinances or in an
1235 unsafe and dangerous manner, such work shall be immediately stopped. The stop work order
1236 shall be in writing and shall be given to the owner of the property involved, or to the owner's
1237 agent or to the person doing the work; and shall state the conditions under which work will be
1238 permitted to resume."

1239 (4) In IRC, Section R202, the following definition is added: "CERTIFIED
1240 BACKFLOW PREVENTER ASSEMBLY TESTER: A person who has shown competence to
1241 test Backflow prevention assemblies to the satisfaction of the authority having jurisdiction
1242 under Utah Code, Subsection [19-4-104\(4\)](#)."

1243 (5) In IRC, Section R202, the definition for "CONDITIONED SPACE" is modified by
1244 deleting the words at the end of the sentence "being heated or cooled by any equipment or

1245 appliance" and replacing them with the following: "enclosed within the building thermal
1246 envelope that is directly heated or cooled, or indirectly heated or cooled by any of the following
1247 means:

- 1248 1. Openings directly into an adjacent conditioned space.
- 1249 2. An un-insulated floor, ceiling or wall adjacent to a conditioned space.
- 1250 3. Un-insulated duct, piping or other heat or cooling source within the space."

1251 (6) In IRC, Section R202, the definition of "Cross Connection" is deleted and replaced
1252 with the following: "CROSS CONNECTION. Any physical connection or potential
1253 connection or arrangement between two otherwise separate piping systems, one of which
1254 contains potable water and the other either water of unknown or questionable safety or steam,
1255 gas, or chemical, whereby there exists the possibility for flow from one system to the other,
1256 with the direction of flow depending on the pressure differential between the two systems (see
1257 "Backflow, Water Distribution")."

1258 (7) In IRC, Section 202, in the definition for gray water a comma is inserted after the
1259 word "washers"; the word "and" is deleted; and the following is added to the end: "and clear
1260 water wastes which have a pH of 6.0 to 9.0; are non-flammable; non-combustible; without
1261 objectionable odors; non-highly pigmented; and will not interfere with the operation of the
1262 sewer treatment facility."

1263 (8) In IRC, Section R202, the definition of "Potable Water" is deleted and replaced
1264 with the following: "POTABLE WATER. Water free from impurities present in amounts
1265 sufficient to cause disease or harmful physiological effects and conforming to the Utah Code,
1266 Title 19, [~~Chapters~~] Chapter 4, Safe Drinking Water Act, and Title 19, Chapter 5, Water
1267 Quality Act, and the regulations of the public health authority having jurisdiction."

1268 (9) IRC, Figure R301.2(5), is deleted and replaced with Table R301.2(5a) and Table
1269 R301.2(5b) as follows:

| | | | | |
|--|--------|----|---|----|
| "TABLE NO. R301.2(5a) | | | | |
| STATE OF UTAH - REGIONAL SNOW LOAD FACTORS | | | | |
| | COUNTY | Po | S | Ao |

| | | | | |
|------|-----------|----|----|-----|
| 1273 | Beaver | 43 | 63 | 6.2 |
| 1274 | Box Elder | 43 | 63 | 5.2 |
| 1275 | Cache | 50 | 63 | 4.5 |
| 1276 | Carbon | 43 | 63 | 5.2 |
| 1277 | Daggett | 43 | 63 | 6.5 |
| 1278 | Davis | 43 | 63 | 4.5 |
| 1279 | Duchesne | 43 | 63 | 6.5 |
| 1280 | Emery | 43 | 63 | 6.0 |
| 1281 | Garfield | 43 | 63 | 6.0 |
| 1282 | Grand | 36 | 63 | 6.5 |
| 1283 | Iron | 43 | 63 | 5.8 |
| 1284 | Juab | 43 | 63 | 5.2 |
| 1285 | Kane | 36 | 63 | 5.7 |
| 1286 | Millard | 43 | 63 | 5.3 |
| 1287 | Morgan | 57 | 63 | 4.5 |
| 1288 | Piute | 43 | 63 | 6.2 |
| 1289 | Rich | 57 | 63 | 4.1 |
| 1290 | Salt Lake | 43 | 63 | 4.5 |
| 1291 | San Juan | 43 | 63 | 6.5 |
| 1292 | Sanpete | 43 | 63 | 5.2 |
| 1293 | Sevier | 43 | 63 | 6.0 |
| 1294 | Summit | 86 | 63 | 5.0 |
| 1295 | Tooele | 43 | 63 | 4.5 |
| 1296 | Uintah | 43 | 63 | 7.0 |
| 1297 | Utah | 43 | 63 | 4.5 |
| 1298 | Wasatch | 86 | 63 | 5.0 |

| | | | | |
|------|------------|----|----|-----|
| 1299 | Washington | 29 | 63 | 6.0 |
| 1300 | Wayne | 36 | 63 | 6.5 |
| 1301 | Weber | 43 | 63 | 4.5 |

TABLE NO. R301.2(5b)

REQUIRED SNOW LOADS FOR SELECTED UTAH CITIES AND TOWNS^{1,2}

The following jurisdictions require design snow load values that differ from the Equation in the Utah Snow Load Study.

| | County | City | Elevation | Ground Snow Load (psf) | Roof Snow Load (psf) ⁶ |
|------|----------|---|-------------|------------------------|-----------------------------------|
| 1306 | Carbon | Price ³ | 5550 | 43 | 30 |
| | | All other county locations ⁵ | -- | -- | -- |
| 1307 | Davis | Fruit Heights ³ | 4500 - 4850 | 57 | 40 |
| 1308 | Emery | Green River ³ | 4070 | 36 | 25 |
| 1309 | Garfield | Panguitch ³ | 6600 | 43 | 30 |
| 1310 | Rich | Woodruff ³ | 6315 | 57 | 40 |
| | | Laketown ⁴ | 6000 | 57 | 40 |
| | | Garden City ⁵ | -- | -- | -- |
| | | Randolph ⁴ | 6300 | 57 | 40 |
| 1311 | San Juan | Monticello ³ | 6820 | 50 | 35 |
| 1312 | Summit | Coalville ³ | 5600 | 86 | 60 |
| | | Kamas ⁴ | 6500 | 114 | 80 |
| 1313 | Tooele | Tooele ³ | 5100 | 43 | 30 |
| 1314 | Utah | Orem ³ | 4650 | 43 | 30 |
| | | Pleasant Grove ⁴ | 5000 | 43 | 30 |
| | | Provo ⁵ | -- | -- | -- |
| 1315 | Wasatch | Heber ⁵ | -- | -- | -- |

| | | | | | |
|------|--|---|------|----|----|
| 1316 | Washington | Leeds ³ | 3460 | 29 | 20 |
| | | Santa Clara ³ | 2850 | 21 | 15 |
| | | St. George ³ | 2750 | 21 | 15 |
| | | All other county locations ⁵ | -- | -- | -- |
| 1317 | Wayne | Loa ³ | 7080 | 43 | 30 |
| 1318 | 1The IRC requires a minimum live load -- See R301.6. | | | | |
| 1319 | 2This table is informational only in that actual site elevations may vary. Table is only valid if site elevation is within 100 feet of the listed elevation. Otherwise, contact the local Building Official. | | | | |
| 1320 | 3Values adopted from Table VII of the Utah Snow Load Study | | | | |
| 1321 | 4Values based on site-specific study. Contact local Building Official for additional information. | | | | |
| 1322 | 5Contact local Building Official. | | | | |
| 1323 | 6Based on Ce =1.0, Ct =1.0 and Is =1.0" | | | | |

1324 (10) IRC, Section R301.6, is deleted and replaced with the following: "R301.6 Utah
 1325 Snow Loads. The snow loads specified in Table R301.2(5b) shall be used for the jurisdictions
 1326 identified in that table. Otherwise, the ground snow load, P_g , to be used in the determination
 1327 of design snow loads for buildings and other structures shall be determined by using the
 1328 following formula: $P_g = (P_o^2 + S^2(A-A_o)^2)^{0.5}$ for A greater than A_o , and $P_g = P_o$ for A less
 1329 than or equal to A_o .

1330 WHERE:

1331 P_g = Ground snow load at a given elevation (psf);

1332 P_o = Base ground snow load (psf) from Table No. R301.2(5a);

1333 S = Change in ground snow load with elevation (psf/100 ft.) From Table No. R301.2(5a);

1334 A = Elevation above sea level at the site (ft./1,000);

1335 A_o = Base ground snow elevation from Table R301.2(5a) (ft./1,000).

1336 The building official may round the roof snow load to the nearest 5 psf. The ground snow

1337 load, Pg, may be adjusted by the building official when a licensed engineer or architect submits
1338 data substantiating the adjustments.

1339 Where the minimum roof live load in accordance with Table R301.6 is greater than the design
1340 roof snow load, such roof live load shall be used for design, however, it shall not be reduced to
1341 a load lower than the design roof snow load. Drifting need not be considered for roof snow
1342 loads less than 20 psf."

1343 ~~[(11) In IRC, Section R302.2, the words "Exception: A" are deleted and replaced with~~
1344 ~~the following:]~~

1345 [~~"Exceptions:~~

1346 ~~[1. A common 2-hour fire-resistance-rated wall is permitted for townhouses if such walls do~~
1347 ~~not contain plumbing or mechanical equipment, ducts or vents in the cavity of the common~~
1348 ~~wall. Electrical installation shall be installed in accordance with Chapters 34 through 43.~~
1349 ~~Penetrations of electrical outlet boxes shall be in accordance with Section R302.4.]~~

1350 ~~[2. In buildings equipped with an automatic residential fire sprinkler system, a"]~~

1351 ~~[(12) In IRC, Section R302.2.4, a new exception 6 is added as follows: "6.~~

1352 ~~Townhouses separated by a common 2-hour fire-resistance-rated wall as provided in Section~~
1353 ~~R302.2."]~~

1354 ~~[(13)]~~ (11) In IRC, Section R302.5.1, the words "self-closing device" are deleted and
1355 replaced with "self-latching hardware".

1356 (12) IRC, Section R302.13, is deleted.

1357 ~~[(14)]~~ (13) In IRC, Section R303.4, the number "5" is changed to "3" in the first
1358 sentence.

1359 ~~[(15)]~~ (14) IRC, Sections R311.7.4 through ~~[R311.7.4.3]~~ R311.7.5.3, are deleted and
1360 replaced with the following: "R311.7.4 Stair treads and risers. ~~[R311.7.4.1]~~ R311.7.5.1 Riser
1361 height. The maximum riser height shall be 8 inches (203 mm). The riser shall be measured
1362 vertically between leading edges of the adjacent treads. The greatest riser height within any
1363 flight of stairs shall not exceed the smallest by more than 3/8 inch (9.5 mm).

1364 ~~[R311.7.4.2]~~ R311.7.5.2 Tread depth. The minimum tread depth shall be 9 inches (228 mm).

1365 The tread depth shall be measured horizontally between the vertical planes of the foremost
 1366 projection of adjacent treads and at a right angle to the tread's leading edge. The greatest tread
 1367 depth within any flight of stairs shall not exceed the smallest by more than 3/8 inch (9.5 mm).
 1368 Winder treads shall have a minimum tread depth of 10 inches (254 mm) measured as above at
 1369 a point 12 inches (305 mm) from the side where the treads are narrower. Winder treads shall
 1370 have a minimum tread depth of 6 inches (152 mm) at any point. Within any flight of stairs, the
 1371 greatest winder tread depth at the 12-inch (305 mm) walk line shall not exceed the smallest by
 1372 more than 3/8 inch (9.5 mm).

1373 [~~R311.7.4.3~~] R311.7.5.3 Profile. The radius of curvature at the leading edge of the tread shall
 1374 be no greater than 9/16 inch (14.3 mm). A nosing not less than 3/4 inch (19 mm) but not more
 1375 than 1 1/4 inches (32 mm) shall be provided on stairways with solid risers. The greatest nosing
 1376 projection shall not exceed the smallest nosing projection by more than 3/8 inch (9.5 mm)
 1377 between two stories, including the nosing at the level of floors and landings. Beveling of
 1378 nosing shall not exceed 1/2 inch (12.7 mm). Risers shall be vertical or sloped from the
 1379 underside of the leading edge of the tread above at an angle not more than 30 degrees (0.51 rad)
 1380 from the vertical. Open risers are permitted, provided that the opening between treads does not
 1381 permit the passage of a 4-inch diameter (102 mm) sphere.

1382 Exceptions.

- 1383 1. A nosing is not required where the tread depth is a minimum of 10 inches (254 mm).
- 1384 2. The opening between adjacent treads is not limited on stairs with a total rise of 30 inches
 1385 (762 mm) or less."

1386 [~~(16) In IRC, Section R312.1.2, the words "adjacent fixed seating" are deleted.]~~

1387 [~~(17)~~] (15) IRC, Section R312.2, is deleted.

1388 [~~(18)~~] (16) IRC, Sections R313.1 through R313.2.1, are deleted and replaced with the
 1389 following: "R313.1 Design and installation. When installed, automatic residential fire
 1390 sprinkler systems for townhouses or one- and two-family dwellings shall be designed and
 1391 installed in accordance with Section P2904 or NFPA 13D."

1392 (17) In IRC, Section 315.3, the following words are added to the first sentence after the

1393 word "installed": "on each level of the dwelling unit and".

1394 ~~[(19) A new]~~ (18) In IRC, Section R315.5, a new exception, 3, is added as follows:

1395 [~~"R315.5 Power source. Carbon monoxide alarms shall receive their primary power from the~~
1396 ~~building wiring when such wiring is served from a commercial source, and when primary~~
1397 ~~power is interrupted, shall receive power from a battery. Wiring shall be permanent and~~
1398 ~~without a disconnecting switch other than those required for over-current protection.]~~

1399 [Exceptions:]

1400 [~~1. Carbon monoxide alarms shall be permitted to be battery operated when installed in~~
1401 ~~buildings without commercial power.]~~

1402 [~~2]~~ "3. Hard wiring of carbon monoxide alarms in existing areas shall not be required where
1403 the alterations or repairs do not result in the removal of interior wall or ceiling finishes
1404 exposing the structure, unless there is an attic, crawl space or basement available which could
1405 provide access for hard wiring, without the removal of interior finishes."

1406 ~~[(20)]~~ (19) A new IRC, Section [~~R315.6]~~ R315.7, is added as follows: "[~~R315.6]~~
1407 R315.7 Interconnection. Where more than one carbon monoxide alarm is required to be
1408 installed within an individual dwelling unit in accordance with Section R315.1, the alarm
1409 devices shall be interconnected in such a manner that the actuation of one alarm will activate
1410 all of the alarms in the individual unit. Physical interconnection of smoke alarms shall not be
1411 required where listed wireless alarms are installed and all alarms sound upon activation of one
1412 alarm.

1413 Exception: Interconnection of carbon monoxide alarms in existing areas shall not be required
1414 where alterations or repairs do not result in removal of interior wall or ceiling finishes exposing
1415 the structure, unless there is an attic, crawl space or basement available which could provide
1416 access for interconnection without the removal of interior finishes."

1417 ~~[(21)]~~ (20) In IRC, Section R403.1.6, a new Exception [~~4]~~ 3 is added as follows: "[~~4]~~ 3.
1418 When anchor bolt spacing does not exceed 32 inches (813 mm) apart, anchor bolts may be
1419 placed with a minimum of two bolts per plate section located not less than 4 inches (102 mm)
1420 from each end of each plate section at interior bearing walls, interior braced wall lines, and at

1421 all exterior walls."

1422 ~~[(22)]~~ (21) In IRC, Section R403.1.6.1, a new exception is added at the end of Item 2
1423 and Item 3 as follows: "Exception: When anchor bolt spacing does not exceed 32 inches (816
1424 mm) apart, anchor bolts may be placed with a minimum of two bolts per plate section located
1425 not less than 4 inches (102 mm) from each end of each plate section at interior bearing walls,
1426 interior braced wall lines, and at all exterior walls."

1427 ~~[(23)]~~ (22) In IRC, Section R404.1, a new exception is added as follows: "Exception:
1428 As an alternative to complying with Sections R404.1 through R404.1.5.3, concrete and
1429 masonry foundation walls may be designed in accordance with IBC Sections 1807.1.5 and
1430 1807.1.6 as amended in Section 1807.1.6.4 and Table 1807.1.6.4 under these rules."

1431 ~~[(24) IRC, Section R501.3, is deleted.]~~

1432 Section 17. Section **15A-3-203** is amended to read:

1433 **15A-3-203. Amendments to Chapters 6 through 15 of IRC.**

1434 (1) In IRC, Section ~~[N1101.8]~~ N1101.5 (R103.2), all words after the words "herein
1435 governed." are deleted and replaced with the following: "Construction documents include all
1436 documentation required to be submitted in order to issue a building permit."

1437 (2) In IRC, Section ~~[N1101.14]~~ N1101.12 (R303.3), all wording after the first sentence
1438 is deleted.

1439 (3) In IRC, Section N1101.13 (R401.2), add Exception as follows:

1440 "Exception: A project complies if the project demonstrates compliance, using the
1441 software RESCheck 2012 Utah Energy Conservation Code, of:

1442 (a) on or after January 1, 2017, and before January 1, 2019, "3 percent better than
1443 code";

1444 (b) on or after January 1, 2019, and before January 1, 2021, "4 percent better than
1445 code"; and

1446 (c) after January 1, 2021, "5 percent better than code"."

1447 ~~[(3)]~~ (4) In IRC, Table ~~[N1102.1.1 (R402.1.1) and Table N1102.1.3 (R402.1.3)]~~, the
1448 rows for "climate zone 3", "climate zone 5 and Marine 4", and "climate zone 6" are deleted and

1449 ~~replaced and~~] N1102.2 (R402.1.2), in the column titled MASS WALL R-VALUE, a new
 1450 footnote j is added as follows:
 1451 "j. Log walls complying with ICC400 and with a minimum average wall thickness of 5 inches
 1452 or greater shall be permitted in Zones 5 through 8 when overall window glazing has a .31
 1453 U-factor or lower, minimum heating equipment efficiency is 90 AFUE (gas) or 84 AFUE (oil),
 1454 and all other component requirements are met."
 1455 [

| "TABLE N1102.1.1 (R402.1.1) | | | | | | | | | | |
|--|------------------------------------|--------------------------------|---|-----------------|------------------------------|--------------------------------|-----------------|------------------------------------|-----------------------------------|---------------------------------------|
| INSULATION AND FENESTRATION REQUIREMENTS BY COMPONENT ^a | | | | | | | | | | |
| CLIMATE ZONE | FENESTRATION U-FACTOR ^a | SKYLIGHT ^b U-FACTOR | GLAZED FENESTRATION SHGC ^{b,c} | CEILING R-VALUE | WOOD FRAME WALL R-VALUE | MASS WALL R-VALUE ^d | FLOOR R-VALUE | BASEMENT ^e WALL R-VALUE | SLAB ^f R-VALUE & DEPTH | CRAWL SPACE ^g WALL R-VALUE |
| 3 | 0.65 | 0.65 | 0.40 | 30 | 15 | 5 | 19 | 0 | 0 | 5/13 |
| 5 and Marine 4 | 0.35 | 0.60 | NR | 38 | 19 or 13 + 5 ^h | 13 | 30 ^e | 10/13 | 10, 2 ft | 10/13 |
| 6 | 0.35 | 0.60 | NR | 49 | 19 or 13 + 5 ^h | 15 | 30 ^e | 10/13 | 10, 4 ft | 10/13 |

^aj. Log walls complying with ICC400 and with a minimum average wall thickness of 5" or greater shall be permitted in Zones 5-8 when overall window glazing is .31 U-factor or lower, minimum heating equipment efficiency is 90 AFUE (gas) or 84 AFUE (oil), and all other component requirements are met."

1463 -

| TABLE N1102.1.3 (R402.1.3) | | | | | | | | | |
|-----------------------------------|-----------------------|-------------------|------------------|---------------------|---------------------------------|----------------|------------------------|---------------------------|--|
| EQUIVALENT U-FACTORS ^a | | | | | | | | | |
| CLIMATE ZONE | FENESTRATION U-FACTOR | SKYLIGHT U-FACTOR | CEILING U-FACTOR | FRAME WALL U-FACTOR | MASS WALL U-FACTOR ^b | FLOOR U-FACTOR | BASEMENT WALL U-FACTOR | CRAWL SPACE WALL U-FACTOR | |
| 3 | 0.65 | 0.65 | 0.035 | 0.082 | 0.141 | 0.047 | 0.360 | 0.136 | |
| 5 and Marine 4 | 0.35 | 0.60 | 0.030 | 0.060 | 0.082 | 0.033 | 0.059 | 0.065 | |
| 6 | 0.35 | 0.60 | 0.026 | 0.060 | 0.060 | 0.033 | 0.059 | 0.065 | |

1469] [(4) In IRC, Section N1102.2.1 (R402.2.1), the last sentence is deleted.]

- 1470 [~~(5)~~ In IRC, Section N1102.2.2 (R402.2.2), the last sentence is deleted.]
- 1471 [~~(6)~~ In IRC, Section N1102.3.3 (R402.3.3), the last sentence is deleted.]
- 1472 [~~(7)~~ In IRC, Section N1102.3.4 (R402.3.4), the last sentence is deleted.]
- 1473 [~~(8)~~ (5) In IRC, Section N1102.4.1 (R402.4.1), in the first sentence, the word "and" is
- 1474 deleted and replaced with the word "or".
- 1475 [~~(9)~~ (6) In IRC, Section N1102.4.1.1 (R402.4.1.1), the last sentence is deleted and
- 1476 replaced with the following: "Where allowed by the [~~building~~] code official, the builder may
- 1477 certify compliance to components criteria for items which may not be inspected during
- 1478 regularly scheduled inspections."
- 1479 [~~(10)~~ (7) In IRC, Section N1102.4.1.2 (R402.4.1.2), the following changes are made:
- 1480 (a) In the first sentence:
- 1481 (i) on or after January 1, 2019, and before January 1, 2021, replace the word "five"
- 1482 with "3.5"; and
- 1483 (ii) after January 1, 2021, replace the word "five" with "three."
- 1484 [~~(a)~~ (b) In the first sentence, the words "in Climate Zones 1 and 2, and [~~3~~] three air
- 1485 changes per hour in [~~Zone~~] Climate Zones 3 through 8" are deleted.
- 1486 [~~(b)~~ (c) In the third sentence, [~~the words "Where required by the building official,"~~
- 1487 ~~and~~] the word "third" [~~are~~] is deleted.
- 1488 [~~(c)~~ (d) The following sentence is inserted after the third sentence: "The following
- 1489 parties shall be approved to conduct testing: Parties certified by BPI or RESNET, or licensed
- 1490 contractors who have completed training provided by Blower Door Test equipment
- 1491 manufacturers or other comparable training."
- 1492 [~~(11)~~ In IRC, Section N1102.4.4 (R402.4.4), the last sentence is deleted.]
- 1493 [~~(12)~~ In IRC, Section N1103.2.2 (R403.2.2), the requirements for total leakage testing
- 1494 are deleted and replaced with the following:]
- 1495 [~~"1. Postconstruction test: Total leakage shall be less than or equal to 10 cfm (283~~
- 1496 ~~L/min) per 100 square feet (9.29 m2) of conditioned floor space when tested at a pressure~~
- 1497 ~~differential of 0.1 inches w.g. (25 Pa) across the entire system, including the manufacturer's air~~

1498 handler enclosure. All register boots shall be taped or otherwise sealed during the test.]
1499 [2. Rough-in test: Total leakage shall be less than or equal to 10 cfm (283 L/min) per
1500 100 square feet (9.29 m²) of conditioned floor area when tested at a pressure differential of at
1501 least 0.1 inches w.g. (25 Pa) across the system, including the manufacturer's air handler
1502 enclosure. All registers shall be taped or otherwise sealed during the test. If the air handler is
1503 not installed at the time of the test, total leakage shall be less than or equal to 7.5 cfm (212
1504 L/min) per 100 square feet (9.29 m²) of conditioned floor area."]

1505 [(13)] (8) In IRC, Section [N1103.2.2 (R403.2.2);] N1103.3.3 (R403.3.3):

1506 (a) the exception for [total] duct air leakage testing is deleted; and

1507 (b) the exception for duct air leakage is replaced:

1508 (i) on or after January 1, 2017, and before January 1, 2019, with the following:

1509 "Exception: The [total] duct air leakage test is not required for systems with all air handlers and
1510 at least [50%] 65% of all ducts (measured by length) located entirely within the building
1511 thermal envelope.";

1512 (ii) on or after January 1, 2019, and before January 1, 2021, with the following:

1513 "Exception: The duct air leakage test is not required for systems with all air handlers and at
1514 least 75% of all ducts (measured by length) located entirely within the building thermal
1515 envelope."; and

1516 (iii) on or after January 1, 2021, with the following: "Exception: The duct air leakage
1517 test is not required for systems with all air handlers and at least 80% of all ducts (measured by
1518 length) located entirely within the building thermal envelope."

1519 (9) In IRC, Section N1103.3.3 (R403.3.3), the following is added after the exception:
1520 "The following parties shall be approved to conduct testing: Parties certified by BPI or
1521 RESNET, or licensed contractors who have completed either training provided by Duct Test
1522 equipment manufacturers or other comparable training."

1523 (10) In IRC, Section N1103.3.4 (R403.3.4):

1524 (a) in Subsection 1, the number 4 is changed to 8, the number 113.3 is changed to 170,
1525 the number 3 is changed to 6, the number 85 is changed to 114.6; and

1526 (b) in Subsection 2:

1527 (i) on or after January 1, 2017, and before January 1, 2019, the number 4 is changed to
1528 8 and the number 113.3 is changed to 226.5;

1529 (ii) on or after January 1, 2019, and before January 1, 2021, the number 4 is changed to
1530 7 and the number 113.3 is changed to 198.2; and

1531 (iii) on or after January 1, 2021, the number 4 is changed to 6 and the number 113.3 is
1532 changed to 169.9.

1533 ~~[(14)]~~ (11) In IRC, Section ~~[N1103.2.3 (R403.2.3)]~~ N1103.3.5 (R403.3.5), the words
1534 "or plenums" are deleted.

1535 ~~[(15) In IRC, Section N1103.4.2 (R403.4.2), the sentences for "3.", "9.", and the last~~
1536 ~~sentence are deleted.]~~

1537 ~~[(16) In IRC, Section N1103.5 (R403.5), the first sentence is deleted.]~~

1538 ~~[(17) IRC, Section N1104.1 (R404.1) and the exception are deleted, and N1104.1.1~~
1539 ~~(R404.1.1) becomes N1104.1 (R404.1).]~~

1540 ~~[(18) In IRC, Table N1105.5.2(1) (R405.5.2(1)), the following changes are made under~~
1541 ~~the column STANDARD REFERENCE DESIGN:]~~

1542 ~~[(a) In the row "Air exchange rate", the words "in Zones 1 and 2, and 3 air changes per~~
1543 ~~hour in Zones 3 through 8" are deleted.]~~

1544 ~~[(b) In the row "Heating systems^{f, g}", the standard reference design is deleted and~~
1545 ~~replaced with the following:]~~

1546 ~~["Fuel Type: same as proposed design]~~

1547 ~~[Efficiencies:]~~

1548 ~~[Electric: air source heat pump with prevailing federal minimum efficiencies]~~

1549 ~~[Nonelectric furnaces: natural gas furnace with prevailing federal minimum~~
1550 ~~efficiencies]~~

1551 ~~[Nonelectric boilers: natural gas boiler with prevailing federal minimum efficiencies]~~

1552 ~~[Capacity: sized in accordance with Section N1103.6"]~~

1553 ~~[(c) In the row "Cooling systems^{f, h}" the words "As proposed" are deleted and replaced~~

1554 with the following:]

1555 ["Fuel Type: Electric]

1556 [Efficiency: in accordance with prevailing federal minimum standards"]

1557 [(d) In the row "Service water heating^{f,g,h,i}", the words "As proposed" are deleted and
1558 replaced with the following:]

1559 ["Fuel Type: same as proposed design]

1560 [Efficiency: in accordance with prevailing federal minimum standards]

1561 [Tank Temperature: 120° F"]

1562 [(e) In the row "Thermal distribution systems" the word "none" is deleted and replaced
1563 with the following: "Thermal distribution system efficiency (DSE) of .080 shall be applied to
1564 both the heating and cooling system efficiencies."]

1565 [(19) In Table N1105.5.2(2) (R405.5.2(2)), the number "0.80" is inserted under
1566 "Forced air systems" for "Distribution system components located in unconditioned space".]

1567 (12) In IRC, Section N1103.5.3 (R403.5.3), Subsection 5 is deleted and Subsections 6
1568 and 7 are renumbered.

1569 (13) In IRC, Section N1106.4 (R406.4), the table is deleted and replaced with the
1570 following:

| 1571 TABLE N1106.4 (R406.4) | |
|----------------------------------|---------------------|
| 1572 MAXIMUM ENERGY RATING INDEX | |
| 1573 CLIMATE ZONE | ENERGY RATING INDEX |
| 15743 | 65 |
| 15755 | 69 |
| 15766 | 68 |

1577 [(20)] (14) In IRC, Section M1307.2, the words "In Seismic Design Categories [D1 and
1578 D2]" D0, D1, and D2, and in townhouses in Seismic Design Category C, are deleted, and in
1579 Subparagraph 1, the last sentence is deleted.

1580 [(21) The RESCheck Software adopted by the United States Department of Energy and

1581 ~~modified to meet the requirements of this section shall be used to verify compliance with this~~
1582 ~~section. The software shall address the Total UA alternative approach and account for~~
1583 ~~Equipment Efficiency Trade-offs when applicable per the standard reference design as~~
1584 ~~amended.]~~

1585 [~~(22)~~] (15) IRC, Section [~~M1411.6~~] M1411.8, is deleted.

1586 Section 18. Section **15A-3-204** is amended to read:

1587 **15A-3-204. Amendments to Chapters 16 through 25 of IRC.**

1588 [~~(1)~~ In IRC, Table M1601.1.1(2), in the section "Round ducts and enclosed rectangular
1589 ducts", the word "enclosed" is deleted; the words "14 inches or less" are deleted and replaced
1590 with "over 8 inches but less than 15 inches"; the wording "8 inches or less" under duct size,
1591 "0.013" under minimum thickness (in.), "30" under equivalent gage no., and "0.0159" under
1592 aluminum minimum thickness (in.), are added; and the section "Exposed rectangular ducts" is
1593 deleted.]

1594 [~~(2)~~ In IRC, Section M1901.3, the word "only" is inserted between the words "labeled"
1595 and "for".]

1596 [~~(3)~~] A new IRC, Section G2401.2, is added as follows: "G2401.2 Meter Protection.
1597 Fuel gas services shall be in an approved location and/or provided with structures designed to
1598 protect the fuel gas meter and surrounding piping from physical damage, including falling,
1599 moving, or migrating ice and snow. If an added structure is used, it must provide access for
1600 service and comply with the IBC or the IRC."

1601 Section 19. Section **15A-3-205** is amended to read:

1602 **15A-3-205. Amendments to Chapters 26 through 35 of IRC.**

1603 (1) A new IRC, Section P2602.3, is added as follows: "P2602.3 Individual water
1604 supply. Where a potable public water supply is not available, individual sources of potable
1605 water supply shall be utilized, provided that the source has been developed in accordance with
1606 Utah Code, Sections [73-3-1](#) and [73-3-25](#), as administered by the Department of Natural
1607 Resources, Division of Water Rights. In addition, the quality of the water shall be approved by
1608 the local health department having jurisdiction."

1609 (2) A new IRC, Section P2602.4, is added as follows: "P2602.4 Sewer required. Every
 1610 building in which plumbing fixtures are installed and all premises having drainage piping shall
 1611 be connected to a public sewer where the sewer is accessible and is within 300 feet of the
 1612 property line in accordance with Utah Code, Section 10-8-38; or an approved private sewage
 1613 disposal system in accordance with Utah Administrative Code, Chapter 4, Rule R317, as
 1614 administered by the Department of Environmental Quality, Division of Water Quality."

1615 (3) In IRC, Section [~~P2801.7~~] P2801.8, all words in the first sentence up to the word
 1616 "water" are deleted.

1617 (4) A new IRC, Section P2902.1.1, is added as follows: "P2902.1.1 Backflow assembly
 1618 testing. The premise owner or [~~his~~] the premise owner's designee shall have backflow
 1619 prevention assemblies operation tested in accordance with administrative rules made by the
 1620 Drinking Water Board at the time of installation, repair, and relocation and at least on an
 1621 annual basis thereafter, or more frequently as required by the authority having jurisdiction.
 1622 Testing shall be performed by a Certified Backflow Preventer Assembly Tester. The
 1623 assemblies that are subject to this paragraph are the Spill Resistant Vacuum Breaker, the
 1624 Pressure Vacuum Breaker Assembly, the Double Check Backflow Prevention Assembly, the
 1625 Double Check Detector Assembly Backflow Preventer, the Reduced Pressure Principle
 1626 Backflow Preventer, and Reduced Pressure Detector Assembly. Third-party certification for
 1627 backflow prevention assemblies will consist of any combination of two certifications,
 1628 laboratory or field. Acceptable third-party laboratory certifying agencies are ASSE, IAPMO,
 1629 and USC-FCCCHR. USC-FCCCHR currently provides the only field testing of backflow
 1630 protection assemblies. Also see www.drinkingwater.utah.gov and rules made by the Drinking
 1631 Water Board."

1632 [~~(5) IRC, Table P2902.3, is deleted and replaced with the following:]~~

1633 [

| "DEVICE | DEGREE OF HAZARD ^a | APPLICATION ^b | APPLICABLE STANDARDS |
|--|-------------------------------|--------------------------|----------------------|
| BACKFLOW PREVENTION ASSEMBLIES: | | | |

| | | | | |
|------|--|--------------------|--|--|
| 1636 | Double check backflow prevention assembly and double check fire protection backflow prevention assembly | Low hazard | Backpressure or backsiphonage Sizes 3/8" - 16" | ASSE 1015, AWWA C510, CSA B64.5, CSA B64.5.1 |
| 1637 | Double check detector fire protection backflow prevention assemblies | Low hazard | Backpressure or backsiphonage Sizes 3/8" - 16" | ASSE 1048 |
| 1638 | Pressure vacuum breaker assembly | High or low hazard | Backsiphonage only Sizes 1/2" - 2" | ASSE 1020, CSA B64.1.2 |
| 1639 | Reduced pressure principle backflow prevention assembly and reduced pressure principle fire protection backflow assembly | High or low hazard | Backpressure or backsiphonage Sizes 3/8" - 16" | ASSE 1013, AWWA C511, CSA B64.4, CSA B64.4.1 |
| 1640 | Reduced pressure detector fire protection backflow prevention assemblies | High or low hazard | Backpressure or backsiphonage (Fire Sprinkler Systems) | ASSE 1047 |
| 1641 | Spill-resistant vacuum breaker assembly | High or low hazard | Backsiphonage only Sizes 1/2" - 2" | ASSE 1056 |
| 1642 | BACKFLOW PREVENTER PLUMBING DEVICES: | | | |

| | | | | |
|------|--|--------------------|--|-------------------------------|
| 1643 | Antisiphon-type fill valves for gravity water closet flush tanks | High hazard | Backsiphonage only | ASSE 1002, CSA B125.3 |
| 1644 | Backflow preventer for carbonated beverage machines | Low hazard | Backpressure or backsiphonage Sizes 1/4" - 3/8" | ASSE 1022 |
| 1645 | Backflow preventer with intermediate atmospheric vents | Low hazard | Backpressure or backsiphonage Sizes 1/4" - 3/8" | ASSE 1012, CSA B64.3 |
| 1646 | Dual check valve type backflow preventers | Low hazard | Backpressure or backsiphonage Sizes 1/4" - 1" | ASSE 1024, CSA B64.6 |
| 1647 | Hose connection backflow preventer | High or low hazard | Backsiphonage only Sizes 1/2" - 1" | ASSE 1052, CSA B64.2, B64.2.1 |
| 1648 | Hose connection vacuum breaker | High or low hazard | Backsiphonage only Sizes 1/2", 3/4", 1" | ASSE 1011, CAN/CSA B64.1.1 |
| 1649 | Atmospheric type vacuum breaker | High or low hazard | Backsiphonage only Sizes 1/2" - 4" | ASSE 1001, CSA B64.1.1 |
| 1650 | Vacuum breaker wall hydrants, frost resistant, automatic draining type | High or low hazard | Backsiphonage only Sizes 3/4", 1" | ASSE 1019, CSA B64.2.2 |
| 1651 | OTHER MEANS or METHODS: | | | |
| 1652 | Air gap | High or low hazard | Backsiphonage only | ASME A112.1.2 |

| | | | | |
|------|---|--------------------|-------------------------------|---------------|
| 1653 | Air gap fittings for use with plumbing fixtures, appliances and appurtenances | High or low hazard | Backpressure or backsiphonage | ASME A112.1.3 |
| 1654 | For SI: 1 inch = 25.4 mm | | | |
| 1655 | a. Low Hazard - See Pollution (Section 202), High Hazard - See Contamination (Section 202) | | | |
| 1656 | b. See Backpressure (Section 202), See Backpressure, low head (Section 202), See Backsiphonage Section 202) | | | |
| 1657 | Installation Guidelines: The above specialty devices shall be installed in accordance with their listing and the manufacturer's instructions and the specific provisions of this chapter." | | | |

1658] ~~[(6) In IRC, Section P3009.1, all words after the word "urinals" are deleted and the~~
 1659 ~~following sentence is added at the end: "Gray water recycling systems for subsurface landscape~~
 1660 ~~irrigation shall conform with UAC R317-401 Gray Water Systems."]~~

1661 ~~[(7) A new IRC, Section P3009.1.1, is added as follows: "P3009.1.1 Recording. The~~
 1662 ~~existence of a gray water recycling system shall be recorded on the deed of ownership for that~~
 1663 ~~property. The certificate of occupancy shall not be issued until the documentation of the~~
 1664 ~~recording required under this section is completed by the owner."]~~

1665 ~~[(8) In IRC, Section P3009.2, the words "and systems for subsurface landscape~~
 1666 ~~irrigation shall comply with Section P3009.14" are deleted.]~~

1667 ~~[(9) IRC, Section P3009.6, is deleted and replaced with the following: "P3009.6~~
 1668 ~~Potable water connections. The potable water supply to any building utilizing a gray water~~
 1669 ~~recycling system shall be protected against backflow by a reduced pressure backflow~~
 1670 ~~prevention assembly installed in accordance with Section P2902."]~~

1671 ~~[(10) In IRC, Section P3009.7, the following is added at the end of the sentence: "and~~
 1672 ~~other clear water wastes which have a pH of 6.0 to 9.0; are non-flammable, non-combustible;~~
 1673 ~~without objectionable odor; non-highly pigmented; and will not interfere with the operation of~~

1674 the sewer treatment facility."]

1675 [(11) In IRC, Section P3009.13.3, in the second sentence, the following is added
1676 between the words "backflow" and "in": "by a reduced pressure backflow prevention assembly
1677 or an air gap installed".]

1678 [(12) IRC, Section P3009.14, is deleted and replaced with the following: "Section
1679 P3009.14 LANDSCAPE IRRIGATION SYSTEMS. Gray water recycling systems utilized for
1680 subsurface irrigation for single family residences shall comply with the requirements of UAC
1681 R317-401, Gray Water Systems. Gray water recycling systems utilized for subsurface
1682 irrigation for other occupancies shall comply with UAC R317-3, Design Requirements for
1683 Wastewater Collection, Treatment and Disposal and UAC R317-4, Onsite Waterwaste
1684 Systems."]

1685 (5) In IRC, Section P2902.1, the following subsections are added as follows:

1686 "P2902.1.1 General Installation Criteria.

1687 Assemblies shall not be installed more than five feet above the floor unless a permanent
1688 platform is installed. The assembly owner, where necessary, shall provide devices or structures
1689 to facilitate testing, repair, and maintenance, and to insure the safety of the backflow
1690 technician.

1691 P2902.1.2 Specific Installation Criteria.

1692 P2902.1.2.1 Reduced Pressure Principle Blackflow Prevention Assembly.

1693 The reduced pressure principle backflow prevention assembly shall be installed as
1694 follows:

1695 a. The assembly may not be installed in a pit.

1696 b. The relief valve of the assembly shall not be directly connected to a waste disposal line,
1697 including a sanitary sewer, a storm drain, or a vent.

1698 c. The assembly shall be installed in a horizontal position only, unless listed or approved for
1699 vertical installation in accordance with Section 303.4.

1700 d. The bottom of the assembly shall be installed a minimum of 12 inches above the floor or
1701 ground.

1702 e. The body of the assembly shall be a minimum of 12 inches from any wall, ceiling, or
1703 obstacle, and shall be readily accessible for testing, repair, and maintenance.

1704 P2902.1.2.2 Double Check Valve Backflow Prevention Assembly.

1705 A double check valve backflow prevention assembly shall be installed as follows:

1706 a. The assembly shall be installed in a horizontal position only, unless listed or approved for
1707 vertical installation.

1708 b. The bottom of the assembly shall be a minimum of 12 inches above the ground or floor.

1709 c. The body of the assembly shall be a minimum of 12 inches from any wall, ceiling, or
1710 obstacle, and shall be readily accessible for testing, repair, and maintenance.

1711 d. If installed in a pit, the assembly shall be installed with a minimum of 12 inches of clearance
1712 between all sides of the vault, including the floor and roof or ceiling, with adequate room for
1713 testing and maintenance.

1714 P2902.1.2.3 Pressure Vacuum Break Assembly and Spill Resistant Pressure Vacuum Breaker
1715 Assembly.

1716 A pressure vacuum break assembly or a spill resistant pressure vacuum breaker assembly shall
1717 be installed as follows:

1718 a. The assembly shall not be installed in an area that could be subject to backpressure or back
1719 drainage conditions.

1720 b. The assembly shall be installed a minimum of 12 inches above all downstream piping and
1721 the highest point of use.

1722 c. The assembly shall be a minimum of 12 inches from any wall, ceiling, or obstacle, and shall
1723 be readily accessible for testing, repair, and maintenance.

1724 d. The assembly shall not be installed below ground, in a vault, or in a pit.

1725 e. The assembly shall be installed in a vertical position."

1726 (6) IRC, Section P2910.5, is deleted and replaced with the following:

1727 "P2910.5 Potable water connections.

1728 When a potable water system is connected to a nonpotable water system, the potable water
1729 system shall be protected against backflow by a reduced pressure backflow prevention

1730 assembly or an air gap installed in accordance with Section 2901."

1731 (7) IRC, Section P2910.9.5, is deleted and replaced with the following:

1732 "P2910.9.5 Makeup water.

1733 Where an uninterrupted nonpotable water supply is required for the intended application,

1734 potable or reclaimed water shall be provided as a source of makeup water for the storage tank.

1735 The makeup water supply shall be protected against backflow by means of an air gap not less

1736 than 4 inches (102 millimeters) above the overflow or by a reduced pressure backflow

1737 prevention assembly installed in accordance with Section 2902."

1738 (8) In IRC, Section P2911.12.4, the following words are deleted: "and backwater

1739 valves".

1740 (9) In IRC, Section P2912.15.6, the following words are deleted: "and backwater

1741 valves".

1742 (10) In IRC, Section P2913.4.2, the following words are deleted: "and backwater

1743 valves".

1744 (11) IRC, Section P3009, is deleted and replaced with the following:

1745 "P3009 Connected to nonpotable water from on-site water reuse systems.

1746 Nonpotable systems utilized for subsurface irrigation for single-family residences shall comply

1747 with the requirements of R317-401, UAC, Gray Water Systems."

1748 ~~[(13)]~~ (12) In IRC, Section P3103.6, the following sentence is added at the end of the
1749 paragraph: "Vents extending through the wall shall terminate not less than 12 inches from the
1750 wall with an elbow pointing downward."

1751 ~~[(14)]~~ (13) In IRC, Section P3104.4, the following sentence is added at the end of the
1752 paragraph: "Horizontal dry vents below the flood level rim shall be permitted for floor drain
1753 and floor sink installations when installed below grade in accordance with Chapter 30, and
1754 Sections P3104.2 and P3104.3. A wall cleanout shall be provided in the vertical vent."

1755 Section 20. Section **15A-3-206** is amended to read:

1756 **15A-3-206. Amendments to Chapters 36 and 44 of IRC.**

1757 (1) In IRC, Section E3901.9, the following exception is added:

1758 "Exception: Receptacles or other outlets adjacent to the exterior walls of the garage, outlets
 1759 adjacent to an exterior wall of the garage, or outlets in a storage room with entry from the
 1760 garage may be connected to the garage branch circuit."

1761 ~~[(1)]~~ (2) In IRC, Section ~~[E3902.12]~~ E3902.16, the following words in the first
 1762 sentence are deleted: "family rooms, dining rooms, living rooms, parlors, libraries, dens," and
 1763 "sunrooms, recreation rooms, closets, hallways, and similar rooms or areas."

1764 (3) In Section E3902.17:

1765 (a) following the word "Exception" the number "1." is added; and

1766 (b) at the end of the section, the following sentences are added:

1767 ~~[Exception:]~~ "2. This section does not apply for a simple move or an extension of a branch
 1768 circuit or an outlet which does not significantly increase the existing electrical load. This
 1769 exception does not include changes involving remodeling or additions to a residence."

1770 ~~[(2)]~~ (3) IRC, Chapter 44, is amended by adding the following reference standard:

| "Standard reference number | Title | Referenced in code section number |
|--|--|-----------------------------------|
| USC-FCCCHR 10th Edition Manual of Cross Connection Control | Foundation for Cross-Connection Control and Hydraulic Research University of Southern California Kaprielian Hall 300 Los Angeles CA 90089-2531 | Table P2902.3" |

1773 Section 21. Section **15A-3-302** is amended to read:

1774 **15A-3-302. Amendments to Chapters 1 and 2 of IPC.**

1775 (1) A new IPC, Section ~~[101.2]~~ 101.2.1, is added as follows: "For clarification, the
 1776 International Private Sewage Disposal Code is not part of the plumbing code even though it is
 1777 in the same printed volume."

1778 (2) In IPC, Section 202, the definition for "Backflow Backpressure, Low Head" is
 1779 deleted.

1780 (3) In IPC, Section 202, the following definition is added: "Certified Backflow

1781 Preventer Assembly Tester. A person who has shown competence to test Backflow prevention
1782 assemblies to the satisfaction of the authority having jurisdiction under Utah Code, Subsection
1783 19-4-104(4)."

1784 (4) In IPC, Section 202, the following definition is added: "Contamination (High
1785 Hazard). An impairment of the quality of the potable water that creates an actual hazard to the
1786 public health through poisoning or through the spread of disease by sewage, industrial fluids or
1787 waste."

1788 (5) In IPC, Section 202, the definition for "Cross Connection" is deleted and replaced
1789 with the following: "Cross Connection. Any physical connection or potential connection or
1790 arrangement between two otherwise separate piping systems, one of which contains potable
1791 water and the other either water of unknown or questionable safety or steam, gas, or chemical,
1792 whereby there exists the possibility for flow from one system to the other, with the direction of
1793 flow depending on the pressure differential between the two systems (see "Backflow")."

1794 (6) In IPC, Section 202, the following definition is added: "Deep Seal Trap. A
1795 manufactured or field fabricated trap with a liquid seal of 4" or larger."

1796 ~~[(7) In IPC, Section 202, in the definition for gray water a comma is inserted after the
1797 word "washers", the word "and" is deleted, and the following is added to the end: "and clear
1798 water wastes which have a pH of 6.0 to 9.0; are non-flammable; non-combustible; without
1799 objectionable odors; non-highly pigmented; and will not interfere with the operation of the
1800 sewer treatment facility."]~~

1801 (7) In IPC, Section 202, the definition for "Essentially Nontoxic Transfer Fluid" is
1802 deleted and replaced with the following:
1803 "ESSENTIALLY NONTOXIC TRANSFER FLUID. Fluids having a Gosselin rating of 1,
1804 including propylene glycol; and mineral oil."

1805 (8) In IPC, Section 202, the definition for "Essentially Toxic Transfer Fluid" is deleted
1806 and replaced with the following:
1807 "ESSENTIALLY TOXIC TRANSFER FLUID. Soil, waste, or gray water; and any fluid that is
1808 not an essentially nontoxic transfer fluid under this code."

1809 [~~(8)~~] (9) In IPC, Section 202, the following definition is added: "High Hazard. See
1810 Contamination."

1811 [~~(9)~~] (10) In IPC, Section 202, the following definition is added: "Low Hazard. See
1812 Pollution."

1813 [~~(10)~~] (11) In IPC, Section 202, the following definition is added: "Pollution (Low
1814 Hazard). An impairment of the quality of the potable water to a degree that does not create a
1815 hazard to the public health but that does adversely and unreasonably affect the aesthetic
1816 qualities of such potable water for domestic use."

1817 [~~(11)~~] (12) In IPC, Section 202, the definition for "Potable Water" is deleted and
1818 replaced with the following: "Potable Water. Water free from impurities present in amounts
1819 sufficient to cause disease or harmful physiological effects and conforming to the Utah Code,
1820 Title 19, Chapter 4, Safe Drinking Water Act, and Title 19, Chapter 5, Water Quality Act, and
1821 the regulations of the public health authority having jurisdiction."

1822 Section 22. Section **15A-3-303** is amended to read:

1823 **15A-3-303. Amendments to Chapter 3 of IPC.**

1824 (1) In IPC, Section 303.4, the following exception is added:

1825 "Exception: Third-party certification for backflow prevention assemblies will consist of any
1826 combination of two certifications, laboratory or field. Acceptable third party laboratory
1827 certifying agencies are ASSE, IAPMO, and USC-FCCCHR. USC-FCCCHR currently
1828 provides the only field testing of backflow protection assemblies. Also see
1829 www.drinkingwater.utah.gov and Division of Drinking Water Rule, Utah Administrative Code,
1830 R309-305-6."

1831 [~~(2) IPC, Section 304.3, Meter Boxes, is deleted.~~]

1832 [~~(3)~~] (2) IPC, Section 311.1, is deleted.

1833 [~~(4)~~] (3) In IPC, Section 312.3, the following is added at the end of the paragraph:

1834 "Where water is not available at the construction site or where freezing conditions limit
1835 the use of water on the construction site, plastic drainage and vent pipe may be permitted to be
1836 tested with air. The following procedures shall be followed:

- 1837 1. Contractor shall recognize that plastic is extremely brittle at lower temperatures and can
1838 explode, causing serious injury or death.
- 1839 2. Contractor assumes all liability for injury or death to persons or damage to property or for
1840 claims for labor and/or material arising from any alleged failure of the system during testing
1841 with air or compressed gasses.
- 1842 3. Proper personal protective equipment, including safety eyewear and protective headgear,
1843 should be worn by all individuals in any area where an air or gas test is being conducted.
- 1844 4. Contractor shall take all precautions necessary to limit the pressure within the plastic piping.
- 1845 5. No [~~water supply~~] drain and vent system shall be pressurized in excess of 6 psi as measured
1846 by accurate gauges graduated to no more than three times the test pressure.
- 1847 6. The pressure gauge shall be monitored during the test period, which should not exceed 15
1848 minutes.
- 1849 7. At the conclusion of the test, the system shall be depressurized gradually, all trapped air or
1850 gases should be vented, and test balls and plugs should be removed with caution."

1851 [~~(5)~~] (4) In IPC, Section 312.5, the following is added at the end of the paragraph:

1852 "Where water is not available at the construction site or where freezing conditions limit the use
1853 of water on the construction site, plastic water pipes may be permitted to be tested with air.

1854 The following procedures shall be followed:

- 1855 1. Contractor shall recognize that plastic is extremely brittle at lower temperatures and can
1856 explode, causing serious injury or death.
- 1857 2. Contractor assumes all liability for injury or death to persons or damage to property or for
1858 claims for labor and/or material arising from any alleged failure of the system during testing
1859 with air or compressed gasses.
- 1860 3. Proper personal protective equipment, including safety eyewear and protective headgear,
1861 should be worn by all individuals in any area where an air or gas test is being conducted.
- 1862 4. Contractor shall take all precautions necessary to limit the pressure within the plastic piping.
- 1863 5. Water supply systems shall be pressure tested to a minimum of 50 psi but not more than 80
1864 psi as measured by accurate gauges graduated to no more than three times the test pressure.

1865 6. The pressure gauge shall be monitored during the test period, which should not exceed 15
1866 minutes.

1867 7. At the conclusion of the test, the system shall be depressurized gradually, all trapped air or
1868 gases should be vented, and test balls and plugs should be removed with caution."

1869 ~~[(6)]~~ (5) A new IPC, Section 312.10.3, is added as follows: "312.10.3 Tester
1870 Qualifications. Testing shall be performed by a Utah Certified Backflow Preventer Assembly
1871 Tester in accordance with Utah Administrative Code, R309-305."

1872 Section 23. Section **15A-3-304** is amended to read:

1873 **15A-3-304. Amendments to Chapter 4 of IPC.**

1874 (1) In IPC, Table 403.1, the following changes are made:

1875 (a) The title for Table 403.1 is deleted and replaced with the following: "Table 403.1,
1876 Minimum Number of Required Plumbing ~~[Facilities^{a, h}]~~ Fixtures_{a, h},";

1877 (b) In ~~[the]~~ row ~~[for]~~ number "3", for "E" occupancy₂ in the field for "OTHER",₂ a new
1878 footnote ~~[i]~~ g is added.

1879 (c) In ~~[the]~~ row number "5", for "I-4 Adult day care and child day care" occupancy₂ in
1880 the field for "OTHER", a new footnote ~~[i]~~ g is added.

1881 (d) A new footnote ~~[h]~~ f is added as follows: "FOOTNOTE: ~~[h]~~ f. When provided, in
1882 public toilet facilities, there shall be an equal number of diaper changing facilities in male toilet
1883 rooms and female toilet rooms. Diaper changing facilities shall meet the requirements of
1884 ASTM F2285-04 (2010) Standard Consumer Safety Performance Specifications for Diaper
1885 Changing Tables for Commercial Use."

1886 (e) A new footnote ~~[i]~~ g is added to the table as follows: "FOOTNOTE ~~[i]~~ g:
1887 Non-residential child care facilities shall comply ~~[with additional sink requirements of Utah~~
1888 ~~Administrative Code R430-100-4.]~~ with the additional requirements for sinks in administrative
1889 rule made by the Department of Health."

1890 (2) A new IPC, Section 406.3, is added as follows: " 406.3 Automatic clothes washer
1891 safe pans. Safe pans, when installed under automatic clothes washers, shall be installed in
1892 accordance with Section 504.7."

1893 (3) A new IPC, Section 412.5, is added as follows: "412.5 Public toilet rooms. All
1894 public toilet rooms in A & E occupancies and M occupancies with restrooms having multiple
1895 water closets or urinals shall be equipped with at least one floor drain."

1896 (4) IPC, Section 423.3, is deleted.

1897 Section 24. Section **15A-3-305** is amended to read:

1898 **15A-3-305. Amendments to Chapter 5 of IPC.**

1899 (1) IPC, Section 502.4, is deleted and replaced with the following: "502.4 Seismic
1900 supports. [~~Appliances designed to be fixed in position shall be fastened or anchored in an~~
1901 ~~approved manner. Water]~~ As a minimum requirement, water heaters shall be anchored or
1902 strapped to resist horizontal displacement caused by earthquake motion. Strapping shall be at
1903 points within the upper one-third and lower one-third of the appliance's vertical dimensions.
1904 [~~At the lower point, the strapping shall maintain a minimum distance of 4 inches (102 mm)~~
1905 ~~above the controls.]"~~

1906 (2) In IPC, Section 504.7.2, the following is added at the end of the section: "When
1907 permitted by the code official, the pan drain may be directly connected to a soil stack, waste
1908 stack, or branch drain. The pan drain shall be individually trapped and vented as required in
1909 Section 907.1. The pan drain shall not be directly or indirectly connected to any vent. The trap
1910 shall be provided with a trap primer conforming to ASSE 1018 or ASSE 1044, a barrier type
1911 floor drain trap seal protection device meeting ASSE 1072, or a deep seal p-trap."

1912 (3) A new IPC, Section 504.7.3, is added as follows: "504.7.3 Pan Designation. A
1913 water heater pan shall be considered an emergency receptor designated to receive the discharge
1914 of water from the water heater only and shall not receive the discharge from any other fixtures,
1915 devices, or equipment."

1916 Section 25. Section **15A-3-306** is amended to read:

1917 **15A-3-306. Amendments to Chapter 6 of IPC.**

1918 (1) IPC, Section 602.3, is deleted and replaced with the following: "602.3 Individual
1919 water supply. Where a potable public water supply is not available, individual sources of
1920 potable water supply shall be utilized provided that the source has been developed in

1921 accordance with Utah Code, Sections 73-3-1, 73-3-3, and 73-3-25, as administered by the
1922 Department of Natural Resources, Division of Water Rights. In addition, the quality of the
1923 water shall be approved by the local health department having jurisdiction. The source shall
1924 supply sufficient quantity of water to comply with the requirements of this chapter."

1925 (2) IPC, Sections 602.3.1, 602.3.2, 602.3.3, 602.3.4, 602.3.5, and 602.3.5.1, are
1926 deleted.

1927 (3) A new IPC, Section 604.4.1, is added as follows: "604.4.1 Manually operated
1928 metering faucets for food service establishments. Self closing or manually operated metering
1929 faucets shall provide a flow of water for at least 15 seconds without the need to reactivate the
1930 faucet."

1931 (4) IPC, Section 606.5, is deleted and replaced with the following: "606.5 Water
1932 pressure booster systems. Water pressure booster systems shall be provided as required by
1933 Section 606.5.1 through 606.5.11."

1934 (5) A new IPC, Section 606.5.11, is added as follows: "606.5.11 Prohibited
1935 installation. In no case shall a booster pump be allowed that will lower the pressure in the
1936 public main to less than the minimum water pressure specified in Utah Administrative Code
1937 R309-105-9."

1938 (6) In IPC, Section 608.1, the words "and pollution" are added after the word
1939 "contamination."

1940 [~~(7) IPC, Table 608.1, is deleted and replaced with the following:~~]

1941 [

| | | | |
|--|---|------------------------------------|---------------------------------|
| TABLE 608.1 | | | |
| Application of Back Flow Preventers | | | |
| DEVICE | DEGREE OF HAZARD^a | APPLICATION^b | APPLICABLE STANDARDS |
| BACKFLOW PREVENTION ASSEMBLIES: | | | |

1945

| | | | | |
|------|--|--------------------|--|--|
| 1946 | Double check backflow prevention assembly and double check fire protection backflow prevention assembly | Low hazard | Backpressure or backsiphonage Sizes 3/8" - 16" | ASSE 1015, AWWA C510, CSA B64.5, CSA B64.5.1 |
| 1947 | Double check detector fire protection backflow prevention assemblies | Low hazard | Backpressure or backsiphonage Sizes 3/8" - 16" | ASSE 1048 |
| 1948 | Pressure vacuum breaker assembly | High or low hazard | Backsiphonage only Sizes 1/2" - 2" | ASSE 1020, CSA B64.1.2 |
| 1949 | Reduced pressure principle backflow prevention assembly and reduced pressure principle fire protection backflow assembly | High or low hazard | Backpressure or backsiphonage Sizes 3/8" - 16" | ASSE 1013, AWWA C511, CSA B64.4, CSA B64.4.1 |
| 1950 | Reduced pressure detector fire protection backflow prevention assemblies | High or low hazard | Backpressure or backsiphonage (Fire Sprinkler Systems) | ASSE 1047 |
| 1951 | Spill-resistant vacuum breaker assembly | High or low hazard | Backsiphonage only Sizes 1/2" - 2" | ASSE 1056 |
| 1952 | BACKFLOW PREVENTER PLUMBING DEVICES: | | | |

| | | | | |
|------|--|--------------------|--|-------------------------------|
| 1953 | Antisiphon-type fill valves for gravity water closet flush tanks | High hazard | Backsiphonage only | ASSE 1002, CSA B125.3 |
| 1954 | Backflow preventer for carbonated beverage machines | Low hazard | Backpressure or backsiphonage Sizes 1/4" - 3/8" | ASSE 1022 |
| 1955 | Backflow preventer with intermediate atmospheric vents | Low hazard | Backpressure or backsiphonage Sizes 1/4" - 3/8" | ASSE 1012, CSA B64.3 |
| 1956 | Dual check valve type backflow preventers | Low hazard | Backpressure or backsiphonage Sizes 1/4" - 1" | ASSE 1024, CSA B64.6 |
| 1957 | Hose connection backflow preventer | High or low hazard | Backsiphonage only Sizes 1/2" - 1" | ASSE 1052, CSA B64.2, B64.2.1 |
| 1958 | Hose connection vacuum breaker | High or low hazard | Backsiphonage only Sizes 1/2", 3/4", 1" | ASSE 1011, CAN/CSA B64.1.1 |
| 1959 | Atmospheric type vacuum breaker | High or low hazard | Backsiphonage only Sizes 1/2" - 4" | ASSE 1001, CSA B64.1.1 |
| 1960 | Vacuum breaker wall hydrants, frost resistant, automatic draining type | High or low hazard | Backsiphonage only Sizes 3/4", 1" | ASSE 1019, CSA B64.2.2 |
| 1961 | OTHER MEANS or METHODS: | | | |
| 1962 | Air gap | High or low hazard | Backsiphonage only | ASME A112.1.2 |

| | | | | |
|------|--|--------------------|-------------------------------|---------------|
| 1963 | Air gap fittings for use with plumbing fixtures, appliances and appurtenances | High or low hazard | Backpressure or backsiphonage | ASME A112.1.3 |
| 1964 | For SI: 1 inch = 25.4 mm | | | |
| 1965 | a. Low Hazard - See Pollution (Section 202), High Hazard - See Contamination (Section 202) | | | |
| 1966 | b. See Backpressure (Section 202), See Backpressure, low head (Section 202), See Backsiphonage (Section 202) | | | |
| 1967 | Installation Guidelines: The above specialty devices shall be installed in accordance with their listing and the manufacturer's instructions and the specific provisions of this chapter." | | | |

1968] (7) In IPC, Section 608.1, the following subsections are added as follows:

1969 "608.1.1 General Installation Criteria.

1970 An assembly shall not be installed more than five feet above the floor unless a permanent

1971 platform is installed. The assembly owner, where necessary, shall provide devices or structures

1972 to facilitate testing, repair, and maintenance and to insure the safety of the backflow technician.

1973 608.1.2 Specific Installation Criteria.

1974 608.1.2.1 Reduced Pressure Principle Blackflow Prevention Assembly.

1975 A reduced pressure principle backflow prevention assembly shall be installed as follows:

1976 a. The assembly shall not be installed in a pit.

1977 b. The relief valve of the assembly shall not be directly connected to a waste disposal line,

1978 including a sanitary sewer, storm drain, or vent.

1979 c. The assembly shall be installed in a horizontal position, unless the assembly is listed or

1980 approved for vertical installation in accordance with Section 303.4.

1981 d. The bottom of each assembly shall be installed a minimum of 12 inches above the ground or

1982 the floor.

1983 e. The body of the assembly shall be a minimum of 12 inches from any wall, ceiling, or

1984 obstacle, and shall be readily accessible for testing, repair, and maintenance.

1985 608.1.2.2 Double Check Valve Backflow Prevention Assembly.

1986 A double check valve backflow prevention assembly shall be installed as follows:

1987 a. The assembly shall be installed in a horizontal position unless the assembly is listed or
1988 approved for vertical installation.

1989 b. The bottom of the assembly shall be a minimum of 12 inches above the ground or the floor.

1990 c. The body of the assembly shall be a minimum of 12 inches from any wall, ceiling, or
1991 obstacle, and shall be readily accessible for testing, repair, and maintenance.

1992 d. If installed in a pit, the assembly shall be installed with a minimum of 12 inches of clearance
1993 around all sides of the vault, including the floor and roof or ceiling, with adequate room for
1994 testing and maintenance.

1995 608.1.2.3 Pressure Vacuum Break Assembly and Spill Resistant Pressure Vacuum Breaker
1996 Assembly.

1997 A pressure vacuum break assembly and spill resistant pressure vacuum breaker assembly shall
1998 be installed as follows:

1999 a. The assembly shall not be installed in an area that could be subject to backpressure or back
2000 drainage conditions.

2001 b. The assembly shall be installed a minimum of 12 inches above all downstream piping and
2002 the highest point of use.

2003 c. The assembly shall be a minimum of 12 inches from any wall, ceiling, or obstacle, and shall
2004 be readily accessible for testing, repair, and maintenance.

2005 d. The assembly shall not be installed below ground or in a vault or pit.

2006 e. The assembly shall be installed in a vertical position."

2007 (8) In IPC, Section 608.3, the word "and" after the word "contamination" is deleted and
2008 replaced with a comma and the words "and pollution" are added after the word "contamination"
2009 in the first sentence.

2010 (9) In IPC, Section 608.5, the words "with the potential to create a condition of either
2011 contamination or pollution or" are added after the word "substances".

2012 (10) In IPC, Section 608.6, the following sentence is added at the end of the paragraph:
2013 "Any connection between potable water piping and sewer-connected waste shall be protected
2014 by an air gap in accordance with Section 608.13.1."

2015 (11) IPC, Section 608.7, is deleted and replaced with the following: "608.7 Stop and
2016 Waste Valves installed below grade. Combination stop-and-waste valves shall be permitted to
2017 be installed underground or below grade. Freeze proof yard hydrants that drain the riser into
2018 the ground are considered to be stop-and-waste valves and shall be permitted. A
2019 stop-and-waste valve shall be installed in accordance with a manufacturer's recommended
2020 installation instructions."

2021 (12) In IPC, Section 608.11, the following sentence is added at the end of the
2022 paragraph: "The coating and installation shall conform to NSF Standard 61 and application of
2023 the coating shall comply with the manufacturer's instructions."

2024 (13) IPC, Section 608.13.3, is deleted and replaced with the following: "608.13.3
2025 Backflow preventer with intermediate atmospheric vent. Backflow preventers with
2026 intermediate atmospheric vents shall conform to ASSE 1012 or CSA CAN/CSA-B64.3. These
2027 devices shall be permitted to be installed on residential boilers only, without chemical
2028 treatment, where subject to continuous pressure conditions. The relief opening shall discharge
2029 by air gap and shall be prevented from being submerged."

2030 (14) IPC, Section 608.13.4, is deleted.

2031 (15) IPC, Section 608.13.9, is deleted and replaced with the following: "608.13.9
2032 Chemical dispenser backflow devices. Backflow devices for chemical dispensers shall comply
2033 with Section 608.16.7."

2034 (16) IPC, Section 608.15.3, is deleted and replaced with the following: "608.15.3
2035 Protection by a backflow preventer with intermediate atmospheric vent. Connections to
2036 residential boilers only, without chemical treatment, shall be protected by a backflow preventer
2037 with an intermediate atmospheric vent."

2038 (17) IPC, Section 608.15.4, is deleted and replaced with the following: "608.15.4
2039 Protection by a vacuum breaker. Openings and outlets shall be protected by atmospheric-type

2040 or pressure-type vacuum breakers. Vacuum breakers shall not be installed under exhaust hoods
2041 or similar locations that will contain toxic fumes or vapors. Fill valves shall be set in
2042 accordance with Section 425.3.1. Atmospheric Vacuum Breakers - The critical level of the
2043 atmospheric vacuum breaker shall be set a minimum of 6 inches (152 mm) above the flood
2044 level rim of the fixture or device. Pipe-applied vacuum breakers shall be installed not less than
2045 6 inches (152 mm) above the flood level rim of the fixture, receptor, or device served. No
2046 valves shall be installed downstream of the atmospheric vacuum breaker. Pressure Vacuum
2047 Breaker - The critical level of the pressure vacuum breaker shall be set a minimum of 12 inches
2048 (304 mm) above the flood level of the fixture or device."

2049 (18) In IPC, Section 608.15.4.2, the following is added after the first sentence:
2050 "Add-on-backflow prevention devices shall be non-removable. In climates where freezing
2051 temperatures occur, a listed self-draining frost proof hose bibb with an integral backflow
2052 preventer shall be used."

2053 (19) IPC, Section 608.16.2, is deleted and replaced as follows: "608.16.2 Connections
2054 to boilers. The potable supply to a boiler shall be protected by an air gap or a reduced pressure
2055 principle backflow preventer, complying with ASSE 1013, CSA B64.4 or AWWA C511.
2056 Exception: The potable supply to a residential boiler without chemical treatment may be
2057 equipped with a backflow preventer with an intermediate atmospheric vent complying with
2058 ASSE 1012 or CSA CAN/CSA-B64.3."

2059 [~~20) IPC, Section 608.16.3, is deleted and replaced with the following: "608.16.3 Heat~~
2060 ~~exchangers. Heat exchangers shall be separated from potable water by double-wall~~
2061 ~~construction. An air gap open to the atmosphere shall be provided between the two walls.]~~

2062 [Exceptions:]

2063 [1. ~~Single wall heat exchangers shall be permitted when all of the following conditions are~~
2064 ~~met:]~~

2065 [a. ~~It utilizes a heat transfer medium of potable water or contains only substances which are~~
2066 ~~recognized as safe by the United States Food and Drug Administration (FDA);]~~

2067 [b. ~~The pressure of the heat transfer medium is maintained less than the normal minimum~~

2068 ~~operating pressure of the potable water system; and]~~

2069 ~~[e. The equipment is permanently labeled to indicate only additives recognized as safe by the~~
2070 ~~FDA shall be used.]~~

2071 ~~[2. Steam systems that comply with paragraph 1 above.]~~

2072 ~~[3. Approved listed electrical drinking water coolers."]~~

2073 ~~[(21)]~~ (20) In IPC, Section 608.16.4.1, a new exception is added as follows:

2074 "Exception: All class 1 and 2 systems containing chemical additives consisting of strictly
2075 glycerine (C.P. or U.S.P. 96.5 percent grade) or propylene glycol shall be protected against
2076 backflow with a double check valve assembly. Such systems shall include written certification
2077 of the chemical additives at the time of original installation and service or maintenance."

2078 ~~[(22)]~~ (21) IPC, Section 608.16.7, is deleted and replaced with the following: "608.16.7
2079 Chemical dispensers. Where chemical dispensers connect to the water distribution system, the
2080 water supply system shall be protected against backflow in accordance with Section 608.13.1,
2081 Section 608.13.2, Section 608.13.5, Section 608.13.6 or Section 608.13.8. Installation shall be
2082 in accordance with Section 608.1.2. Chemical dispensers shall connect to a separate dedicated
2083 water supply ~~[separate from any]~~ line, and not a sink faucet."

2084 ~~[(23)]~~ (22) IPC, Section 608.16.8, is deleted and replaced with the following: "608.16.8
2085 Portable cleaning equipment. Where the portable cleaning equipment connects to the water
2086 distribution system, the water supply system shall be protected against backflow in accordance
2087 with Section 608.13.1~~;~~ or Section 608.13.2 ~~[or Section 608.13.8]."~~

2088 ~~[(24)]~~ (23) A new IPC, Section 608.16.11, is added as follows: "608.16.11 Automatic
2089 and coin operated car washes. The water supply to an automatic or coin operated car wash
2090 shall be protected in accordance with Section 608.13.1 or Section 608.13.2."

2091 ~~[(25)]~~ (24) IPC, Section 608.17, is deleted and replaced with the following: "608.17
2092 Protection of individual water supplies. See Section 602.3 for requirements."

2093 Section 26. Section **15A-3-308** is amended to read:

2094 **15A-3-308. Amendments to Chapter 8 of IPC.**

2095 ~~[IPC, Chapter 8, is not amended.]~~

2096 In IPC, Section 802.1.1, the last sentence is deleted.

2097 Section 27. Section **15A-3-310** is amended to read:

2098 **15A-3-310. Amendments to Chapter 10 of IPC.**

2099 [~~In IPC, Section 1002.4, the following is added at the end of the paragraph: "Approved~~

2100 Means of Maintaining Trap Seals. Approved means of maintaining trap seals include the

2101 following, but are not limited to the methods cited:]

2102 [1. ~~A listed trap seal primer conforming to ASSE 1018 and ASSE 1044.~~]

2103 [2. ~~A hose bibb or bibbs within the same room.~~]

2104 [3. ~~Drainage from an untrapped lavatory discharging to the tailpiece of those fixture~~

2105 traps which require priming. All fixtures shall be in the same room and on the same floor level

2106 as the trap primer.]

2107 [4. ~~Barrier type floor drain trap seal protection device meeting ASSE Standard 1072.~~]

2108 [5. ~~Deep seal p-trap.~~]

2109 IPC, Chapter 10, is not amended.

2110 Section 28. Section **15A-3-311** is amended to read:

2111 **15A-3-311. Amendments to Chapter 11 of IPC.**

2112 [~~(1) IPC, Section 1104.2, is deleted and replaced with the following: "1104.2~~

2113 Combining storm and sanitary drainage prohibited. The combining of sanitary and storm

2114 drainage systems is prohibited."]

2115 (1) A new IPC, Section 1106.1.1, is added as follows:

2116 "1106.1.1 Alternate Methods.

2117 An approved alternate storm drain sizing method may be allowed."

2118 (2) IPC, Section 1109, is deleted.

2119 Section 29. Section **15A-3-313** is amended to read:

2120 **15A-3-313. Amendments to Chapter 13 of IPC.**

2121 [~~(1) In IPC, Section 1301.1, all words after the word "urinals" are deleted and the~~

2122 following sentence is added at the end: "Gray water recycling systems for subsurface landscape

2123 irrigation shall conform with UAC R317-401 Gray Water Systems."]

2124 ~~[(2) A new IPC, Section 1301.1.1, is added as follows: "1301.1.1 Recording. The~~
2125 ~~existence of a gray water recycling system shall be recorded on the deed of ownership for that~~
2126 ~~property. The certificate of occupancy shall not be issued until the documentation of the~~
2127 ~~recording required under this section is completed by the owner."]~~

2128 ~~[(3) In IPC, Section 1301.2, the words "and systems for subsurface landscape irrigation~~
2129 ~~shall comply with Section 1303" are deleted.]~~

2130 ~~[(4) IPC, Section 1301.6, is deleted and replaced with the following: "1301.6 Potable~~
2131 ~~water connections. The potable water supply to any building utilizing a gray water recycling~~
2132 ~~system shall be protected against backflow by a reduced pressure backflow prevention~~
2133 ~~assembly installed in accordance with Section 608."]~~

2134 ~~[(5) In IPC, Section 1301.7, the following is added at the end of the sentence: "and~~
2135 ~~other clear water wastes which have a pH of 6.0 to 9.0; are non-flammable, non-combustible;~~
2136 ~~without objectionable odor; non-highly pigmented; and will not interfere with the operation of~~
2137 ~~the sewer treatment facility."]~~

2138 ~~[(6) In IPC, Section 1302.3, in the second sentence, the following is added between the~~
2139 ~~words "backflow" and "in": "by a reduced pressure backflow prevention assembly or an air gap~~
2140 ~~installed".]~~

2141 ~~[(7) IPC, Section 1303, is deleted and replaced with the following: "Section 1303~~
2142 ~~SUBSURFACE LANDSCAPE IRRIGATION SYSTEMS. Gray water recycling systems~~
2143 ~~utilized for subsurface irrigation for single family residences shall comply with the~~
2144 ~~requirements of UAC R317-401, Gray Water Systems. Gray water recycling systems utilized~~
2145 ~~for subsurface irrigation for other occupancies shall comply with UAC R317-3, Design~~
2146 ~~Requirements for Wastewater Collection, Treatment and Disposal and UAC R317-4, Onsite~~
2147 ~~Waterwaste Systems."]~~

2148 (1) A new IPC, Section 1301.4.1, is added as follows:
2149 "1301.4.1 Recording.
2150 The existence of a nonpotable water system shall be recorded on the deed of ownership for the
2151 property. The certificate of occupancy shall not be issued until the documentation for the

2152 recording required under this section is completed by the property owner."

2153 (2) IPC, Section 1301.5, is deleted and replaced with the following:

2154 "1301.5 Potable water connections.

2155 Where a potable water system is connected to a nonpotable water system, the potable water
2156 supply shall be protected against backflow by a reduced pressure backflow prevention
2157 assembly or an air gap installed in accordance with Section 608."

2158 (3) IPC, Section 1301.9.5, is deleted and replaced with the following:

2159 "1301.9.5 Makeup water.

2160 Where an uninterrupted supply is required for the intended application, potable or reclaimed
2161 water shall be provided as a source of makeup water for the storage tank. The makeup water
2162 supply shall be protected against backflow by a reduced pressure backflow prevention
2163 assembly or an air gap installed in accordance with Section 608. A full-open valve located on
2164 the makeup water supply line to the storage tank shall be provided. Inlets to the storage tank
2165 shall be controlled by fill valves or other automatic supply valves installed to prevent the tank
2166 from overflowing and to prevent the water level from dropping below a predetermined point.
2167 Where makeup water is provided, the water level shall not be permitted to drop below the
2168 source water inlet or the intake of any attached pump."

2169 (4) IPC, Section 1302.12.4, is deleted and replaced with the following:

2170 "1302.12.4 Inspection and testing of backflow prevention assemblies.

2171 Testing of a backflow preventer shall be conducted in accordance with Sections 312.10.1,
2172 312.10.2, and 312.10.3."

2173 (5) IPC, Section 1303.15.6, is deleted and replaced with the following:

2174 "1303.15.6 Inspection and testing of backflow prevention assemblies.

2175 Testing of a backflow prevention assembly shall be conducted in accordance with Sections
2176 312.10.1, 312.10.2, and 312.10.3."

2177 (6) IPC, Section 1304.4.2, is deleted and replaced with the following:

2178 "1304.4.2 Inspection and testing of backflow prevention assemblies.

2179 Testing of a backflow preventer or backwater valve shall be conducted in accordance with

2180 Sections 312.10.1, 312.10.2, and 312.10.3."

2181 Section 30. Section **15A-3-314** is amended to read:

2182 **15A-3-314. Amendments to Chapter 14 of IPC.**

2183 [~~(1) In IPC, Chapter 14, the following referenced standard is added under ASSE:]~~

2184 [

| "Standard reference number | Title | Referenced in code section number |
|----------------------------|---|-----------------------------------|
| 1072-2007 | Performance Requirements for Barrier Type Floor Drain Trap Seal Protection Devices | 1004.2" |

2187] [~~(2) In IPC, Chapter 14, the following referenced standard is added:]~~

2188 [

| "Standard reference number | Title | Referenced in code section number |
|---|---|-----------------------------------|
| USC-FCCCHR 10th Edition Manual of Cross Connection Control | Foundation for Cross-Connection Control and Hydraulic Research University of Southern California Kaprielian Hall 300 Los Angeles CA 90089-2531 | Table 608.1" |

2191] IPC, Chapter 14, is deleted and replaced with the following:

2192 "1401. Subsurface Landscape Irrigation Systems.

2193 Gray water recycling systems utilized for subsurface irrigation for single-family residences

2194 shall comply with the requirements of UAC R317-401, Gray Water Systems. Gray water

2195 recycling systems utilized for subsurface irrigation for other occupancies shall comply with

2196 UAC R317-3, Design Requirements for Wastewater Collection, Treatment, and Disposal, and

2197 UAC R317-4, Onsite Waterwaste Systems."

2198 Section 31. Section **15A-3-315** is enacted to read:

2199 **15A-3-315. Amendments to Chapter 15 of IPC.**

2200 In IPC, Chapter 15, the following referenced standard is added:

| <u>"Standard reference number</u> | <u>Title</u> | <u>Referenced in code section number</u> |
|---|---|--|
| <u>USC-FCCCHR 10th Edition Manual of Cross Connection Control</u> | <u>Foundation for Cross-Connection Control and Hydraulic Research University of Southern California Kaprielian Hall 300 Los Angeles CA 90089-2531</u> | <u>Table 608.1"</u> |

2203 Section 32. Section **15A-3-401** is amended to read:

2204 **15A-3-401. General provisions.**

2205 The following are adopted as amendments to the IMC to be applicable statewide:

2206 [~~1) In IMC, Section 202, the definition for "CONDITIONED SPACE" is deleted and~~
 2207 ~~replaced with the following: "CONDITIONED SPACE. An area, room, or space enclosed~~
 2208 ~~within the building thermal envelope that is directly heated or cooled, or indirectly heated or~~
 2209 ~~cooled by any of the following means:]~~

2210 [~~1. Openings directly into an adjacent conditioned space.]~~

2211 [~~2. An un-insulated floor, ceiling or wall adjacent to a conditioned space.]~~

2212 [~~3. Un-insulated duct, piping or other heat or cooling source within the space."]~~

2213 [(2) In IMC, Section 403.2.1, Item 3, is deleted and replaced with the following:

2214 "Except as provided in Table 403.3, Note h, where mechanical exhaust is required by Note b in
 2215 Table 403.3, recirculation of air from such spaces is prohibited. All air supplied to such spaces
 2216 shall be exhausted, including any air in excess of that required by Table 403.3."

2217 [(3) In IMC, Table 403.3, Note b, is deleted and replaced with the following: "Except
 2218 as provided in Note h, mechanical exhaust required and the recirculation of air from such
 2219 spaces is prohibited (see Section 403.2.1, Item 3)."]

2220 [(4) In IMC, Table 403.3, Note h is deleted and replaced with the following:]

2221 ~~["1. For a nail salon where a nail technician files or shapes an acrylic nail, as defined~~
2222 ~~by rule by the Division of Occupational and Professional Licensing, in accordance with Title~~
2223 ~~63G, Chapter 3, Utah Administrative Rulemaking Act, each nail station where a nail technician~~
2224 ~~files or shapes an acrylic nail shall be provided with:]~~

2225 ~~[a. a source capture system capable of filtering and recirculating air to inside space not~~
2226 ~~less than 50 cfm per station; or]~~

2227 ~~[b. a source capture system capable of exhausting not less than 50 cfm per station."]~~

2228 ~~[2. Except as provided in paragraph 3, the requirements described in paragraph 1 apply~~
2229 ~~beginning on July 1, 2020.]~~

2230 ~~[3. The requirements described in paragraph 1 apply beginning on July 1, 2014 if the~~
2231 ~~nail salon is under or begins new construction or remodeling on or after July 1, 2014.]~~

2232 ~~[(5) In IMC, Section 403, a new Section 403.8 is added as follows: "Retrospective~~
2233 ~~effect. Removal, alteration, or abandonment shall not be required, and continued use and~~
2234 ~~maintenance shall be allowed, for a ventilation system within an existing installation that~~
2235 ~~complies with the requirements of this Section 403 regardless of whether the ventilation system~~
2236 ~~satisfied the minimum ventilation rate requirements of prior law."]~~

2237 ~~[(6) In IMC, Table 603.4, in the section "Round ducts and enclosed rectangular ducts",~~
2238 ~~the word "enclosed" is deleted; the words "14 inches or less" are deleted and replaced with~~
2239 ~~"over 8 inches but less than 15 inches"; the wording "8 inches or less" under duct size, "0.013"~~
2240 ~~under minimum thickness (in.), "30" under equivalent gage no., and "0.0159" under aluminum~~
2241 ~~minimum thickness (in.), are added; and the section "Exposed rectangular ducts" is deleted.]~~

2242 ~~[(7)]~~ (1) In IMC, Section 1004.2, the first sentence is deleted and replaced with the
2243 following: "~~[Boilers]~~ In accordance with Title 34A, Chapter 7, Safety, and requirements made
2244 by rule by the Labor Commission, boilers and pressure vessels in Utah are regulated by the
2245 Utah Labor Commission, Division of Boiler, Elevator and Coal Mine Safety, except those
2246 located in private residences or in apartment houses of less than five family units. Boilers shall
2247 be installed in accordance with their listing and labeling, with minimum clearances as
2248 prescribed by the manufacturer's installation instructions and the state boiler code, whichever is

2249 greater."

2250 [~~(8)~~] (2) In IMC, Section 1004.3.1, the word "unlisted" is inserted before the word
2251 "boilers".

2252 [~~(9)~~] (3) IMC, Section 1101.10, is deleted.

2253 (4) In IMC, Section 1209.3, the following words are added at the end of the section:
2254 "or other methods approved for the application."

2255 Section 33. Section **15A-3-501** is amended to read:

2256 **15A-3-501. General provisions.**

2257 The following are adopted as an amendment to the IFGC to be applicable statewide:

2258 (1) In IFGC, Section 404.9, a new Section 404.9.1, is added as follows: "404.9.1 Meter
2259 protection. Fuel gas services shall be in an approved location and/or provided with structures
2260 designed to protect the fuel gas meter and surrounding piping from physical damage, including
2261 falling, moving, or migrating ice and snow. If an added structure is used, it must still provide
2262 access for service and comply with the IBC or the IRC."

2263 (2) IFGC, Section 409.5.3, is deleted.

2264 (3) In IFGC, Section 631.2, the following sentence is inserted before the first sentence:

2265 "[~~Boilers~~] In accordance with Title 34A, Chapter 7, Safety, and requirements made by rule by
2266 the Labor Commission, boilers and pressure vessels in Utah are regulated by the Utah Labor
2267 Commission, Division of Boiler, Elevator and Coal Mine Safety, except those located in
2268 private residences or in apartment houses of less than five family units. Boilers shall be
2269 installed in accordance with their listing and labeling, with minimum clearances as prescribed
2270 by the manufacturer's installation instructions and the state boiler code, whichever is greater."

2271 Section 34. Section **15A-3-601** is amended to read:

2272 **15A-3-601. General provisions.**

2273 The following are adopted as amendments to the NEC to be applicable statewide:

2274 (1) The IRC provisions are adopted as the residential electrical standards applicable to
2275 installations applicable under the IRC. All other installations shall comply with the adopted
2276 NEC.

2277 ~~[(2) In NEC, Section 310.15(B)(7), the second sentence is deleted and replaced with~~
2278 ~~the following: "For application of this section, the main power feeder shall be the feeder(s)~~
2279 ~~between the main disconnect and the panelboard(s)."]~~

2280 (2) NEC, Section 240.87(B), is modified to add the following as an additional
2281 approved equivalent means:

2282 "6. An instantaneous trip function set at or below the available fault current."

2283 Section 35. Section **15A-3-701** is amended to read:

2284 **15A-3-701. General provisions.**

2285 The following is adopted as an amendment to the IECC to be applicable statewide:

2286 ~~[(1) In IECC, Section C202, the definition for "CONDITIONED SPACE" is deleted~~
2287 ~~and replaced with the following: "CONDITIONED SPACE. An area, room or space enclosed~~
2288 ~~within the building thermal envelope that is directly heated or cooled, or indirectly heated or~~
2289 ~~cooled by any of the following means:]~~

2290 ~~[1. Openings directly into an adjacent conditioned space.]~~

2291 ~~[2. An un-insulated floor, ceiling or wall adjacent to a conditioned space.]~~

2292 ~~[3. Un-insulated duct, piping or other heat or cooling source within the space.]"~~

2293 ~~[(2) In IECC, Section C404.4, a new exception is added as follows: "Exception: Heat~~
2294 ~~traps, other than the arrangement of piping and fittings, shall be prohibited unless a means of~~
2295 ~~controlling thermal expansion can be ensured as required in the IPC Section 607.3."]~~

2296 (1) In IECC, Section C403.2.9.1.3, the words "by the designer" are deleted.

2297 ~~[(3)]~~ (2) In IECC, Section R103.2, all words after the words "herein governed." are
2298 deleted and replaced with the following: "Construction documents include all documentation
2299 required to be submitted in order to issue a building permit."

2300 ~~[(4) In IECC, Section R202, the definition for "CONDITIONED SPACE" is deleted~~
2301 ~~and replaced with the following: "CONDITIONED SPACE. An area, room or space enclosed~~
2302 ~~within the building thermal envelope that is directly heated or cooled, or indirectly heated or~~
2303 ~~cooled by any of the following means:]~~

2304 ~~[1. Openings directly into an adjacent conditioned space.]~~

2305 [~~2. An un-insulated floor, ceiling or wall adjacent to a conditioned space.~~
 2306 ~~3. Un-insulated duct, piping or other heat or cooling source within the space.~~"]
 2307 [(5)] (3) In IECC, Section R303.3, all wording after the first sentence is deleted.
 2308 (4) In IECC, Section R401.2, a new number 4 is added as follows:
 2309 "4. Compliance may be shown by demonstrating a result, using the software
 2310 RESCheck 2012 Utah Energy Conservation Code, of:
 2311 (a) on or after January 1, 2017, and before January 1, 2019, "3 percent better than
 2312 code";
 2313 (b) on or after January 1, 2019, and before January 1, 2021, "4 percent better than
 2314 code"; and
 2315 (c) after January 1, 2021, "5 percent better than code".
 2316 [(6)] (5) In IECC, Table [~~R402.1.1 and Table R402.1.3, the rows for "climate zone 3",~~
 2317 ~~"climate zone 5 and Marine 4, and climate zone 6" are deleted and replaced and] R402.2, in the~~
 2318 column entitled MASS WALL R-VALUE, a new footnote j is added as follows:
 2319 [

| "TABLE R402.1.1 | | | | | | | | | | |
|--|------------------------------------|--------------------------------|---|-----------------|---------------------------|----------------------------------|-----------------|------------------------------------|-----------------------------------|---------------------------------------|
| INSULATION AND FENESTRATION REQUIREMENTS BY COMPONENT ^a | | | | | | | | | | |
| CLIMATE ZONE | FENESTRATION U-FACTOR ^b | SKYLIGHT ^b U-FACTOR | GLAZED FENESTRATION SHGC ^{b,c} | CEILING R-VALUE | WOOD FRAME WALL R-VALUE | MASS WALL R-VALUE ^{d,e} | FLOOR R-VALUE | BASEMENT ^f WALL R-VALUE | SLAB ^g R-VALUE & DEPTH | CRAWL SPACE ^h WALL R-VALUE |
| 3 | 0.65 | 0.65 | 0.40 | 30 | 15 | 5 | 19 | 0 | 0 | 5/13 |
| 5 and Marine 4 | 0.35 | 0.60 | NR | 38 | 19 or 13 + 5 ^h | 13 | 30 ^e | 10/13 | 10, 2 ft | 10/13 |
| 6 | 0.35 | 0.60 | NR | 49 | 19 or 13 + 5 ^h | 15 | 30 ^e | 10/13 | 10, 4 ft | 10/13 |

j. Log walls complying with ICC400 and with a minimum average wall thickness of 5" or greater shall be permitted in Zones 5-8 when overall window glazing is .31 U-factor or lower, minimum heating equipment efficiency is 90 AFUE (gas) or 84 AFUE (oil), and all other component requirements are met.

| TABLE R402.1.3 EQUIVALENT U-FACTORS ^a | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|
|--|--|--|--|--|--|--|--|--|--|--|

| CLIMATE ZONE | FENESTRATION U-FACTOR | SKYLIGHT U-FACTOR | CEILING U-FACTOR | FRAME WALL U-FACTOR | MASS WALL U-FACTOR | FLOOR U-FACTOR | BASEMENT WALL U-FACTOR | CRAWL SPACE WALL U-FACTOR |
|----------------|-----------------------|-------------------|------------------|---------------------|--------------------|----------------|------------------------|---------------------------|
| 3 | 0.65 | 0.65 | 0.035 | 0.082 | 0.141 | 0.047 | 0.360 | 0.136 |
| 5 and Marine 4 | 0.35 | 0.60 | 0.030 | 0.060 | 0.082 | 0.033 | 0.059 | 0.065 |
| 6 | 0.35 | 0.60 | 0.026 | 0.060 | 0.060 | 0.033 | 0.059 | 0.065 |

2332]"j. Log walls complying with ICC400 and with a minimum average wall thickness of 5 inches
 2333 or greater shall be permitted in Zones 5 through 8 when overall window glazing has a .31
 2334 U-factor or lower, minimum heating equipment efficiency is, for gas, 90 AFUE, or, for oil, 84
 2335 AFUE, and all other component requirements are met."

2336 [~~7~~] In IECC, Section R402.2.1, the last sentence is deleted.]

2337 [~~8~~] In IECC, Section R402.2.2, the last sentence is deleted.]

2338 [~~9~~] In IECC, Section R402.3.3, the last sentence is deleted.]

2339 [~~10~~] In IECC, Section R402.3.4, the last sentence is deleted.]

2340 [~~11~~] (6) In IECC, Section R402.4.1, in the first sentence, the word "and" is deleted
 2341 and replaced with the word "or".

2342 [~~12~~] (7) In IECC, Section R402.4.1.1, the last sentence is deleted and replaced with
 2343 the following: "Where allowed by the [building] code official, the builder may certify
 2344 compliance to components criteria for items which may not be inspected during regularly
 2345 scheduled inspections."

2346 [~~13~~] (8) In IECC, Section R402.4.1.2, the following changes are made:

2347 (a) In the first sentence:

2348 (i) on or after January 1, 2019, and before January 1, 2021, replace the word "five"
 2349 with "3.5"; and

2350 (ii) after January 1, 2021, replace the word "five" with "three."

2351 [~~a~~] (b) In the first sentence, the words "in Climate Zones 1 and 2, and [~~3~~] three air
 2352 changes per hour in [~~Zone~~] Climate Zones 3 through 8" are deleted.

2353 [~~b~~] (c) In the third sentence, the [~~words "Where required by the building official," and~~
 2354 ~~the~~] word "third" [~~are~~] is deleted.

2355 [(e)] (d) The following sentence is inserted after the third sentence: "The following
 2356 parties shall be approved to conduct testing: Parties certified by BPI or RESNET, or licensed
 2357 contractors who have completed training provided by Blower Door Test equipment
 2358 manufacturers or other comparable training."

2359 [~~(14) In IECC, Section R402.4.4, the last sentence is deleted.~~]

2360 [~~(15) In IECC, Section R403.2.2, the requirements for duct tightness testing are deleted
 2361 and replaced with the following:~~]

2362 [~~"1. Postconstruction test: Total leakage shall be less than or equal to 10 cfm (283
 2363 L/min) per 100 square feet (9.29 m²) of conditioned floor space when tested at a pressure
 2364 differential of 0.1 inches w.g. (25 Pa) across the entire system, including the manufacturer's air
 2365 handler enclosure. All register boots shall be taped or otherwise sealed during the test.~~]

2366 [~~2. Rough-in test: Total leakage shall be less than or equal to 10 cfm (283 L/min) per
 2367 100 square feet (9.29 m²) of conditioned floor area when tested at a pressure differential of at
 2368 least 0.1 inches w.g. (25 Pa) across the system, including the manufacturer's air handler
 2369 enclosure. All registers shall be taped or otherwise sealed during the test. If the air handler is
 2370 not installed at the time of the test, total leakage shall be less than or equal to 7.5 cfm (212
 2371 L/min) per 100 square feet (9.29 m²) of conditioned floor area."~~]

2372 [(16)] (9) In IECC, Section [~~R403.2.2;~~] R403.3.3:

2373 (a) the exception for [~~total~~] duct air leakage testing is deleted; and

2374 (b) the exception for duct air leakage is replaced:

2375 (i) on or after January 1, 2017, and before January 1, 2019, with the following:

2376 "Exception: The total leakage test is not required for systems with all air handlers and at least
 2377 [~~50%~~] 65% of all ducts (measured by length) located entirely within the building thermal
 2378 envelope.";

2379 (ii) on or after January 1, 2019, and before January 1, 2021, with the following:

2380 "Exception: The duct air leakage test is not required for systems with all air handlers and at
 2381 least 75% of all ducts (measured by length) located entirely within the building thermal
 2382 envelope."; and

2383 (iii) on or after January 1, 2021, with the following: "Exception: The duct air leakage
2384 test is not required for systems with all air handlers and at least 80% of all ducts (measured by
2385 length) located entirely within the building thermal envelope."

2386 (10) In IECC, Section R403.3.3, the following is added after the exception:

2387 "The following parties shall be approved to conduct testing:

2388 1. Parties certified by BPI or RESNET.

2389 2. Licensed contractors who have completed training provided by Duct Test equipment
2390 manufacturers or other comparable training."

2391 (11) In IECC, Section R403.3.4:

2392 (a) in Subsection 1, the number 4 is changed to 8, the number 113.3 is changed to 170,
2393 the number 3 is changed to 6, and the number 85 is changed to 114.6; and

2394 (b) in Subsection 2:

2395 (i) on or after January 1, 2017, and before January 1, 2019, the number 4 is changed to
2396 8 and the number 113.3 is changed to 226.5;

2397 (ii) on or after January 1, 2019, and before January 1, 2021, the number 4 is changed to
2398 7 and the number 113.3 is changed to 198.2; and

2399 (iii) on or after January 1, 2021, the number 4 is changed to 6 and the number 113.3 is
2400 changed to 169.9.

2401 ~~[(17)] (12) In IECC, Section [R403.2.3] R403.3.5, the words "or plenums" are deleted.~~

2402 ~~[(18) In IECC, Section R403.4.2, the sentences for "3." and "9." and the last sentence~~
2403 ~~are deleted.]~~

2404 ~~[(19) In IECC, Section R403.5, the first sentence is deleted.]~~

2405 ~~[(20) IECC, Section R404.1 and the exception are deleted, and R404.1.1 becomes~~
2406 ~~R404.1.]~~

2407 ~~[(21) In IECC, Table R405.5.2(1), the following changes are made under the column~~
2408 ~~STANDARD REFERENCE DESIGN:]~~

2409 ~~[(a) In the row "Air exchange rate", the words "in Zones 1 and 2, and 3 air changes per~~
2410 ~~hour in Zones 3 through 8" are deleted.]~~

2411 ~~[(b) In the row "Heating systems^{f, g}", the standard reference design is deleted and~~
2412 ~~replaced with the following:]~~

2413 ~~["Fuel Type: same as proposed design]~~

2414 ~~[Efficiencies:]~~

2415 ~~[Electric: air source heat pump with prevailing federal minimum efficiencies]~~

2416 ~~[Nonelectric furnaces: natural gas furnace with prevailing federal minimum~~
2417 ~~efficiencies]~~

2418 ~~[Nonelectric boilers: natural gas boiler with prevailing federal minimum efficiencies]~~

2419 ~~[Capacity: sized in accordance with Section N1103.6"]~~

2420 ~~[(c) In the row "Cooling systems^{f, h}" the words "As proposed" are deleted and replaced~~
2421 ~~with the following:]~~

2422 ~~["Fuel Type: Electric]~~

2423 ~~[Efficiency: in accordance with prevailing federal minimum standards"]~~

2424 ~~[(d) In the row "Service water heating^{f, g, h, i}", the words "As proposed" are deleted and~~
2425 ~~replaced with the following:]~~

2426 ~~["Fuel Type: same as proposed design]~~

2427 ~~[Efficiency: in accordance with prevailing federal minimum standards]~~

2428 ~~[Tank Temperature: 120° F"]~~

2429 ~~[(e) In the row "Thermal distribution systems" the word "none" is deleted and replaced~~
2430 ~~with the following: "Thermal distribution system efficiency (DSE) of .080 shall be applied to~~
2431 ~~both the heating and cooling system efficiencies."]~~

2432 ~~[(22) In IECC, Table R405.5.2(2), the number "0.80" is inserted under "Forced air~~
2433 ~~systems" for "Distribution system components located in unconditioned space".]~~

2434 ~~[(23) The RESCheck Software adopted by the United States Department of Energy and~~
2435 ~~modified to meet the requirements of this section shall be used to verify compliance with this~~
2436 ~~section. The software shall address the Total UA alternative approach and account for~~
2437 ~~Equipment Efficiency Trade-offs when applicable per the standard reference design as~~
2438 ~~amended:.]~~

2439 (13) In IECC, Section R403.5.3, Subsection 5 is deleted and Subsections 6 and 7 are
 2440 renumbered.

2441 (14) In IECC, Section R406.4, the table is deleted and replaced with the following:

2442 TABLE R406.4

2443 MAXIMUM ENERGY RATING INDEX

| <u>2444CLIMATE ZONE</u> | <u>ENERGY RATING INDEX</u> |
|-------------------------|----------------------------|
| <u>24453</u> | <u>65</u> |
| <u>24465</u> | <u>69</u> |
| <u>24476</u> | <u>68</u> |

2448 Section 36. Section **15A-3-801** is amended to read:

2449 **Part 8. Statewide Amendments to International Existing Building Code**

2450 **15A-3-801. General provisions.**

2451 [~~Mobile homes built before June 15, 1976 that are subject to relocation, building~~
 2452 ~~alteration, remodeling, or rehabilitation shall comply with the following:]~~

2453 [~~(1) Related to exits and egress windows:]~~

2454 [~~(a) Egress windows. The home has at least one egress window in each bedroom, or a~~
 2455 ~~window that meets the minimum specifications of the U.S. Department of Housing and Urban~~
 2456 ~~Development's (HUD) Manufactured Homes Construction and Safety Standards (MHCSS)~~
 2457 ~~program as set forth in 24 C.F.R. Parts 3280 and 3282, MHCSS 3280.106 and 3280.404 for~~
 2458 ~~manufactured homes. These standards require the window to be at least 22 inches in the~~
 2459 ~~horizontal or vertical position in its least dimension and at least five square feet in area. The~~
 2460 ~~bottom of the window opening shall be no more than 36 inches above the floor, and the locks~~
 2461 ~~and latches and any window screen or storm window devices that need to be operated to permit~~
 2462 ~~exiting shall not be located more than 54 inches above the finished floor.]~~

2463 [~~(b) Exits. The home is required to have two exterior exit doors, located remotely from~~
 2464 ~~each other, as required in MHCSS 3280.105. This standard requires that single-section homes~~

2465 have the doors no less than 12 feet, center-to-center, from each other, and multisection home
2466 doors no less than 20 feet center-to-center from each other when measured in a straight line,
2467 regardless of the length of the path of travel between the doors. One of the required exit doors
2468 must be accessible from the doorway of each bedroom and no more than 35 feet away from any
2469 bedroom doorway. An exterior swing door shall have a 28-inch-wide by 74-inch-high clear
2470 opening and sliding glass doors shall have a 28-inch-wide by 72-inch-high clear opening. Each
2471 exterior door other than screen/storm doors shall have a key-operated lock that has a passage
2472 latch; locks shall not require the use of a key or special tool for operation from the inside of the
2473 home.]

2474 [~~(2) Related to flame spread:~~]

2475 [~~(a) Walls, ceilings, and doors. Walls and ceilings adjacent to or enclosing a furnace or~~
2476 ~~water heater shall have an interior finish with a flame-spread rating not exceeding 25. Sealants~~
2477 ~~and other trim materials two inches or less in width used to finish adjacent surfaces within~~
2478 ~~these spaces are exempt from this provision, provided all joints are supported by framing~~
2479 ~~members or materials with a flame spread rating of 25 or less. Combustible doors providing~~
2480 ~~interior or exterior access to furnace and water heater spaces shall be covered with materials of~~
2481 ~~limited combustibility (i.e., 5/16-inch gypsum board, etc.), with the surface allowed to be~~
2482 ~~interrupted for louvers ventilating the space. However, the louvers shall not be of materials of~~
2483 ~~greater combustibility than the door itself (i.e., plastic louvers on a wooden door). Reference~~
2484 ~~MHCSS 3280.203.]~~

2485 [~~(b) Exposed interior finishes. Exposed interior finishes adjacent to the cooking range~~
2486 ~~(surfaces include vertical surfaces between the range top and overhead cabinets, the ceiling, or~~
2487 ~~both) shall have a flame-spread rating not exceeding 50, as required by MHCSS 3280.203.~~
2488 ~~Backsplashes not exceeding six inches in height are exempted. Ranges shall have a vertical~~
2489 ~~clearance above the cooking top of not less than 24 inches to the bottom of combustible~~
2490 ~~cabinets, as required by MHCSS 3280.204(e).]~~

2491 [~~(3) Related to smoke detectors:~~]

2492 [~~(a) Location. A smoke detector shall be installed on any ceiling or wall in the hallway~~

2493 or space communicating with each bedroom area between the living area and the first bedroom
2494 door, unless a door separates the living area from that bedroom area, in which case the detector
2495 shall be installed on the living-area side, as close to the door as practicable, as required by
2496 MHCSS 3280.208. Homes with bedroom areas separated by anyone or combination of
2497 common-use areas such as a kitchen, dining room, living room, or family room (but not a
2498 bathroom or utility room) shall be required to have one detector for each bedroom area. When
2499 located in the hallways, the detector shall be between the return air intake and the living areas.]

2500 ~~[(b) Switches and electrical connections. Smoke detectors shall have no switches in~~
2501 ~~the circuit to the detector between the over-current protection device protecting the branch~~
2502 ~~circuit and the detector. The detector shall be attached to an electrical outlet box and connected~~
2503 ~~by a permanent wiring method to a general electrical circuit. The detector shall not be placed~~
2504 ~~on the same branch circuit or any circuit protected by a ground-fault circuit interrupter.]~~

2505 ~~[(4) Related to solid-fuel-burning stoves/fireplaces:]~~

2506 ~~[(a) Solid-fuel-burning fireplaces and fireplace stoves. Solid-fuel-burning,~~
2507 ~~factory-built fireplaces, and fireplace stoves may be used in manufactured homes, provided that~~
2508 ~~they are listed for use in manufactured homes and installed according to their~~
2509 ~~listing/manufacturer's instructions and the minimum requirements of MHCSS 3280.709(g).]~~

2510 ~~[(b) Equipment. A solid-fuel-burning fireplace or fireplace stove shall be equipped~~
2511 ~~with an integral door or shutters designed to close the fire chamber opening and shall include~~
2512 ~~complete means for venting through the roof, a combustion air inlet, a hearth extension, and~~
2513 ~~means to securely attach the unit to the manufactured home structure.]~~

2514 ~~[(i) Chimney. A listed, factory-built chimney designed to be attached directly to the~~
2515 ~~fireplace/fireplace stove and equipped with, in accordance with the listing, a termination device~~
2516 ~~and spark arrester, shall be required. The chimney shall extend at least three feet above the part~~
2517 ~~of the roof through which it passes and at least two feet above the highest elevation of any part~~
2518 ~~of the manufactured home that is within 10 feet of the chimney.]~~

2519 ~~[(ii) Air-intake assembly and combustion-air inlet. An air-intake assembly shall be~~
2520 ~~installed in accordance with the terms of listings and the manufacturer's instruction. A~~

2521 ~~combustion-air inlet shall conduct the air directly into the fire chamber and shall be designed to~~
2522 ~~prevent material from the hearth from dropping on the area beneath the manufactured home.]~~

2523 ~~[(iii) Hearth. The hearth extension shall be of noncombustible material that is a~~
2524 ~~minimum of 3/8-inch thick and shall extend a minimum of 16 inches in front and eight inches~~
2525 ~~beyond each side of the fireplace/fireplace stove opening. The hearth shall also extend over the~~
2526 ~~entire surface beneath a fireplace stove and beneath an elevated and overhanging fireplace.]~~

2527 ~~[(5) Related to electrical wiring systems:]~~

2528 ~~[(a) Testing. All electrical systems shall be tested for continuity in accordance with~~
2529 ~~MHCSS 3280.810, to ensure that metallic parts are properly bonded; tested for operation, to~~
2530 ~~demonstrate that all equipment is connected and in working order; and given a polarity check,~~
2531 ~~to determine that connections are proper.]~~

2532 ~~[(b) 5.2 Protection. The electrical system shall be properly protected for the required~~
2533 ~~amperage load. If the unit wiring employs aluminum conductors, all receptacles and switches~~
2534 ~~rated at 20 amperes or less that are directly connected to the aluminum conductors shall be~~
2535 ~~marked CO/ALA. Exterior receptacles, other than heat tape receptacles, shall be of the~~
2536 ~~ground-fault circuit interrupter (GFI) type. Conductors of dissimilar metals (copper/aluminum~~
2537 ~~or copper-clad aluminum) must be connected in accordance with NEC, Section 110-14.]~~

2538 ~~[(6) Related to replacement furnaces and water heaters:]~~

2539 ~~[(a) Listing. Replacement furnaces or water heaters shall be listed for use in a~~
2540 ~~manufactured home. Vents, roof jacks, and chimneys necessary for the installation shall be~~
2541 ~~listed for use with the furnace or water heater.]~~

2542 ~~[(b) Securement and accessibility. The furnace and water heater shall be secured in~~
2543 ~~place to avoid displacement. Every furnace and water heater shall be accessible for servicing,~~
2544 ~~for replacement, or both as required by MHCSS 3280.709(a).]~~

2545 ~~[(c) Installation. Furnaces and water heaters shall be installed to provide complete~~
2546 ~~separation of the combustion system from the interior atmosphere of the manufactured home,~~
2547 ~~as required by MHCSS.]~~

2548 ~~[(i) Separation. The required separation may be achieved by the installation of a~~

2549 ~~direct-vent system (sealed combustion system) furnace or water heater or the installation of a~~
2550 ~~furnace and water heater venting and combustion systems from the interior atmosphere of the~~
2551 ~~home. There shall be no doors, grills, removable access panels, or other openings into the~~
2552 ~~enclosure from the inside of the manufactured home. All openings for ducts, piping, wiring,~~
2553 ~~etc., shall be sealed.]~~

2554 ~~[(ii) Water heater. The floor area in the area of the water heater shall be free from~~
2555 ~~damage from moisture to ensure that the floor will support the weight of the water heater.]~~

2556 The following are adopted as amendments to the IEBC and are applicable statewide:

2557 (1) In Section 202, the following definition is added: "BUILDING OFFICIAL. See
2558 Code Official."

2559 (2) In Section 202, the definition for "code official" is deleted and replaced with the
2560 following:

2561 "CODE OFFICIAL. The officer or other designated authority having jurisdiction (AHJ)
2562 charged with the administration and enforcement of this code."

2563 (3) In Section 202, the definition for existing buildings is deleted and replaced with the
2564 following:

2565 "EXISTING BUILDING. A building that is not a dangerous building and that was either
2566 lawfully erected under a prior adopted code, or deemed a legal non-conforming building by the
2567 code official."

2568 (4) In Section 301.1, the exception is deleted.

2569 (5) Section 403.5 is deleted and replaced with the following:

2570 "403.5 Bracing for unreinforced masonry parapets and other appendages upon reroofing.

2571 Where the intended alteration requires a permit for reroofing and involves removal of roofing

2572 materials from more than 25% of the roof area of a building assigned to Seismic Design

2573 Category D, E, or F that has parapets constructed of unreinforced masonry or appendages such

2574 as cornices, spires, towers, tanks, signs, statuary, etc., the work shall include installation of

2575 bracing to resist out-of-plane seismic forces, unless an evaluation demonstrates compliance of

2576 such items. For purposes of this section, design seismic forces need not be taken greater than

2577 75% of those that would be required for the design of similar nonstructural components in new
2578 buildings of similar purpose and location."

2579 (6) In Section 705.1, Exception number 3, the following is added at the end of the
2580 exception:

2581 "This exception does not apply if the existing facility is undergoing a change of occupancy
2582 classification."

2583 (7) Section 707.3.1 is deleted and replaced with the following:

2584 "707.3.1 Bracing for unreinforced masonry bearing wall parapets and other appendages.
2585 Where a permit is issued for reroofing more than 25 percent of the roof area of a building
2586 assigned to Seismic Design Category D, E, or F that has parapets constructed of unreinforced
2587 masonry or appendages such as cornices, spires, towers, tanks, signs, statuary, etc., the work
2588 shall include installation of bracing to resist the reduced International Building Code level
2589 seismic forces as specified in Section 301.1.4.2 of this code unless an evaluation demonstrates
2590 compliance of such items."

2591 (8) (a) Section 1007.3.1 is deleted and replaced with the following:

2592 "1007.3.1 Compliance with the International Building Code Level Seismic Forces.
2593 When a building or portion thereof is subject to a change of occupancy such that a change in
2594 the nature of the occupancy results in a higher risk category based on Table 1604.5 of the
2595 International Building Code or when such change of occupancy results in a design occupant
2596 load increase of 100% or more, the building shall conform to the seismic requirements of the
2597 International Building Code for the new risk category."

2598 (b) Section 1007.3.1, exceptions 1 through 3 remain unchanged.

2599 (c) In Section 1007.3.1, add a new exception 4 as follows:

2600 "4. Where the design occupant load increase is less than 25 occupants and the occupancy
2601 category does not change."

2602 (9) In Section 1012.7.3, exception 2 is deleted.

2603 (10) In Section 1012.8.2, number 7 is added as follows:

2604 "7. When a change of occupancy in a building or portion of a building results in a Group R-2

2605 occupancy, not less than 20% of the dwelling or sleeping units shall be Type B dwelling or
2606 sleeping units. These dwelling or sleeping units may be located on any floor of the building
2607 provided with an accessible route. Two percent, but not less than one unit, of the dwelling or
2608 sleeping units shall be Type A dwelling units."

2609 Section 37. Section **15A-3-901** is enacted to read:

2610 **Part 9. Installation and Safety Requirements for Mobile Homes**

2611 **Built Before June 15, 1976**

2612 **15A-3-901. General provisions.**

2613 Mobile homes built before June 15, 1976, that are subject to relocation, building
2614 alteration, remodeling, or rehabilitation shall comply with the following:

2615 (1) Related to exits and egress windows:

2616 (a) Egress windows. The home has at least one egress window in each bedroom, or a
2617 window that meets the minimum specifications of the United States Department of Housing
2618 and Urban Development's (HUD) Manufactured Homes Construction and Safety Standards
2619 (MHCSS) program as set forth in 24 C.F.R. Parts 3280 and 3282, MHCSS 3280.106 and
2620 3280.404 for manufactured homes. These standards require the window to be at least 22
2621 inches in the horizontal or vertical position in its least dimension and at least five square feet in
2622 area. The bottom of the window opening shall be no more than 36 inches above the floor, and
2623 the locks and latches and any window screen or storm window devices that need to be operated
2624 to permit exiting shall not be located more than 54 inches above the finished floor.

2625 (b) Exits. The home is required to have two exterior exit doors, located remotely from
2626 each other, as required in MHCSS 3280.105. This standard requires that a single-section home
2627 have the doors no less than 12 feet, center-to-center, from each other, and a multisection home
2628 have the doors no less than 20 feet, center-to-center, from each other, when measured in a
2629 straight line, regardless of the length of the path of travel between the doors. One of the
2630 required exit doors must be accessible from the doorway of each bedroom and no more than 35
2631 feet away from any bedroom doorway. An exterior swing door shall have a 28-inch-wide by
2632 74-inch-high clear opening and sliding glass doors shall have a 28-inch-wide by 72-inch-high

2633 clear opening. Each exterior door other than screen/storm doors shall have a key-operated lock
2634 that has a passage latch; locks shall not require the use of a key or special tool for operation
2635 from the inside of the home.

2636 (2) Related to flame spread:

2637 (a) Walls, ceilings, and doors. Walls and ceilings adjacent to or enclosing a furnace or
2638 water heater shall have an interior finish with a flame-spread rating not exceeding 25. Sealants
2639 and other trim materials two inches or less in width used to finish adjacent surfaces within
2640 these spaces are exempt from this provision, provided all joints are supported by framing
2641 members or materials with a flame spread rating of 25 or less. Combustible doors providing
2642 interior or exterior access to furnace and water heater spaces shall be covered with materials of
2643 limited combustibility (i.e., 5/16-inch gypsum board, etc.), with the surface allowed to be
2644 interrupted for louvers ventilating the space. However, the louvers shall not be of materials of
2645 greater combustibility than the door itself (i.e., plastic louvers on a wooden door). Reference
2646 MHCSS 3280.203.

2647 (b) Exposed interior finishes. Exposed interior finishes adjacent to the cooking range
2648 (surfaces include vertical surfaces between the range top and overhead cabinets, the ceiling, or
2649 both) shall have a flame-spread rating not exceeding 50, as required by MHCSS 3280.203.
2650 Backsplashes not exceeding six inches in height are exempted. Ranges shall have a vertical
2651 clearance above the cooking top of not less than 24 inches to the bottom of combustible
2652 cabinets, as required by MHCSS 3280.204(e).

2653 (3) Related to smoke detectors:

2654 (a) Location. A smoke detector shall be installed on any ceiling or wall in the hallway
2655 or space communicating with each bedroom area between the living area and the first bedroom
2656 door, unless a door separates the living area from that bedroom area, in which case the detector
2657 shall be installed on the living-area side, as close to the door as practicable, as required by
2658 MHCSS 3280.208. Homes with bedroom areas separated by any one or combination of
2659 common-use areas such as a kitchen, dining room, living room, or family room (but not a
2660 bathroom or utility room) shall be required to have one detector for each bedroom area. When

2661 located in the hallways, the detector shall be between the return air intake and the living areas.

2662 (b) Switches and electrical connections. Smoke detectors shall have no switches in the
2663 circuit to the detector between the overcurrent protection device protecting the branch circuit
2664 and the detector. The detector shall be attached to an electrical outlet box and connected by a
2665 permanent wiring method to a general electrical circuit. The detector shall not be placed on the
2666 same branch circuit or any circuit protected by a ground-fault circuit interrupter.

2667 (4) Related to solid-fuel-burning stoves/fireplaces:

2668 (a) Solid-fuel-burning fireplaces and fireplace stoves. Solid-fuel-burning, factory-built
2669 fireplaces and fireplace stoves may be used in manufactured homes, provided that they are
2670 listed for use in manufactured homes and installed according to their listing/manufacture's
2671 instructions and the minimum requirements of MHCSS 3280.709(g).

2672 (b) Equipment. A solid-fuel-burning fireplace or fireplace stove shall be equipped with
2673 an integral door or shutters designed to close the fire chamber opening and shall include
2674 complete means for venting through the roof, a combustion air inlet, a hearth extension, and
2675 means to securely attach the unit to the manufactured home structure.

2676 (i) Chimney. A listed, factory-built chimney designed to be attached directly to the
2677 fireplace/fireplace stove and equipped with, in accordance with the listing, a termination device
2678 and spark arrester shall be required. The chimney shall extend at least three feet above the part
2679 of the roof through which it passes and at least two feet above the highest elevation of any part
2680 of the manufactured home that is within 10 feet of the chimney.

2681 (ii) Air-intake assembly and combustion-air inlet. An air-intake assembly shall be
2682 installed in accordance with the terms of listings and the manufacturer's instruction. A
2683 combustion-air inlet shall conduct the air directly into the fire chamber and shall be designed to
2684 prevent material from the hearth from dropping on the area beneath the manufactured home.

2685 (iii) Hearth. The hearth extension shall be of noncombustible material that is a
2686 minimum of 3/8-inch thick and shall extend a minimum of 16 inches in front and eight inches
2687 beyond each side of the fireplace/fireplace stove opening. The hearth shall also extend over the
2688 entire surface beneath a fireplace stove and beneath an elevated and overhanging fireplace.

2689 (5) Related to electrical wiring systems:

2690 (a) Testing. All electrical systems shall be tested for continuity, in accordance with
2691 MHCSS 3280.810, to ensure that metallic parts are properly bonded; tested for operation, to
2692 demonstrate that all equipment is connected and in working order; and given a polarity check,
2693 to determine that connections are proper.

2694 (b) 5.2 Protection. The electrical system shall be properly protected for the required
2695 amperage load. If the unit wiring employs aluminum conductors, all receptacles and switches
2696 rated at 20 amperes or less that are directly connected to the aluminum conductors shall be
2697 marked CO/ALA. Exterior receptacles, other than heat tape receptacles, shall be of the
2698 ground-fault circuit interrupter (GFCI) type. Conductors of dissimilar metals
2699 (copper/aluminum or copper-clad aluminum) must be connected in accordance with NEC,
2700 Section 110-14.

2701 (6) Related to replacement furnaces and water heaters:

2702 (a) Listing. Replacement furnaces or water heaters shall be listed for use in a
2703 manufactured home. Vents, roof jacks, and chimneys necessary for the installation shall be
2704 listed for use with the furnace or water heater.

2705 (b) Securement and accessibility. The furnace and water heater shall be secured in
2706 place to avoid displacement. Every furnace and water heater shall be accessible for servicing,
2707 for replacement, or both as required by MHCSS 3280.709(a).

2708 (c) Installation. Furnaces and water heaters shall be installed to provide complete
2709 separation of the combustion system from the interior atmosphere of the manufactured home,
2710 as required by MHCSS.

2711 (i) Separation. The required separation may be achieved by the installation of a
2712 direct-vent system (sealed combustion system) furnace or water heater or the installation of
2713 furnace and water heater venting and combustion systems from the interior atmosphere of the
2714 home. There shall be no doors, grills, removable access panels, or other openings into the
2715 enclosure from the inside of the manufactured home. All openings for ducts, piping, wiring,
2716 etc., shall be sealed.

2717 (ii) Water heater. The floor area in the area of the water heater shall be free from
2718 damage from moisture to ensure that the floor will support the weight of the water heater.

2719 Section 38. Section **15A-4-103** is amended to read:

2720 **15A-4-103. Amendments to IBC applicable to City of Farmington.**

2721 The following amendments are adopted as amendments to the IBC for the City of
2722 Farmington:

2723 ~~[(1) A new IBC, Section (F) 903.2.13, is added as follows: "(F) 903.2.13 Group R;~~
2724 ~~Division 3 Occupancies. An automatic sprinkler system shall be installed throughout every~~
2725 ~~dwelling in accordance with NFPA 13D, when any of the following conditions are present:]~~

2726 ~~[1. The structure is over two stories high, as defined by the building code;]~~

2727 ~~[2. The nearest point of structure is more than 150 feet from the public way;]~~

2728 ~~[3. The total floor area of all stories is over 5,000 square feet (excluding from the calculation~~
2729 ~~the area of the basement and/or garage); or]~~

2730 ~~[4. The structure is located on a street constructed after March 1, 2000, that has a gradient over~~
2731 ~~12% and, during fire department response, access to the structure will be gained by using such~~
2732 ~~street. (If the access is intended to be from a direction where the steep gradient is not used, as~~
2733 ~~determined by the Chief, this criteria shall not apply).]~~

2734 ~~[Such sprinkler system shall be installed in basements, but need not be installed in garages;~~
2735 ~~under eaves or in enclosed attic spaces, unless required by the Chief."]~~

2736 ~~[(2)]~~ (1) A new IBC, Section 907.9, is added as follows: "907.9 Alarm Circuit
2737 Supervision. Alarm circuits in alarm systems provided for commercial uses (defined as other
2738 than one- and two-family dwellings and townhouses) shall have Class "A" type of supervision.
2739 Specifically, Type "B" or End-of-line resistor and horn supervised systems are not allowed."

2740 ~~[(3)]~~ (2) In NFPA Section 13-07, new sections are added as follows: "6.8.6 FDC
2741 Security Locks Required. All Fire Department connections installed for fire sprinkler and
2742 standpipe systems shall have approved security locks.

2743 6.10 Fire Pump Disconnect Signs. When installing a fire pump, red plastic laminate signs shall
2744 be installed in the electrical service panel, if the pump is wired separately from the main

2745 disconnect. These signs shall state: "Fire Pump Disconnect ONLY" and "Main Breaker DOES
2746 NOT Shut Off Fire Pump".

2747 22.1.6 Plan Preparation Identification. All plans for fire sprinkler systems, except for
2748 manufacturer's cut sheets of equipment shall include the full name of the person who prepared
2749 the drawings. When the drawings are prepared by a registered professional engineer, the
2750 engineer's signature shall also be included.

2751 22.2.2.3 Verification of Water Supply:

2752 22.2.2.3.1 Fire Flow Tests. Fire flow tests for verification of water supply shall be conducted
2753 and witnessed for all applications other than residential unless directed otherwise by the Chief.
2754 For residential water supply, verification shall be determined by administrative procedure.

2755 22.2.2.3.2 Accurate and Verifiable Criteria. The design calculations and criteria shall include
2756 an accurate and verifiable water supply.

2757 24.2.3.7 Testing and Inspection of Systems. Testing and inspection of sprinkler systems shall
2758 include, but are not limited to:

2759 Commercial:

2760 FLUSH-Witness Underground Supply Flush;

2761 ROUGH Inspection-Installation of Riser, System Piping, Head Locations and all Components,
2762 Hydrostatic Pressure Test;

2763 FINAL Inspection-Head Installation and Escutcheons, Inspectors Test Location and Flow,
2764 Main Drain Flow, FDC Location and Escutcheon, Alarm Function, Spare Parts, Labeling of
2765 Components and Signage, System Completeness, Water Supply Pressure Verification,
2766 Evaluation of Any Unusual Parameter."

2767 Section 39. Section **15A-4-107** is amended to read:

2768 **15A-4-107. Amendments to IBC applicable to Sandy City.**

2769 The following amendments are adopted as amendments to the IBC for Sandy City:

2770 (1) A new IBC, Section (F)903.2.13, is added as follows: "(F)903.2.13 An automatic
2771 sprinkler system shall be installed in accordance with NFPA 13 throughout buildings
2772 containing all occupancies where fire flow exceeds 2,000 gallons per minute, based on Table

2773 B105.1 of the [2009] 2015 International Fire Code. Exempt locations as indicated in Section
 2774 903.3.1.1.1 are allowed.

2775 Exception: Automatic fire sprinklers are not required in buildings used solely for worship,
 2776 Group R Division 3, Group U occupancies and buildings complying with the International
 2777 Residential Code unless otherwise required by the International Fire Code.

2778 (2) A new IBC, Appendix L, is added and adopted as follows: "Appendix L
 2779 BUILDINGS AND STRUCTURES CONSTRUCTED IN AREAS DESIGNATED AS
 2780 WILDLAND-URBAN INTERFACE AREAS

2781 AL 101.1 General. Buildings and structures constructed in areas designated as Wildland-Urban
 2782 Interface Areas by Sandy City shall be constructed using ignition resistant construction as
 2783 determined by the Fire Marshal. Section 502 of the 2006 International Wildland-Urban
 2784 Interface Code (IWUIC), as promulgated by the International Code Council, shall be used to
 2785 determine Fire Hazard Severity. The provisions listed in Chapter 5 of the 2006 International
 2786 Wildland-Urban Interface Code, as modified herein, shall be used to determine the
 2787 requirements for Ignition Resistant Construction.

2788 (i) In Section 504 of the IWUIC Class I IGNITION-RESISTANT CONSTRUCTION a new
 2789 Section 504.1.1 is added as follows: "504.1.1 General. Subsections 504.5, 504.6, and 504.7
 2790 shall only be required on the exposure side of the structure, as determined by the Fire Marshal,
 2791 where defensible space is less than 50 feet as defined in Section 603 of the 2006 International
 2792 Wildland-Urban Interface Code.

2793 (ii) In Section 505 of the IWUIC Class 2 IGNITION-RESISTANT CONSTRUCTION
 2794 Subsections 505.5 and 505.7 are deleted."

2795 Section 40. Section **15A-4-203** is amended to read:

2796 **15A-4-203. Amendments to IRC applicable to City of Farmington.**

2797 The following amendments are adopted as amendments to the IRC for the City of
 2798 Farmington:

2799 [~~1~~] In IRC, R324 Automatic Sprinkler Systems, new IRC, Sections R324.1 and
 2800 R324.2 are added as follows: "~~R324.1~~ When required. An automatic sprinkler system shall be

2801 installed throughout every dwelling in accordance with NFPA 13D, when any of the following
2802 conditions are present:]

2803 [~~1. the structure is over two stories high, as defined by the building code;~~]

2804 [~~2. the nearest point of structure is more than 150 feet from the public way;~~]

2805 [~~3. the total floor area of all stories is over 5,000 square feet (excluding from the calculation
2806 the area of the basement and/or garage); or]~~

2807 [~~4. the structure is located on a street constructed after March 1, 2000 that has a gradient over
2808 12% and, during fire department response, access to the structure will be gained by using such
2809 street. (If the access is intended to be from a direction where the steep gradient is not used, as
2810 determined by the Chief, this criteria shall not apply).]~~

2811 [~~R324.2 Installation requirements and standards. Such sprinkler system shall be installed in
2812 basements, but need not be installed in garages, under eaves or in enclosed attic spaces, unless
2813 required by the Chief. Such system shall be installed in accordance with NFPA 13D."~~]

2814 [~~(2)~~] (1) In IRC, Chapter 44, the following NFPA referenced standards are added as
2815 follows:

| | | |
|--|--------|--|
| | | "TABLE |
| | ADD | |
| | 13D-07 | Installation of Sprinkler Systems in One- and Two-family Dwellings and Manufactured Homes, as amended by these rules |
| | 13R-07 | Installation of Sprinkler Systems in Residential Occupancies Up to and Including Four Stories in Height" |

2820 [~~(3)~~] (2) In NFPA, Section 13D-07, new sections are added as follows: "1.15 Reference
2821 to NFPA 13D. All references to NFPA 13D in the codes, ordinances, rules, or regulations
2822 governing NFPA 13D systems shall be read to refer to "modified NFPA 13D" to reference the
2823 NFPA 13D as amended by additional regulations adopted by Farmington City.

2824 4.9 Testing and Inspection of Systems. Testing and inspection of sprinkler systems shall

2825 include, but are not limited to:

2826 Residential:

2827 ROUGH Inspection-Verify Water Supply Piping Size and Materials, Installation of Riser,
2828 System Piping, Head Locations and all Components, Hydrostatic Pressure Test.

2829 FINAL Inspection-Inspectors Test Flow, System Completeness, Spare Parts, Labeling of
2830 Components and Signage, Alarm Function, Water Supply Pressure Verification.

2831 5.2.2.3 Exposed Piping of Metal. Exposed Sprinkler Piping material in rooms of dwellings
2832 shall be of Metal.

2833 EXCEPTIONS:

2834 a. CPVC Piping is allowed in unfinished mechanical and storage rooms only when specifically
2835 listed for the application as installed.

2836 b. CPVC Piping is allowed in finished, occupied rooms used for sports courts or similar uses
2837 only when the ceiling/floor framing above is constructed entirely of non-combustible materials,
2838 such as a concrete garage floor on metal decking.

2839 5.2.2.4 Water Supply Piping Material. Water Supply Piping from where the water line enters
2840 the dwelling adjacent to and inside the foundation to the fire sprinkler contractor
2841 point-of-connection shall be metal, suitable for potable plumbing systems. See Section 7.1.4
2842 for valve prohibition in such piping. Piping down stream from the point-of-connection used in
2843 the fire sprinkler system, including the riser, shall conform to NFPA 13D standards.

2844 5.4 Fire Pump Disconnect Signs. When installing a Fire Pump, Red Plastic Laminate Signs
2845 shall be installed in the electrical service panel, if the pump is wired separately from the main
2846 disconnect. These signs shall state: "Fire Pump Disconnect ONLY" and "Main Breaker DOES
2847 NOT Shut Off Fire Pump".

2848 7.1.4 Valve Prohibition. NFPA 13D, Section 7.1 is hereby modified such that NO VALVE is
2849 permitted from the City Water Meter to the Fire Sprinkler Riser Control.

2850 7.6.1 Mandatory Exterior Alarm. Every dwelling that has a fire sprinkler system shall have an
2851 exterior alarm, installed in an approved location. The alarm shall be of the combination
2852 horn/strobe or electric bell/strobe type, approved for outdoor use.

2853 8.1.05 Plan Preparation Identification. All plans for fire sprinkler systems, except for
2854 manufacturer's cut sheets of equipment, shall include the full name of the person who prepared
2855 the drawings. When the drawings are prepared by a registered professional engineer, the
2856 engineer's signature shall also be included.

2857 8.7 Verification of Water Supply:

2858 8.7.1 Fire Flow Tests: Fire Flow Tests for verification of Water Supply shall be conducted and
2859 witnesses for all applications other than residential, unless directed otherwise by the Chief. For
2860 residential Water Supply, verification shall be determined by administrative procedure.

2861 8.7.2 Accurate and Verifiable Criteria. The design calculations and criteria shall include an
2862 accurate and verifiable Water Supply.

2863 Section 41. Section **15A-6-101** is enacted to read:

2864 **CHAPTER 6. ADDITIONAL CONSTRUCTION REQUIREMENTS**

2865 **Part 1. Nitrogen Oxide Emission Limits for Natural Gas-Fired Water Heaters**

2866 **15A-6-101. Title.**

2867 (1) This chapter is known as "Additional Construction Requirements."

2868 (2) This part is known as "Nitrogen Oxide Emission Limits for Natural Gas-Fired
2869 Water Heaters."

2870 Section 42. Section **15A-6-102** is enacted to read:

2871 **15A-6-102. Nitrogen Oxide emission limits for natural gas-fired water heaters.**

2872 (1) As used in this section:

2873 (a) "BTU" means British Thermal Unit.

2874 (b) (i) "Heat input" means the heat of combustion released by fuel burned in a water
2875 heater based on the heating value of the fuel.

2876 (ii) "Heat input" does not include the enthalpy of a water heater's incoming combustion
2877 air.

2878 (c) "Heat output" means the enthalpy of a water heater's working fluid output.

2879 (d) "Natural gas-fired water heater" means a device that heats water:

2880 (i) using natural gas combustion;

2881 (ii) for use external to the device at a pressure that is less than or equal to 160 pounds
2882 per square inch gage; and

2883 (iii) to a thermostatically controlled temperature less than or equal to:

2884 (A) 210 degrees Fahrenheit; or

2885 (B) 99 degrees Celsius.

2886 (e) "ppm" means parts of Nitrogen Oxide per million parts of water heater air output.

2887 (f) "Recreational vehicle" means the same as that term is defined in Section [13-14-102](#).

2888 (2) Subject to Subsection (6), a person may not sell or install a natural gas-fired water
2889 heater with an emission rate greater than the following limits:

2890 (a) for a water heater that has a heat input of less than or equal to 75,000 BTU per hour
2891 that is not installed in a mobile home, a limit of:

2892 (i) 10 nanograms per Joule of heat output; or

2893 (ii) 15 ppm, corrected to 3% oxygen;

2894 (b) for a water heater that has a heat input of greater than 75,000 BTU per hour and less
2895 than 2,000,000 BTU per hour that is not installed in a mobile home, a limit of:

2896 (i) 10 nanograms per Joule of heat output; or

2897 (ii) 20 ppm, corrected to 3% oxygen;

2898 (c) for a water heater installed in a mobile home, a limit of:

2899 (i) 40 nanograms per Joule of heat output; or

2900 (ii) 20 ppm, corrected to 3% oxygen;

2901 (d) for a pool or spa water heater with a heat input that is less than or equal to 400,000
2902 BTU per hour, a limit of:

2903 (i) 40 nanograms per Joule of heat output; or

2904 (ii) 55 ppm, corrected to 3% oxygen; and

2905 (e) for a pool or spa water heater with a heat input of greater than 400,000 BTU per
2906 hour and less than 2,000,000 BTU per hour, a limit of:

2907 (i) 14 nanograms per Joule of heat output; or

2908 (ii) 55 ppm, corrected to 3% oxygen.

2937 (iii) is capable of withstanding fluid pressure created by fresh concrete; and
2938 (b) the project is designed and stamped by a structural engineer licensed in the state.

2939 Section 44. Section **15A-6-202** is enacted to read:

2940 **15A-6-202. Non-polyurethane insulating concrete forms.**

2941 (1) Notwithstanding any other provision of this title, a governing body in the state that
2942 issues a building permit may not:

2943 (a) deny issuing a building permit to a project solely because the project uses non-
2944 polyurethane insulating concrete form block that complies with Subsection (2); or

2945 (b) require a project to apply additional flame retardants to the surface of non-
2946 polyurethane insulating concrete form block that has a flame spread that is less than or equal to
2947 25.

2948 (2) A project may use non-polyurethane insulating concrete form block if:

2949 (a) the non-polyurethane insulating concrete form block is manufactured using foam
2950 plastic insulation that complies with applicable requirements in Title 15A, State Construction
2951 and Fire Codes Act, for flame spread index and smoke development index;

2952 (b) the non-polyurethane insulating concrete form block complies with any other
2953 requirements applicable to insulating concrete forms in Title 15A, State Construction and Fire
2954 Codes Act; and

2955 (c) the project is designed and stamped by a structural engineer who is licensed in the
2956 state.

2957 Section 45. Section **58-11a-502** is amended to read:

2958 **58-11a-502. Unlawful conduct.**

2959 Unlawful conduct includes:

2960 (1) practicing or engaging in, or attempting to practice or engage in activity for which a
2961 license is required under this chapter unless:

2962 (a) the person holds the appropriate license under this chapter; or

2963 (b) an exemption in Section [58-1-307](#) or [58-11a-304](#) applies;

2964 (2) knowingly employing any other person to engage in or practice or attempt to

2965 engage in or practice any occupation or profession licensed under this chapter if the employee
2966 is not licensed to do so under this chapter or exempt from licensure;

2967 (3) touching, or applying an instrument or device to the following areas of a client's
2968 body:

2969 (a) the genitals or the anus, except in cases where the patron states to a licensee that the
2970 patron requests a hair removal procedure and signs a written consent form, which must also
2971 include the witnessed signature of a legal guardian if the patron is a minor, authorizing the
2972 licensee to perform a hair removal procedure; or

2973 (b) the breast of a female patron, except in cases in which the female patron states to a
2974 licensee that the patron requests breast skin procedures and signs a written consent form, which
2975 must also include the witnessed signature of a parent or legal guardian if the patron is a minor,
2976 authorizing the licensee to perform breast skin procedures;

2977 (4) using or possessing a solution composed of at least 10% methyl methacrylate on a
2978 client;

2979 (5) performing an ablative procedure as defined in Section 58-67-102;

2980 (6) when acting as an instructor regarding a service requiring licensure under this
2981 chapter, for a class or education program where attendees are not licensed under this chapter,
2982 failing to inform each attendee in writing that:

2983 (a) taking the class or program without completing the requirements for licensure under
2984 this chapter is insufficient to certify or qualify the attendee to perform a service for
2985 compensation that requires licensure under this chapter; and

2986 (b) the attendee is required to obtain licensure under this chapter before performing the
2987 service for compensation; or

2988 (7) failing as a salon or school where nail technology is practiced or taught to maintain
2989 a source capture system required under [~~Section 15A-3-401~~] Title 15A, State Construction and
2990 Fire Codes Act, including failing to maintain and clean a source capture system's air filter
2991 according to the manufacturer's instructions.

2992 Section 46. **Repealer.**

- 2993 This bill repeals:
- 2994 Section **15A-3-106.5**, Amendments to Chapter 15 of IBC.
- 2995 Section 47. **Effective date.**
- 2996 This bill takes effect on July 1, 2016.