- 1 HB40
- 2 188868-1
- 3 By Representative South
- 4 RFD: Transportation, Utilities and Infrastructure
- 5 First Read: 09-JAN-18
- 6 PFD: 11/28/2017

1	188868-1:n:11/17/2017:FC/tgw LSA2017-3526
2	
3	
4	
5	
6	
7	
8	SYNOPSIS: Existing law provides for size and weight
9	restrictions on certain vehicles operating in
10	Alabama.
11	This bill would further provide for the
12	length of certain vehicles and would allow motor
13	vehicle weight increases for vehicles that have
14	conversion equipment installed allowing the vehicle
15	to operate on compressed natural gas or compressed
16	liquefied gas.
17	
18	A BILL
19	TO BE ENTITLED
20	AN ACT
21	
22	To amend Section 32-9-20, Code of Alabama 1975, as
23	last amended by Act 2017-442, 2017 Regular Session, relating
24	to the restrictions on the operation of certain motor
25	vehicles; to further provide for the length of certain
26	vehicles; and to allow for weight increases for vehicles
27	having conversion equipment installed that allows the webicle

to operate on compressed natural gas or compressed liquefied gas.

BE IT ENACTED BY THE LEGISLATURE OF ALABAMA:

Section 1. Section 32-9-20, Code of Alabama 1975, as last amended by Act 2017-442, 2017 Regular Session, is amended to read as follows:

"§32-9-20.

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

- "(a) It shall be unlawful for any person to drive or move on any highway in this state any vehicle or vehicles of a size or weight except in accordance with the following:
- "(1) WIDTH. Vehicles and combinations of vehicles, operating on highways with traffic lanes 12 feet or more in width, shall not exceed a total outside width, including any load thereon, of 102 inches, exclusive of mirrors or other safety devices approved by the State Transportation Department. The Director of the State Transportation Department may, in his or her discretion, designate other public highways for use by vehicles and loads with total outside widths not exceeding 102 inches, otherwise; vehicles and combinations of vehicles, operating on highways with traffic lanes less than 12 feet in width, shall not exceed a total outside width, including any load thereon, of 96 inches, exclusive of mirrors or other safety devices approved by the State Transportation Department. No passenger vehicle shall carry any load extending beyond the line of the fenders. No vehicle hauling forest products or culvert pipe on any highway in this state shall have a load exceeding 102 inches in width.

"(2) HEIGHT. No vehicle or semitrailer or trailer
shall exceed in height 13 1/2 feet, including load.

3

4

5

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

"(3) LENGTH. No vehicle shall exceed in length 40 feet; except, that the length of a truck-semitrailer combination, semitrailers, including load, used in a truck tractor-semitrailer combination, shall not exceed 57 feet; semitrailers and trailers, including load, used in a truck tractor-semitrailer-trailer combination, shall not exceed 28 1/2 feet each; and motor vehicles designed, used, or maintained primarily as a mobile dwelling, office, or commercial space, commonly called motor homes, shall not exceed 45 feet. Semitrailers exceeding 53 1/2 feet shall only be operated on highways designated pursuant to Section 32-9-1 and shall only be operated when the distance between the kingpin of the semitrailer and the rearmost axle or a point midway between the two rear axles, if the two rear axles are tandem axles, does not exceed 41 feet and if the semitrailer is equipped with a rear underride guard of a substantial construction consisting of a continuous lateral beam extending to within four inches of the lateral extremities of the semitrailer and located not more than 22 inches from the surface as measured with the semitrailers empty and on a level surface. For purposes of enforcement of this subdivision, lengths of semitrailers and trailers refer to the cargo carrying portion of the unit. Truck tractor units used exclusively in combinations transporting motor vehicles may directly carry a portion of the cargo, provided that the

combinations are restricted to truck tractor-semitrailer combinations only and provided further that the overall length of these particular combinations shall not exceed 65 feet; except that the overall length of stinger-steered type units shall not exceed 75 80 feet. No truck tractor-semitrailer combination used exclusively for transporting motor vehicles shall carry any load extending more than three four feet beyond the front or four six feet beyond the rear of the combination. No other vehicle operated on a highway shall carry any load extending more than a total of five feet beyond both the front and rear, inclusive, of the vehicle.

"(4) WEIGHT.

"a. The gross weight imposed on the highway by the wheels of any one axle of a vehicle shall not exceed 20,000 pounds, or such other weight, if any, as may be permitted by federal law to keep the state from losing federal funds; provided, that inadequate bridges shall be posted to define load limits.

"b. For the purpose of this section, an axle load shall be defined as the total load transmitted to the road by all wheels whose centers are included between two parallel transverse vertical planes 40 inches apart, extending across the full width of the vehicle.

"c. Subject to the limit upon the weight imposed upon the highway through any one axle as set forth herein, the total weight with load imposed upon the highway by all the axles of a vehicle or combination of vehicles shall not exceed

1	the gross weight given for the respective distances between
2	the first and last axle of the vehicle or combination of vehi-
3	cles, measured longitudinally to the nearest foot as set forth
4	in the following table:

COMPUTED GROSS WEIGHT TABLE

5

6 For various spacings of axle groupings

7	Distance in feet between first	Maximum load in
8	and last axles of vehicle or	pounds on all the
9	combination of vehicles	axles

10		2 axles	3 axles	4 axles	5 axles	6 axles
11	8 or	36,000	42,000	42,000		
12	less					
13	9	38,000	42,500	42,500		
14	10	40,000	43,500	43,500		
15	11		44,000	44,000		
16	12		45,000	50,000	50,000	
17	13		45,500	50,500	50,500	
18	14		46,500	51,500	51,500	
19	15		47,000	52,000	52,000	
20	16		48,000	52,500	58,000	58,000

1	17	48,500	53,500	58,500	58 , 500
2	18	49,500	54,000	59,000	59,000
3	19	50,000	54,500	60,000	60,000
4	20	51,000	55,500	60,500	66,000
5	21	51,500	56,000	61,000	66,500
6	22	52,500	56,500	61,500	67 , 000
7	23	53,000	57,500	62,500	68,000
8	24	54,000	58,000	63,000	68 , 500
9	25	54,500	58,500	63,500	69,000
10	26	56,000	59,500	64,000	69,500
11	27	57,000	60,000	65,000	70,000
12	28	59,000	60,500	65,500	71,000
13	29	60,000	61,500	66,000	71,500
14	30		62,000	66,500	72 , 000
15	31		63,500	67,000	72 , 500
16	32		64,500	68,000	73 , 500
17	33		65,000	69,000	74,000
18	34		65,500	70,000	74 , 500
19	35		66,500	71,000	75 , 000
20	36		67,000	72,000	76 , 000
21	37		68,000	73,000	77,000
22	38		69,000	74,000	78 , 000

1	39	70,000	75,000	79 , 000
2	40	71,000	76,000	80,000
3	41	72,000	77,000	81,000
4	42	73,000	78 , 000	82,000
5	43	74,000	79,000	83,000
6	44 and	75,000	80,000	84,000
7	over			

"Except as provided by special permits, no vehicle or combination of vehicles exceeding the gross weights specified above shall be permitted to travel on the public highways within the State of Alabama.

"No vehicle or combination of vehicles shall be permitted to operate on any portion of the Interstate Highway System of Alabama that shall have a greater weight than 20,000 pounds carried on any one axle, including all enforcement tolerances, or with a tandem axle weight in excess of 34,000 pounds, including all enforcement tolerances, or with an overall gross weight on a group of two or more consecutive axles produced by application of the following formula:

20 W=500 LN + 12N + 36
21 N-1

where W = overall gross weight on any group of twoor more consecutive axles to the nearest 500 pounds, L =distance in feet between the extreme of any group of two or more consecutive axles, and N = number of axles in group under consideration; except, that two consecutive sets of tandem axles may carry a gross load of 34,000 pounds each, provided the overall distance between the first and last axles of the consecutive sets of tandem axles is 36 feet or more; provided, that the overall gross weight may not exceed 80,000 pounds, including all enforcement tolerances. Nothing in this section shall be construed as permitting size or weight limits on the National System of Interstate and Defense Highways in this state in excess of those permitted under 23 U.S.C. Section 127. If the federal government prescribes or adopts vehicle size or weight limits greater than or less than those now prescribed by 23 U.S.C. Section 127 for the National System of Interstate and Defense Highways, the increased or decreased limits shall become effective on the National System of Interstate and Defense Highways in this state. Nothing in this section shall be construed to deny the operation of any vehicle or combination of vehicles that could be lawfully operated upon the highways and roads of this state on January 4, 1975.

1

2

3

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

"d. For purposes of enforcement of this subdivision, all weights less than or equal to the sum of the weight otherwise prescribed by this subdivision, plus an additional

weight to be calculated by multiplying the weight prescribed by this subdivision by one-tenth (.10) that shall represent a scale or enforcement tolerance, shall be deemed to be in compliance with the requirements of this section, and shall not constitute violations thereof. No evidence shall be admitted into evidence or considered by the trier of fact in any civil action unless the evidence proffered would tend to prove that the weight of the vehicle exceeded the amount provided in this subsection. Nothing in this paragraph d. shall restrict or affect the right of any defendant to place in evidence such evidence tending to prove the defendant was in compliance with this section.

"e. Dump trucks, dump trailers, concrete mixing trucks, fuel oil, gasoline trucks, and trucks designated and constructed for special type work or use shall not be made to conform to the axle spacing requirements of paragraph (4)c of this section; provided, that the vehicle shall be limited to a weight of 20,000 pounds per axle plus scale tolerances; and, provided further, that the maximum gross weight of the vehicles shall not exceed the maximum weight allowed by this section for the appropriate number of axles, irrespective of the distance between axles, plus allowable scale tolerances. All axles shall be brake equipped. Trucks delivering asphalt plant mix which do not exceed the maximum allowable gross weight and operate within 50 miles of their home base shall not be required to conform to the requirements of paragraph (4)a of this section. Concrete mixing trucks which operate

within 50 miles of their home base and do not exceed the maximum allowable gross weight shall not be required to conform to the requirements of paragraph (4)a of this section. It shall be a violation if the vehicles named under this subdivision travel upon bridges designated and posted by the Transportation Director as incapable of carrying the load.

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

"f. If the driver of any vehicle can comply with the weight requirements of this section by shifting or equalizing the load on all wheels or axles and does so when requested by the proper authority, the driver shall not be held to be operating in violation of this section.

"q. When portable scales are used in the enforcement of this section, the axles of any vehicle described or commonly referred to as tandem or triaxle rigs or units (that is, vehicles having two or more axles in addition to a steering axle), the group of tandem or triaxles shall be weighed simultaneously, and the total weight so derived shall be divided by the number of axles weighed in the group to arrive at the per axle weight, except that if any one axle in the group exceeds 20,000 pounds in weight, it shall not exceed the weight of any other axle in the group by more than 50 percent. When portable scales are used to determine the weight of a vehicle pursuant to this section, the operator of the vehicle will be permitted to move the vehicle to the nearest platform scales certified by the Department of Agriculture and Industries and operated by a bonded operator within a distance of 10 highway miles, accompanied by an enforcement officer to

verify the accuracy of the portable scales used in determining the vehicle weight. If the weight of the vehicle is shown by the platform scales to be within the legal limits of this section, the operator of the vehicle shall not be held to be in violation of this section.

"h. The governing body of a county, by appropriate resolution, may authorize limitations less than those prescribed herein for vehicles operated upon the county highways of the county.

- "i. The State Transportation Department may post or limit any road or bridge to weights less than those prescribed by this section. It is the legislative intent and purpose that this section be rigidly enforced by the State Transportation Department, the Alabama State Law Enforcement Agency and any other authorized law enforcement officers of the state, any county, or city and incorporated towns.
- "j. Two and three axle vehicles being used exclusively for the purpose of transporting agricultural commodities or products to and from a farm and for agricultural purposes relating to the operation and maintenance of a farm by any farmer, custom harvester or husbandman may not be made to conform to the axle requirements of paragraph (4)a of this section or the gross weight requirements of paragraph (4)c of this section.
- "(b)(1) Any vehicle utilizing an auxiliary power or idle reduction technology unit in order to promote reduction of fuel use and emissions because of engine idling shall be

allowed an additional 400 pounds total to the gross, axle, tandem, or bridge formula weight limits defined in this section.

- "(2) To be eligible for the exception provided in this subsection, the operator of the vehicle must provide written proof or certification of the weight of the auxiliary power unit (APU) and demonstrate or certify the idle reduction technology is fully functional at all times.
- "(3) Written proof or certification of the weight of the APU must be available to law enforcement officers if the vehicle is found in violation of applicable weight laws. The weight allowed cannot exceed 400 pounds or the actual weight proven or certified, whichever is less.
- "(4) It is the intent of this subsection to apply at the state highway level the weight limit increase for vehicles using a functioning auxiliary power or idle reduction technology as provided in the Federal Energy Policy Act of 2005.
- "(c) (1) Any motor vehicle, if operated by an engine fueled primarily by natural gas, may exceed any vehicle weight limit, up to a maximum gross vehicle weight of 82,000 pounds, under this section by an amount that is equal to the difference between:
- "a. The weight of the vehicle attributable to the natural gas tank and fueling system carried by that vehicle; and

1	"b. The weight of a comparable diesel tank and
2	<pre>fueling system.</pre>
3	"(2) This subsection applies on federal interstate
4	highways to the weight limit increases for vehicles using an
5	EPA certified natural gas engine or an EPA approved conversion
6	unit installed on the vehicle which allows the vehicle to
7	operate primarily on compressed natural gas or liquefied
8	natural gas."
9	Section 2. This act shall become effective on the
10	first day of the third month following its passage and
11	approval by the Governor, or its otherwise becoming law.